FROM-SAKURA OF AMERICA

N.A.: Not Applicable

+5104750973

T-181 P.002/003 F-517

MATERIAL SAFETY DATA SHEET

(Required under OSHA's Hazard Communication Standard 29 CFR 1910.1200

Page 1 of 2 K #: XLP12, XLP16, XLP25, XLP36, XLP50	
Telephone Number: +81 (0)6 - 6910 - 8824 (Japan)	
FAX Number: +81 (0)6 - 6910 - 8834 (Japan)	
Publisher: Takahiro Shirai	
OSHA PEL ACGIH TLV	

All colors of this product fulfill the requirement of the European Standard EN71-3.

Section III - Physical / Char	mical Characteristics		
Boiling Point:	N.D.	Specific Gravity: (HzO = 1 at 26°C)	1<
Vapor Pressure: (mmHg)	N.D.	Melting Point:	Abut 70°C
Vapor Density: (Air = 1)	N.D.	Evaporation Rate: (Butyl Acetate = 1)	N.D.
Solublity in Water	Non solublity	· · · · · · · · · · · · · · · · · · ·	
Appearance and Odor	Stick, Waxy odor		
Section IV - Fire and Explor	sion Hezard Data		
Flash Point (Method Uses): N.D.		Flammable Limits: LEL: N.D. UEL;	N.D.
Extinguish Media:			
In case of fire, use	water spray, foam or d	ry chemical powder.	•
Special Fire Fighting Procedu			
	No apecial mo	ntion	
Unusual Fire and Explosion F Toxic gases(carbon mus		sulfur oxide) will form upon com	hustion,

N.D.: Not Determined

Section VIII - Control Measures Respiratory Protection (Specify Type): Not necessary Local Exhaust: Special: Not necessary Ventilation Not necessary Mechanical (General): Other: Not necessary Not necessary Protective Gloves: Eye Protection: Not necessary Not necessary Other Protective Clothing or Equipment: Not necessary Work / Hygienic Practices: In the case of stuck to the skin, rinso with running water and soap.

This information horein is given good faith, but no warranty, expressed or implied is made.