FROM-SAKURA OF AMERICA

3378.

+5104750973

T-181 P.002/003 F-511

MATERIAL SAFETY DATA SHEET

(Required under OSHA's Hazard Communication Standard 29 CFR 1910.1200

(XLP) Page 1 of 2 Cray-Pas Expressionist Saries: (XLP numbers) - all 48 colors. Set stock #: XLP12, XLP16, XLP25, XLP36, XLP50 opersions in Post xiPost x Section I Manufacturer's Name: Telephone Number: Sakura Color Products Corporation +81 (0)6 - 6910 - 8824 (Japan) Address: **FAX Number:** 1-6-20, Morinomiya Chuo, Chuo-ku, Osaka, 540-8508 Japan +81 (0)6 - 6910 - 8834 (Japan) **Published Date:** Publisher: December 20, 1999 Takahiro Shirai Section II - Hazardous Ingredients / Identity Information Hazardous Components CAS No. WT % OSHA PEL **ACGIH TLV**

This product is approved by ACMI (The Art & Creative Materials Institute, Inc.), and carries the "AP" seal of non-toxic approval in USA.

All colors of this product fulfill the requirement of the European Standard EN71-3.

Section III - Physical / Chem	tical Characteristic	28	
Boiling Point:	N.D.	Specific Gravity: (HzO = 1 at 26°C)	1<
Vapor Pressure: (mmHg)	N.D.	Meiting Point:	Abut 70°C
Vapor Density: (Air = 1)	N.D.	Evaporation Rate: (Butyl Acetate = 1)	N.D.
Solubility in Water	Non solubility		
Appearance and Odor	Stick, Waxy odd	or	
Section IV – Fire and Explos	ion Hazard Data		
Flash Point (Method Uses): N.D.		Flammable Limits; LEL: N.D. UEL; N.D.	
Extinguish Media;			
In case of fire, use	water spray, foam	or dry chemical powder.	•
Special Fire Fighting Procedu	es: No special	mention	
Unusual Fire and Explosion H Toxic gases(carbon mon		ides, sulfur oxide) will form upon con	hustion,
N.A.: Not Applicable	N.D.: Not Determined		

This information herein is given good faith, but no warranty, expressed or implied is made.

AND .