

1382

SANFORD CORPORATION
2740 WASHINGTON BLVD.
BELLWOOD, IL. 60104

EMERGENCY TEL: 1-800-228-5635

Sanford Corporation has been advised by counsel that the OSHA Hazard Communication Standard does not apply to the Sanford product described in this MSDS. The reason for this exemption is contained in 29 CFR Part 1910.1200 (h) (6) (vii) as amended August 26, 1987 per Federal Register Vol. 52, No. 163, p 31877-31878. The information contained in this MSDS is forwarded to you for your information but is not meant to imply that the product is covered by the Hazard Communication Standard nor is the MSDS meant to comply with all requirements of the Hazard Communication Standard.

DATE OF LAST REVISION: October 15, 1992

DOCUMENT SEQUENCE NO.: 191-02

97-10472 A-H

1. IDENTIFICATION:

NAME: Sharpie® Ultra Fine Point

COLORS: Red, Blue, Green, Yellow, Orange, Brown, Purple

#37074

2. COMPOSITION:

Dyes

Solvents: n-propanol (71-23-8)
n-butanol (71-36-3)
diacetone alcohol (123-42-2)

3. PHYSICAL DATA:

(for n-propanol)

BOILING POINT: 207°F
SPECIFIC GRAVITY: 0.8044 at 20/20°C (water = 1)
VAPOR PRESSURE: 13 mm Hg at 20°C
VAPOR DENSITY: 2.07 at 20°C (air = 1)
EVAPORATION RATE: 1.3 (butyl acetate = 1)
SOLUBILITY IN WATER: complete
APPEARANCE/ODOR: clear, colorless mobile liquid with mild alcohol odor
FLASH POINT: 84°F Tag Open Cup (ASTM D 1310)
LOWER FLAMMABILITY LIMIT: 2.2% in air by volume
UPPER FLAMMABILITY LIMIT: 14.0% in air by volume

V#075993

11/19/96