

To: *Carole Warko*
 From: *Maintenance Dept*

000933



Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List) Limestone: Crushed Stone
 Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name <u>W.F. Saunders & Sons, Inc.</u>	Emergency Telephone Number <u>(315) 469-3217</u>
Address (Number, Street, Cty, State, and ZIP Code) <u>P.O. Drawer A</u>	Telephone Number for Information
<u>Nedrow, NY 13120</u>	Date Prepared <u>3/20/88</u>
	Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA-PEL	ACGIH-TLV	Other Limits Recommended
<u>Limestone (Ca CO₃); calcium carbonate</u>			<u>Total Dust = 30 mg/m³/% Quartz +3</u>
<u>Crystalline Silica (Si O₂; quartz)</u>			<u>Respirable Dust = 10 mg/m³/% Quartz +2</u>

Section III — Physical/Chemical Characteristics

Boiling Point <u>NA</u>	Specific Gravity (H ₂ O = 1)	<u>2.5 to 3.0</u>
Vapor Pressure (mm Hg) <u>NA</u>	Melting Point	<u>NA</u>
Vapor Density (AIR = 1) <u>NA</u>	Evaporation Rate (Butyl Acetate = 1)	<u>0</u>
Solubility in Water <u>Negligible</u>		

Appearance and Odor
Grey, white and tan angular particles. No odor. Range in size from powder to boulders

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) <u>NA</u>	Flammable Limits <u>NA</u>	LEL	UEL
Extinguishing Media <u>NA</u>			
Special Fire Fighting Procedures <u>NA</u>			

Unusual Fire and Explosion Hazards
None

