



K23731

MATERIAL SAFETY DATA SHEET

Share Corporation
P.O. Box 245013
Milwaukee, WI 53224



GENERAL INFORMATION NUMBER: (414) 355-4000
EMERGENCY TELEPHONE NUMBER: (800) 776-7192
CHEMTREC: (800) 424-9300

REVISION DATE: December 27, 1999
DATE OF ISSUE: March 20, 2001

I - Product Identification

Rubber In A Can

PRODUCT CODE: 8002

CHEMICAL FORMULATION: Pressurized rubber coating.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 2

FLAMMABILITY: 4

REACTIVITY: 0

HAZARD RATING: 4 - Extreme;

3 - High;

2 - Moderate;

1 - Slight;

0 - Insignificant

II - Hazardous Ingredients

Values reported as TWA unless noted.

SUBSTANCE	APPROX %	OSHA PEL	ACGIH TLV	EPA 40 CFR:			CAS#
				302	355	372	
Aliphatic Petroleum Solvent	20.0-25.0	300 ppm	300 ppm	N	N	Y	64742-89-8
Calcium Carbonate (as total dust)	20.0-25.0	15 ppm	10 ppm	N	N	N	1317-65-3
Carbon Black (nuisance dust)	1.00-5.00	3.5 mg/m ³	3.5 mg/m ³	N	N	N	1333-86-4
Toluene	10.0-15.0	100 ppm	50 ppm (skin)	Y	N	Y	108-88-3
Liquified Petroleum Gas	25.0-30.0	1000 ppm	1000 ppm	N	N	N	68476-85-7

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit
 N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No
 302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).
 355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).
 372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): N/D

SPECIFIC GRAVITY (WATER = 1): < 1.0

VAPOR PRESSURE (psig) @130°F: 90

VOC CONTENT (% by weight): 65.70

VAPOR DENSITY (AIR = 1): > 1.0

EVAPORATION RATE (ETHER = 1): < 1.0

SOLUBILITY IN WATER: Negligible

pH: N/A

APPEARANCE AND ODOR: Thick black liquid; petroleum odor.

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): < 0 (concentrate) (TEST METHOD): T.O.C.

NFPA 30B Rating: 2

FLAMMABLE LIMITS IN AIR (VOLUME %) UPPER: 1.8 LOWER: 9.2

FLAME EXTENSION: 18"

EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog to prevent vapor pressure buildup. Firefighters should be equipped with full protective gear including self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD: At elevated temperatures (over 54°C-130°F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

PRODUCT NAME: Rubber In A Can

PRODUCT CODE: 8002

V - Reactivity Data

STABILITY: Stable

INCOMPATIBILITY: Strong oxidizers

CONDITIONS TO AVOID: Do not store above 54°C-130°F. Keep away from heat, direct sunlight, open flames or sparks. Dropping of containers may cause bursting.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, oxides of Sulfur and additional toxic chemicals may be formed in small amounts.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None

VI - Health Hazard Data

ROUTES OF ENTRY INHALATION: X EYE CONTACT: X SKIN CONTACT: X INGESTION: X

INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None

EFFECTS OF OVEREXPOSURE

IF IN EYES: Irritation.

IF ON SKIN: Dermatitis or oil acne with prolonged exposure.

IF SWALLOWED: May cause abdominal spasms and other symptoms that parallel over-exposure from inhalation. Aspiration of material into the lungs can cause chemical pneumonitis, which may be fatal.

IF INHALED: Headache, dizziness, nausea, and incoordination.

EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush under eyes and eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Remove contaminated clothing. Wash with soap and water. If irritation persists, obtain medical attention.

IF SWALLOWED: Do not induce vomiting. Obtain medical attention.

IF INHALED: Remove person to fresh air and provide oxygen if breathing is difficult. If breathing has stopped, administer artificial respiration. Obtain medical attention.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition and ventilate area. Soak up spilled material with inert absorbent material and place in a properly labeled closed container.

WASTE DISPOSAL METHOD: Consult local environmental authorities. Dispose of empty cans in non-incinerated trash only.

VIII - Special Protection Information

RESPIRATORY PROTECTION: None required if good ventilation is maintained. If recommended exposure limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.

VENTILATION

LOCAL: Recommended

MECHANICAL: Not required

PROTECTIVE GLOVES: Chemical resistant

EYE PROTECTION: Safety glasses.

OTHER PROTECTIVE EQUIPMENT: Protective clothing.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place away from heat or open flame. Keep container tightly closed when not in use.

OTHER PRECAUTIONS: Keep out of reach of children. Do not puncture or incinerate cans.

IX - Transportation Information

DOT INFORMATION: Consumer Commodity ORM-D

DOT PROPER SHIPPING NAME: Consumer Commodity

DOT CLASS: ORM-D

DOT ID NUMBER: None

DOT PACKING GROUP: None

REVISION DATE: December 27, 1999


Preparers Initials: PMR

DATE OF ISSUE: March 20, 2001

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Share Corporation assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.

MATERIAL SAFETY DATA SHEET

Share Corporation
P.O. Box 245013
Milwaukee, WI 53224



GENERAL INFORMATION NUMBER: (414) 355-4000
EMERGENCY TELEPHONE NUMBER: (800) 776-7192
CHEMTREC: (800) 424-9300

REVISION DATE: January 2, 2003
DATE OF ISSUE: February 11, 2003

I - Product Identification

Paint Stripper Aerosol

PRODUCT CODE: 8580

CHEMICAL FORMULATION: Pressurized solvent based cleaner.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 3

FLAMMABILITY: 4

REACTIVITY: 1

HAZARD RATING: 4 - Extreme;

3 - High;

2 - Moderate;

1 - Slight;

0 - Insignificant

II - Hazardous Ingredients

Values reported as TWA unless noted.

SUBSTANCE	APPROX %	OSHA PEL	ACGIH TLV	EPA 40 CFR:			CAS #
				302	355	372	
Methylene Chloride	40.0-60.0	25 ppm	25 ppm	Y	N	Y	75-09-2
Toluene	10.0-20.0	100 ppm	100 ppm	Y	N	Y	108-88-3
Methanol	1.00-5.00	200 ppm	200 ppm	Y	N	Y	67-56-1
Liquid Petroleum Gas	5.00-10.0	1000 ppm	1000 ppm	N	N	N	68476-85-7

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit
N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No
302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).
355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).
372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): 96

SPECIFIC GRAVITY (WATER = 1): 1.13

VAPOR PRESSURE (mm Hg): 50

VOC CONTENT (% by weight): ~ 45

VAPOR DENSITY (AIR = 1): > 1.0

EVAPORATION RATE (WATER = 1): N/D

SOLUBILITY IN WATER: Slight

pH: N/A

APPEARANCE AND ODOR: Clear to opaque liquid, mild sweet solvent odor.

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): -70 (concentrate) (TEST METHOD): T.O.C.

FLAME EXTENSION: N/D

FLAMMABLE LIMITS IN AIR (VOLUME %) UPPER: N/D

LOWER: N/D NFPA 30B Rating: 1

EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD: Extreme temperature above 120 °F may cause bursting.

V - Reactivity Data**STABILITY:** Stable**INCOMPATIBILITY:** Strong oxidizers, acids and bases & selected amines.**CONDITIONS TO AVOID:** Excess heat and open flame.**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may produce oxides of carbon; hydrogen chloride and phosgene.**HAZARDOUS POLYMERIZATION:** Will not occur.**CONDITIONS TO AVOID:** None**VI - Health Hazard Data****ROUTES OF ENTRY** **INHALATION: X** **EYE CONTACT: X** **SKIN CONTACT: X** **INGESTION: X**
INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS:

Methylene Chloride (CAS# 75-09-2)

EFFECTS OF OVEREXPOSURE**IF IN EYES:** Moderate irritation, pain, slight corneal injury.**IF ON SKIN:** Irritation, with prolonged or repeated exposure.**IF SWALLOWED:** Gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis.**IF INHALED:** Irritation of nasal and upper respiratory tract. Abusive or excessive inhalation may cause dizziness, nausea and other central nervous system effects.**EMERGENCY AND FIRST AID PROCEDURES****IF IN EYES:** Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.**IF ON SKIN:** Wash with soap and water. If irritation persists, obtain medical attention.**IF SWALLOWED:** Contact physician or poison control center immediately. Do not induce vomiting.**IF INHALED:** Remove person to fresh air. If breathing has stopped, administer artificial respiration.**VII - Spill or Leak Protection****STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Ventilate area and remove all sources of ignition. Contain spill. Soak up spilled material with inert absorbent material and place in a properly marked closed container for proper disposal.**WASTE DISPOSAL METHOD:** Consult local environmental authorities. Dispose of cans in non-incinerated trash only.**VIII - Special Protection Information****RESPIRATORY PROTECTION:** Use with adequate ventilation. Do not breathe vapors or mists. If recommended Exposure Limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.**VENTILATION****LOCAL:** Recommended**MECHANICAL:** Not required**PROTECTIVE GLOVES:** Chemical resistant.**EYE PROTECTION:** Safety glasses or chemical resistant gloves.**OTHER PROTECTIVE EQUIPMENT:** Protective clothing.**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Store in a cool, dry place away from heat or open flame. Do not expose to direct sunlight or store at temperatures above 120 °F.**OTHER PRECAUTIONS:** Keep out of reach of children. Do not puncture or incinerate container.**IX - Transportation Information (ground transportation only)****DOT PROPER SHIPPING NAME:** Consumer Commodity**DOT CLASS:** ORM-D**DOT ID NUMBER:** None**DOT PACKING GROUP:** None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: January 2, 2003**Prepared by:** PMR**DATE OF ISSUE:** February 11, 2003

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Share Corporation assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.