



SEP 18 1986

# MATERIAL SAFETY DATA SHEET

MSDS NUMBER **80,070-5** PAGE 1

<b>24 HOUR EMERGENCY ASSISTANCE</b>			<b>GENERAL MSDS ASSISTANCE</b>		
SHELL: 713-473-9461 CHEMTREC: 800-424-9300			SHELL: 713-241-4819		
ACUTE HEALTH 3	FIRE 1	REACTIVITY 0	HAZARD RATING	LEAST - 0 HIGH - 3	SLIGHT - 1 EXTREME - 4
*For acute and chronic health effects refer to the discussion in Section III					



SECTION I	NAME
PRODUCT	SHELLZONE(R) ANTIFREEZE LS
CHEMICAL NAME	ETHYLENE GLYCOL
CHEMICAL FAMILY	GLYCOL
SHELL CODE	32350 94010 94012

SECTION II-A		PRODUCT/INGREDIENT	
NO.	COMPOSITION	CAS NUMBER	PERCENT
P	SHELLZONE ANTIFREEZE	MIXTURE	100
1	ETHYLENE GLYCOL	107-21-1	84-94
2	DIETHYLENE GLYCOL	111-46-6	0-10
3	WATER	7732-18-5	2-4
4	INORGANIC/ORGANIC SALTS		2-4

SECTION II-B		ACUTE TOXICITY DATA	
NO.	ACUTE ORAL LD50	ACUTE DERMAL LD50	ACUTE INHALATION LC50
1	4.0 G/KG - RAT	19.5 G/KG - RABBIT	NONE
1	5.0 G/KG - RABBIT		
2	14.8 G/KG - RAT	11.9 G/KG - RABBIT	NONE

BASED UPON DATA AVAILABLE TO SHELL, COMPONENTS 3 AND 4 IN THIS PRODUCT ARE NOT HAZARDOUS UNDER OSHA HAZARD COMMUNICATION (29 CFR 1910.1200).

### SECTION III HEALTH INFORMATION

THE HEALTH EFFECTS NOTED BELOW ARE CONSISTENT WITH REQUIREMENTS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

**EYE CONTACT**  
BASED ON PRESENCE OF COMPONENT 1, PRODUCT IS MODERATELY TO SEVERELY IRRITATING TO THE EYES. VAPORS CAN ALSO CAUSE SEVERE EYE IRRITATION.

**SKIN CONTACT**  
BASED ON PRESENCE OF COMPONENTS 1 AND 2, PRODUCT IS MILDLY IRRITATING TO THE SKIN AND SLIGHTLY TOXIC ON PROLONGED OR REPEATED CONTACT.

**INHALATION**  
VAPORS ARE MILDLY TO MARKEDLY IRRITATING TO THE LUNGS DEPENDING ON THE EXPOSURE LEVEL.

**INGESTION**

PRODUCT MAY BE HARMFUL OR FATAL IF SWALLOWED; MAY PRODUCE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION AND KIDNEY DAMAGE WHICH MAY BE FATAL. INGESTION OF COMPONENT 2 MAY ALSO PRODUCE LIVER DAMAGE.

**SIGNS AND SYMPTOMS**

IRRITATION AS NOTED ABOVE. EARLY TO MODERATE CNS DEPRESSION MAY BE EVIDENCED BY GIDDINESS, HEADACHE, DIZZINESS AND NAUSEA; IN EXTREME CASES, UNCONSCIOUSNESS AND DEATH MAY OCCUR. KIDNEY DAMAGE MAY BE EVIDENCED BY CHANGES IN URINE OUTPUT, URINE APPEARANCE OR EDEMA (SWELLING FROM FLUID RETENTION). LIVER DAMAGE MAY BE EVIDENCED BY LOSS OF APPETITE, JAUNDICE (YELLOWISH SKIN COLOR) AND SOMETIMES PAIN IN THE UPPER ABDOMEN ON THE RIGHT SIDE.

**AGGRAVATED MEDICAL CONDITIONS**

PREEXISTING SKIN, EYE, AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. IMPAIRED KIDNEY AND LIVER FUNCTIONS FROM PREEXISTING DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

**OTHER HEALTH EFFECTS**

INTENTIONAL ABUSE, MISUSE OR OTHER MASSIVE EXPOSURE MAY CAUSE MULTIPLE ORGAN DAMAGE AND/OR DEATH.

SEE SECTION VI FOR ADDITIONAL INFORMATION.

-----  
**SECTION IV OCCUPATIONAL EXPOSURE LIMITS**  
-----

NO.	PEL/TWA	OSHA PEL/CEILING	TLV/TWA	ACGIH TLV/STEL	OTHER
1			50 PPM - CEILING		
1			10 MG/M3	20 MG/M3	

CEILING VALUE IS FOR EG VAPORS, OTHERS ARE FOR EG PARTICULATES.

-----  
**SECTION V EMERGENCY AND FIRST AID PROCEDURES**  
-----

**EYE CONTACT**

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.

**SKIN CONTACT**

FLUSH SKIN WITH WATER. IF IRRITATION OCCURS, GET MEDICAL ATTENTION.

**INHALATION**

REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION.

**INGESTION**

DO NOT GIVE LIQUIDS IF VICTIM IS UNCONSCIOUS OR VERY DROWSY. OTHERWISE, GIVE NO MORE THAN 2 GLASSES OF WATER AND INDUCE VOMITING BY GIVING 30CC (2 TABLESPOONS) SYRUP OF IPECAC.\* IF IPECAC IS UNAVAILABLE, GIVE 2 GLASSES OF WATER AND INDUCE VOMITING BY TOUCHING FINGER TO BACK OF VICTIM'S THROAT. KEEP VICTIM'S HEAD BELOW HIPS WHILE VOMITING. GET MEDICAL ATTENTION.

**NOTE TO PHYSICIAN**

IF VICTIM IS A CHILD, GIVE NO MORE THAN 1 GLASS OF WATER AND 15CC (1 TABLESPOON) SYRUP OF IPECAC. IF SYMPTOMS SUCH AS LOSS OF GAG REFLEX, CONVULSIONS OR UNCONSCIOUSNESS OCCUR BEFORE EMESIS, GASTRIC LAVAGE SHOULD BE CONSIDERED FOLLOWING INTUBATION WITH A CUFFED ENDOTRACHEAL TUBE.

-----  
**SECTION VI SUPPLEMENTAL HEALTH INFORMATION**  
-----

RARE CASE REPORTS OF ETHYLENE GLYCOL SENSITIZATION (ALLERGY) HAVE BEEN PUBLISHED BUT ALLERGY TO ETHYLENE GLYCOL IS NOT A COMMON PHENOMENON.

IN ONE STUDY, WHEN ETHYLENE GLYCOL WAS ADMINISTERED IN THE DIET AT DAILY DOSES UP TO 1.0 G/KG TO PREGNANT RATS, NO MATERNAL TOXICITY, NO EMBRYOTOXICITY NOR TERATOGENICITY WERE OBSERVED. IN A MORE RECENT STUDY, WHEN ETHYLENE GLYCOL WAS ADMINISTERED BY GAVAGE AT DAILY DOSES OF 1.25 G/KG AND ABOVE TO PREGNANT RATS, OR AT 750 MG/KG AND ABOVE TO PREGNANT MICE, THERE WAS AN INCREASE IN THE NUMBER OF MALFORMED FETUSES AT ALL DOSE LEVELS. EXCEPT AT THE LOWEST DOSE LEVEL IN MICE, THERE WAS ALSO EVIDENCE OF MATERNAL TOXICITY AT ALL DOSE LEVELS.

-----  
**SECTION XI ENVIRONMENTAL PROTECTION**  
-----

**SPILL OR LEAK PROCEDURES**

MAY BURN ALTHOUGH NOT READILY IGNITABLE. USE CAUTIOUS JUDGMENT WHEN CLEANING UP LARGE SPILLS. \*\*\* LARGE SPILLS \*\*\* WEAR RESPIRATOR AND PROTECTIVE CLOTHING AS APPROPRIATE. SHUT OFF SOURCE OF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIAL; DISPOSE OF PROPERLY. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE. \*\*\* SMALL SPILLS \*\*\* TAKE UP WITH AN ABSORBENT MATERIAL AND DISPOSE OF PROPERLY.

**WASTE DISPOSAL**

PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH LOCAL REGULATIONS.

**ENVIRONMENTAL HAZARDS**

KEEP OUT OF SURFACE WATERS, SEWERS, AND WATERWAYS ENTERING OR LEADING TO SURFACE WATERS. NOTIFY AUTHORITIES IF ANY EXPOSURE TO THE GENERAL PUBLIC OR ENVIRONMENT OCCURS OR IS LIKELY TO OCCUR.

-----  
**SECTION XII SPECIAL PRECAUTIONS**  
-----

STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM FLAMES AND HIGH TEMPERATURES.

WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE.

-----  
**SECTION XIII TRANSPORTATION REQUIREMENTS**  
-----

DEPARTMENT OF TRANSPORTATION CLASSIFICATION: NOT HAZARDOUS BY D.O.T. REGULATIONS

-----  
**SECTION XIV OTHER REGULATORY CONTROLS**  
-----

THE COMPONENTS OF THIS PRODUCT ARE LISTED ON THE EPA/TSCA INVENTORY OF CHEMICAL SUBSTANCES.

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, SHELL MAKES NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. SHELL ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.

DATE PREPARED: NOVEMBER 13, 1985

-----  
JOHN P. SEPEZI

**BE SAFE**

READ OUR PRODUCT  
SAFETY INFORMATION ...AND PASS IT ON  
(PRODUCT LIABILITY LAW  
REQUIRES IT)

SHELL OIL COMPANY  
PRODUCT SAFETY AND COMPLIANCE  
P. O. BOX 4320  
HOUSTON, TX 77210

SECTION VII PHYSICAL DATA

BOILING POINT: 330-340 (DEG F)	SPECIFIC GRAVITY: 1.1373 (H2O=1)	VAPOR PRESSURE: N/AV (MM HG)
MELTING POINT: N/AV (DEG F)	SOLUBILITY: COMPLETE (IN WATER)	VAPOR DENSITY: >1 (AIR=1)
EVAPORATION RATE (N-BUTYL ACETATE = 1): <0.01		POUR POINT: -40 DEG. F

APPEARANCE AND ODOR: BLUE GREEN, SLIGHTLY VISCOUS LIQUID. MILD ODOR.

SECTION VIII FIRE AND EXPLOSION HAZARDS

FLASH POINT AND METHOD: 246 DEG. F SETAFLASH	FLAMMABLE LIMITS % VOLUME IN AIR LOWER: N/AP UPPER: N/AP
---	---

EXTINGUISHING MEDIA  
USE WATER FOG, "ALCOHOL" FOAM, DRY CHEMICAL OR CO2.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS  
MATERIAL WILL NOT BURN UNLESS PREHEATED. DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR (HELMET WITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS), INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER.

SECTION IX REACTIVITY

STABILITY: STABLE HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS AND MATERIALS TO AVOID:  
KEEP AWAY FROM STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS  
CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

SECTION X EMPLOYEE PROTECTION

RESPIRATORY PROTECTION  
IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS (SEC. IV) USE A NIOSH-APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE. IN ACCORD WITH 29 CFR 1910.134 USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR OR AN AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS.

PROTECTIVE CLOTHING  
AVOID CONTACT WITH EYES. WEAR CHEMICAL GOGGLES IF THERE IS LIKELIHOOD OF CONTACT WITH EYES. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. WEAR CHEMICAL RESISTANT GLOVES AND OTHER CLOTHING AS REQUIRED TO MINIMIZE CONTACT. TEST DATA FROM PUBLISHED LITERATURE AND/OR GLOVE AND CLOTHING MANUFACTURERS INDICATE THE BEST PROTECTION IS PROVIDED BY NITRILE, NEOPRENE, PVC OR NATURAL RUBBER GLOVES.

ADDITIONAL PROTECTIVE MEASURES  
USE VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS. EYE WASH FOUNTAINS AND SAFETY SHOWERS SHOULD BE AVAILABLE FOR EMERGENCY USE.