


MATERIAL SAFETY DATA SHEET

For chemicals, coatings and related materials

DATE PREPARED: 3-19-87

Supercedes: 5/86

NAME : Sonneborn Building Products
ADDRESS: 7711 Computer Avenue
ADDRESS: Minneapolis, MN
ADDRESS:
ZIPCODE: 55435



EMERGENCY PHONE NUMBER
DAY: (612)-835-3434
NIGHT: CHEMTREC
(800)-424-9300
INFORMATION PHONE NUMBER
(612)-835-3434

Section I - Product

NUMBER: 11-495
NAME : SONNEBORN KURE-N-SEAL (BP 3635)
CLASS : COATING

H M I S Hazard Codes
Health: 2 Moderate
Flammability: 2 Moderate
Reactivity: 0 Minimal
Personal Protective Equipment: G

Section II - Hazardous Ingredients

Table with 5 columns: Ingredient, Percent by weight, C. A. S. Registry No., LEL, Vapor Pressure mm Hg @ 20 C. Rows include Aromatic Hydrocarbon Blend, Xylene, and Aliphatic petroleum Distillate.

Section III - Physical Data

Boiling Range: 300. - 400. deg F
Vapor Pressure: 10.1 mm @ 20 deg C
Specific Gravity: 0.86
Evaporation Rate: Slower (relative to n-butyl acetate)
Freezing Point: N/A deg F
Vapor Density: Heavier than air
H2O Soluble: Negligible (< 0.1%)
% Volatile by Volume: 87.01 %

Appearance and Odor: Clear thin liquid with solvent odor

Section IV - Fire and Explosion Hazard Data

Flash point: 101.0 deg F
Explosive Limits: LEL 0.9, UEL 7.0 (%V in air)
FLAMMABILITY CLASSIFICATION
OSHA: Combustible Liquid - Class II
DOT : Combustible Liquid
EXTINGUISHING MEDIA: Foam, CO2, Dry Chemical

SPECIAL FIRE FIGHTING PROCEDURES:

Wear self-contained breathing apparatus and protective clothing. Use water to cool exposed containers. Water stream directed into fire may cause frothing with subsequent spread of fire.

USUAL FIRE AND EXPLOSION HAZARDS:

Irritating and/or toxic gases or fumes may be generated by thermal decomposition or combustion. Closed containers may rupture or explode (due to pressure build-up) when exposed to extreme heat.

Vapor is heavier than air, and may travel along the ground to be

reignited at locations distant from the source; flashback of flame may occur.

Empty containers may contain explosive vapors or dangerous residues. DO NOT cut, puncture, or weld on or near container.

=====  
=====  
Section V - Toxicological Information  
=====

----- Ingredient ----- Material Description	PEL	TLV (twa)	LD50(mg/kg)		LC50(ppm)	
	ppm	mg/m3	ppm	(rat) ORAL	(rbt) DERMAL	(rat) INHAL
Aromatic Hydrocarbon Blend	N/A	N/A	100.0	4700.0	N/A	3670.0
Xylene	100.	N/A	100.0	4300.0	N/A	5000.0
Aliphatic petroleum Distillate	500.	N/A	100.0	N/A	N/A	N/A

=====  
=====  
Section VI - Health Hazard Data  
=====

EFFECTS OF OVEREXPOSURE: THRESHOLD LIMIT VALUES: See Section V

ACUTE HAZARDS:

EYES: Moderate irritant. May cause reversible corneal injury.

SKIN: Moderate irritant. May cause dermatitis and allergic responses.

INHALATION: Respiratory irritant and intoxicant.

Overexposure shown by headache, dizziness and confusion to coma.

Material aspirated into lungs may cause chemical pneumonitis.

INGESTION: May cause irritation of mouth, throat, and stomach.

Symptoms include nausea, abdominal pain and possible collapse.

\*\*\*Preexisting pulmonary and dermatological disorders may be aggravated by exposure to hazardous components.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with plenty of water at least 15 minutes. Obtain immediate medical attention.

SKIN: Remove contaminated clothing. Wash affected area(s) thoroughly with soap and water. Consult a physician.

INHALATION: Remove to fresh air. If breathing is difficult, give oxygen. Administer artificial respiration if not breathing. Obtain medical attention.

INGESTION: DO NOT INDUCE VOMITTING.

Give water or milk if victim is conscious and not drowsy.

Should vomiting occur, be sure to keep victim's head below hips to avoid aspiration of vomitus into the lungs. Obtain immediate medical attention.

=====  
=====  
Section VII - Reactivity Data  
=====

STABILITY: Stable

STABILITY CONDITIONS TO AVOID:

Sources of ignition.

INCOMPATIBILITY (MATERIALS TO AVOID CONTACT WITH):

Strong bases or oxidants. Strong Lewis or mineral acids.

HAZARDOUS DECOMPOSITION PRODUCTS:  
Acrid smoke. Oxides of carbon.  
HAZARDOUS POLYMERIZATION: Will not occur  
POLYMERIZATION CONDITIONS TO AVOID:

=====  
=====  
Section VIII - Spill or Leak Procedures  
=====  
=====

STEPS FOR MATERIAL SPILLAGE:

Ventilate area. Wear appropriate protective equipment during cleanup. Eliminate sources of ignition. Shut off source of leak if safe to do so. Dike or contain spill. Absorb with inert material. Sweep or shovel into containers with lids. Cover loosely and store in a well-ventilated area until disposal. Wash spill area with soap and water. Prevent washings from entering waterways.

WASTE DISPOSAL METHODS:

Review all local, state, and federal regulations concerning health and pollution for appropriate disposal procedures.

=====  
=====  
Section IX - Special Protection Information  
=====  
=====

RESPIRATORY PROTECTION:

If the TLV is exceeded, if use is performed in a poorly ventilated confined space or area with limited ventilation, use NIOSH-approved respirator in accordance with 29 CFR 1910.134.

Use self-contained breathing apparatus when burning out cured compound

VENTILATION:

Local exhaust as needed to control vapor/dust levels to below recommended limits.

PROTECTIVE GLOVES:

Impervious rubber.

EYE PROTECTION:

Chemical safety goggles


OTHER PROTECTIVE EQUIPMENT:

Accessible eye wash and safety shower.  
Clean protective clothing

=====  
=====  
Section X - Special Precautions  
=====  
=====

HANDLING AND STORAGE PRECAUTIONS:

FOR PROFESSIONAL USE ONLY  
DO NOT TAKE INTERNALLY  
AVOID CONTACT WITH EYES, SKIN, AND CLOTHING  
AVOID BREATHING VAPOR/DUST/MIST  
WASH THOROUGHLY AFTER HANDLING  
TIGHTLY RESEAL ALL PARTIALLY USED CONTAINERS  
USE ONLY WITH ADEQUATE VENTILATION  
STORE AWAY FROM SOURCES OF IGNITION



KEEP OUT OF REACH OF CHILDREN

\*THIS CONTAINER HAZARDOUS WHEN EMPTY\*

DO NOT REUSE EMPTY CONTAINER WITHOUT COMMERCIAL CLEAN OR RECONDITION  
STORE EMPTY CONTAINER AWAY FROM HEAT AND FLAME

OTHER PRECAUTIONS:

\*Studies suggest that chronic overexposure and/or systemic toxicity effects are targeted at the kidneys and liver.

\*\*\*N/A = Information or data Not Available\*\*\*

D.O.T. Hazard Class: Combustible Liquid  
D.O.T. Shipping Name: Paint Liquid, N.O.S.  
(Aliphatic and Aromatic Hydrocarbon Blend)  
UN/NA Number: UN1263  
EPA RCRA Class: Ignitable  
EPA RCRA Number: D001  
ON EPA TSCA Inventory: Yes

"This information is furnished without warranty, representation, inducement, or license of any kind, except that this information is accurate to the best of Rexnord Inc.'s knowledge or is obtained from sources believed by Rexnord, Inc. to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from the use thereof. Rexnord, Inc. assumes no responsibility for injuries proximately caused by the Material if reasonable safety procedures are not adhered to as stipulated in this data sheet. Additionally, Rexnord, Inc. assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material."