

MATERIAL SAFETY DATA SHEET

000362

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME SPRAY PRODUCTS CORPORATION		EMERGENCY TELEPHONE NO. 215/277-1010
ADDRESS (Number, Street, City, State, and ZIP Code) P.O. BOX 737, NORRISTOWN, PA 19404		
CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS CLEAR #470, #370, #970	
CHEMICAL FAMILY	FORMULA	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE ACRYLOID (ROHM-HAAS)	10		METALLIC COATINGS		
SOLVENTS	75	*	FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS PROPANE	15				
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
E.E. ACETATE				4	
MIBK				8	
ACETONE				34	
METH. CHLORIDE				16	
TOLUENE				13	
				<u>75</u>	

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	-43.7	SPECIFIC GRAVITY (H ₂ O=1)	.801
VAPOR PRESSURE (mm Hg.)	70	PERCENT VOLATILE BY VOLUME (%)	85
VAPOR DENSITY (AIR=1)	1.28	EVAPORATION RATE (_____ = 1)	8.6
SOLUBILITY IN WATER	MODERATE		
APPEARANCE AND ODOR			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	T.C.C. -138°F.	FLAMMABLE LIMITS	2.2^L	8.9^U
EXTINGUISHING MEDIA	FOAMY CO₂, DRY CHEMICALS			
SPECIAL FIRE FIGHTING PROCEDURES	HANDLE AS EXTREMELY FLAMMABLE LIQUID.			
UNUSUAL FIRE AND EXPLOSION HAZARDS	CONTENTS UNDER PRESSURE			
	DO NOT STORE ABOVE 120°F.			

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

700 P.P.M.

EFFECTS OF OVEREXPOSURE

ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS,
"HANGOVER", AND RECOVER.

EMERGENCY AND FIRST AID PROCEDURES

REMOVE VICTIM TO FRESH AIR. IF BREATHING
HAS STOPPED, GIVE ARTIFICIAL RESPIRATION.

SECTION VI - REACTIVITY DATA

STABILITY

UNSTABLE

CONDITIONS TO AVOID

STABLE

X

SPARKS, OPEN FLAME

INCOMPATIBILITY (Materials to avoid)

HAZARDOUS DECOMPOSITION PRODUCTS

STRONG OXIDIZING AGENTS

HAZARDOUS
POLYMERIZATION

MAY OCCUR

CONDITIONS TO AVOID

WILL NOT OCCUR

--- X

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

AVOID OPEN FLAMES OR SPARK SOURCE / PROVIDE ADEQUATE VENTILATION

WASTE DISPOSAL METHOD

EVAPORATE OR FLUSH WITH WATER REMOVE TO CONTAINER.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

NORMALLY NOT REQUIRED

VENTILATION

LOCAL EXHAUST

DESIRABLE

SPECIAL

MECHANICAL (General)

AS REQUIRED

OTHER

PROTECTIVE GLOVES

NORMALLY NOT REQUIRED

EYE PROTECTION

NORMALLY NOT REQUIRED

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

EXTREMELY FLAMMABLE - CONTENTS

UNDER PRESSURE. DO NOT STORE ABOVE 120°F. KEEP FROM OPEN FLAMES OR
OTHER PRECAUTIONS SPARK.

DO NOT PUNCTURE OR INCINERATE CAN.