



Page 1
T

MSDS066

066.0

MATERIAL SAFETY DATA SHEET

(MSDS)

ITEM NUMBER: 066 - SPRAYWAY SPRAY ADHESIVE
IDENTITY (As Used On Label and List): SPRAYWAY SPRAY ADHESIVE

EMERGENCY MEDICAL Telephone# 1-800-228-5635 X 009 (24 Hrs) Outside of the U.S.A. Call 651-632-9275

PRODUCT HAZARD RATINGS (NFPA): Health = 1, Fire = 4, Reactivity = 0, Protective Equipment = *B

(Rating Legend: 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

***** SECTION I

SPRAYWAY, INC.

TELEPHONE NUMBER FOR INFORMATION : 1-

800-332-9000

484 VISTA AVE.

ADDISON

DATE PRINTED : 11/14/00 NAME OF

PREPARER : Ron Cepa

IL 60101

***** SECTION II - HAZARDOUS INGREDIENTS / IDENTITY

INFORMATION *****

Chemical Names By Wt. (LD50-Oral Rat)	Exposure Limits SEC 313	SARA Title III TLV/TWA	ACGIH PEL	OSHA	%
---	----------------------------	---------------------------	--------------	------	---

Heptane (CAS#142-82-5)	NA	NA	400ppm	400ppm	10-15
Cyclohexane(CAS #110-82-7)	12.7 mg/kg	YES	300	300	30-35
Liquefied Petroleum Gas (CAS#68476-85-7)	NA	NA	1000ppm	1000ppm	30-35
Dimethyl Ether (CAS#115-10-6)	NA	NA	1000ppm	1000ppm	10-15
Styrene Butadiene Rubber(CAS#26471-45-4)	NA	NA	NA	NA	3-5
Modified Wood Rosin(CAS#64365-17-9)	NA	NA	NA	NA	5-10

Unidentified ingredients are not considered hazardous under the Federal Hazard Communication Standard.

Components Listed As A Suspected Carcinogen: None

***** SECTION III - PHYSICAL CHARACTERISTICS

Boiling Point: NA Vapor Pressure (psig): 100 +/-5 @130F Specific Gravity (H2O=1): <1.0
Solubility/Water: Negligible Vapor Density (AIR=1): >1 Evaporation Rate (Ether=1): <1
Appearance and Odor: Light tan with a solvent odor.

***** SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: This product is considered to be extremely flammable as described in 16CFR 1500.45.

Flammable Limits - % Volume In Air (Propellant): LEL: 1.8 UEL: 9.2

Extinguishing Media: Carbon dioxide, foam and/or dry chemical may be used.

Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.

Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.

Unusual Fire and Explosion Hazards: At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

***** SECTION V - REACTIVITY DATA *****

Stability: Stable Hazardous Polymerization: Oxides of carbon

Incompatibility (Materials to Avoid): Oxidizing agents Hazardous Decomposition Products: Carbon dioxide, carbon monoxide, and additional toxic chemicals may be formed in small amounts.

Conditions to Avoid: Do not store above 54C-130F. Keep away from heat, direct sunlight, open flames or sparks. Dropping of containers may cause bursting.

***** SECTION VI - HEALTH HAZARD DATA *****

Route(s) of Entry - Inhalation: X Eyes: X Skin: X Ingestion: X

Signs and Symptoms of Exposure: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, nausea, etc.

Prolonged or repeated skin contact may defat the skin and cause dermatitis. Allergic reactions may arise in sensitive individuals. Eye irritant.

Medical Conditions Generally Aggravated by Exposure: Preexisting skin or eye disorders may be aggravated by exposure to this product.

Emergency and First Aid Procedures: Eye Contact: Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get

medical attention if irritation persists. Skin Contact: Remove contaminated clothing. Flush skin with water, follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. Inhalation: Remove victim to fresh air and provide oxygen if breathing is difficult.

Give artificial respiration if not breathing. Get medical attention. Ingestion: Get medical attention. Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs.

***** SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE *****

Releases or Spilled: Remove all sources of ignition and ventilate area. Soak up spill with an inert absorbent and place into a designated disposal container. Consult local regulatory agency for proper disposition of material.

Waste Disposal Method: Do not puncture or incinerate containers. When contents are depleted continue to depress button until all gas is expelled. Dispose of container in accordance with local, state, and federal regulations.

Handling And Storing: Avoid breathing vapor. Keep away from heat and flame. Use with adequate ventilation. Do not puncture or incinerate containers. Do not expose to direct sunlight or store at temperatures above 130F (54C). Store as Level 3 Aerosol (NFPA 30B).

Other Precautions: Please read and follow the directions on the product label; they are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your

