

MSDS Enclosed

SUPERIOR LUBRICANTS CO. INC.  
32 WARD ROAD  
NORTH TONAWANDA, NEW YORK 14120  
(716) 693-6050

423 A  
Acct #  
Customer Name Syracuse City School District (Acct Payable Dept)  
Address 775 Harrison Street  
Town, State, Zip code Syracuse, NY 13210

Date : 5/22/90

Dear VALUED CUSTOMER:

Enclosed are Material Safety Data Sheets (MSDS) for the following products that you have recently purchased from Superior Lubricants:

SEE BELOW

These MSDS's are provided to help ensure a safe work environment for your employees and in compliance with OSHA Hazard Communication Standards. The information contained herein should be used for health and safety training and not for specification purposes. This information should be made available to all employees handling the product as well as your customers.


It is your responsibility to properly label repackaged products, train and supervise your workers and develop safe handling procedures.

We appreciate your patronage and will continue to provide quality products and service. If you need any additional information or MSDS sheets please feel free to contact me.

Cam2 Devron

Sincerely,

Susan A. Hoover  
Susan H. Hoover  
Systems Manager



MSDS Enclosed



000892

MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

PAGE #1

PRODUCT NAME - CAN2 DEXRON II-D

M.S.D.S. DATE: 8/28/86

MANUFACTURER: RV0000000001
SUN REFINING AND MARKETING COMPANY
TEN PENN CENTER
1801 MARKET STREET
PHILADELPHIA, PA 19103

SYNONYMS.....:
CAS REGISTRY NO...: SEE SEC. 2
CAS NAME.....: NO CLASSIFICATION - MIXTURE
CHEMICAL FAMILY...: BLEND
INFORMATION
SUPPLIER.....: RAMONA PANSON
PHONE.....: 215-293-6487

SECTION 2 - INGREDIENTS

SEVERELY SOLVENT REFINED LIGHT PARAFFINIC DISTILLATE CAS# 64741-89-5;
SEVERELY SOLVENT REFINED HEAVY PARAFFINIC DISTILLATE CAS# 64741-88-4;
ORGANO-METALLO COMPOUNDS; REF DYE. PRODUCT TYPICALLY CONTAINS 0.03%
ZINC; 0.21% SULPHUR.

SECTION 3 - PHYSICAL DATA

BOILING POINT.....: HIGH (DEG. F) HIGH (DEG. C)
MELTING POINT.....: N/A (DEG. F) N/A (DEG. C)
SPECIFIC GRAVITY.....: 0.88 (H2O=1)
PACKING DENSITY.....: N/A KG/M3
VAPOR PRESSURE.....: NIL (MM HG AT 20C)
VAPOR DENSITY.....: 10+ (AIR=1)
SOLUBILITY IN WATER....: NIL (% BY VOL)
PH INFORMATION.....: 6.4 AT CONC. G/L H2O
% VOLATILES BY VOL.....: NIL
EVAPORATION RATE.....: 1000 X SLOWER (ETHYL ETHER=1)
OCTANOL/WATER COEFF....: N.D.
APPEARANCE.....: RED FLUID
ODOR.....: SLIGHT ODOR
ODOR THRESHOLD.....: N.D. (PPM)

SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT 350 MINIMUM COC (DEG. F) 177 MINIMUM COC (DEG. C)  
AUTOIGNITION TEMP. 695 ESTIMATED (DEG. F) 368 ESTIMATED (DEG. C)

NEPA CLASSIFICATION	HAZARD RATING
HEALTH - 0	0 - LEAST
FIRE - 1	1 - SLIGHT
REACTIVITY - 0	2 - MODERATE

SPECIFIC HAZARD

FLAMMABLE LIMITS IN AIR -

LOWER EXPLOSIVE LIMIT (LEL) NOT DETERMINED % VOL.

UPPER EXPLOSIVE LIMIT (UEL) NOT DETERMINED % VOL.

FIRE AND EXPLOSION HAZARDS - CAN BE MADE TO BURN (FLASH POINT GREATER THAN 200F)

EXTINGUISHING MEDIA - WATER FOG. CHEMICAL FOAM. DRY CHEMICAL POWDER. CARBON DIOXIDE.

SPECIAL FIRE FIGHTING INSTRUCTIONS - WEAR SELF-CONTAINED BREATHING APPARATUS WHEN FIRE FIGHTING IN CONFINED SPACE.

SECTION 5 - HEALTH HAZARD INFORMATION

EXPOSURE LIMITS - SUN RECOMMENDATION

8 HR. TIME WEIGHTED PERMISSIBLE EXPOSURE PPM 5.00 MB

ROUTES OF EXPOSURE AND EFFECTS -

INHALATION - NO ACUTE EFFECTS EXPECTED TO TWICE EXPOSURE LIMIT.

SKIN - PRACTICALLY NON-TOXIC IF ABSORBED (LD50 GREATER THAN 2000 MG/KG).

MINIMAL IRRITATION WITH PROLONGED OR REPEATED CONTACT.

EYE - CONTACT WITH THE EYE MAY CAUSE MINIMAL IRRITATION.

INGESTION - PRACTICALLY NON-TOXIC (LD50 GREATER THAN 1500 MG).

ESTIMATED LD 50 IN RATS. IS: GREATER THAN 15 GM/KG.

FIRST AID -

INHALATION - MOVE PERSON TO FRESH AIR.

SKIN - WASH WITH SOAP AND WATER UNTIL NO ODOR REMAINS. WASH CLOTHING BEFORE REUSE.

EYE - FLUSH WITH WATER. IF IRRITATION PERSISTS, OBTAIN MEDICAL ASSISTANCE.

INGESTION - GIVE LIQUIDS AND INDUCE VOMITING UNLESS VICTIM IS UNCONSCIOUS. OBTAIN MEDICAL ASSISTANCE. SMALL AMOUNTS WHICH ACCIDENTALLY ENTER MOUTH SHOULD BE RINSED OUT UNTIL TASTE IS GONE.

SECTION 6 - REACTIVITY DATA

STABILITY - STABLE

INCOMPATIBLE MATERIALS - STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION - PRODUCTS: CARBON MONOXIDE AND HYDROGEN

POLYMERIZATION - WILL NOT OCCUR

SECTION 7 - SPECIAL PROTECTION INFORMATION

VENTILATION - VENTILATE AS NEEDED TO COMPLY WITH EXPOSURE LIMIT.

PERSONAL PROTECTIVE EQUIPMENT

EYE - PRODUCT MINIMALLY IRRITATING TO EYES. LOCAL SAFETY POLICY  
DECISION

GLOVES - IMPERVIOUS GLOVES RECOMMENDED WHEN PROLONGED SKIN CONTACT  
CANNOT BE AVOIDED.

RESPIRATOR - CONCENTRATION-IN-AIR DETERMINES PROTECTION NEEDED. USE  
ONLY NIOSH CERTIFIED RESPIRATORY PROTECTION. RESPIRATORY PROTECTION  
USUALLY NOT NEEDED UNLESS PRODUCT IS HEATED OR MISTED.

OTHER - IF CONTACT IS UNAVOIDABLE, WEAR IMPERVIOUS PROTECTIVE GEAR.  
LAUNDRY SOILED CLOTHES.

SECTION 8 - DISPOSAL PROCEDURES

AQUATIC TOXICITY - NOT DETERMINED

SPILL, LEAK OR RELEASE - CONTAIN SPILL, ABSORB ON INERT MATERIAL.

WASTE DISPOSAL METHOD - FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS. DO  
NOT FLUSH TO DRAIN/STORM SEWER. CONTRACT TO AUTHORIZED DISPOSAL  
SERVICE.

SECTION 9 - SPECIAL PRECAUTIONS

STORAGE AND HANDLING CONDITIONS - NFPA CLASS IIIB STORAGE. AVOID  
PROLONGED BREATHING OF MIST OR VAPOR. AVOID PROLONGED OR REPEATED  
CONTACT WITH SKIN. WASH THOROUGHLY AFTER HANDLING.

SECTION 10 - ADDITIONAL PRECAUTIONS AND LABELS -  
NO ADDITIONAL PRECAUTIONS OR LABELS