

HYW Kell Diesel Synacel 30:10
School

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

001008

800100



IDENTITY (As Used on Label and List) **STAIN BUSTER**

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I Superior Quality Products

Distributor's Name **SQP**

Emergency Telephone Number

Address (Number, Street, City, State, and ZIP Code)
702 Potential Parkway

Telephone Number for Information
518/374-7786

Scotia, NY 12302

Date Prepared

Revised **3/15/88**

Signature of Preparer (optional)
Martin Nolan

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	CAS#	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Dipropylene Glycol Methyl Ether	34590-94-8	100ppm(skin)	100ppm	N.E.	~ 5
Ethylene Glycol Butyl Ether	111-76-2	TWA50ppm(skin)	25ppm(skin)	N.E.	~ 5

Section III - Physical/Chemical Characteristics

Boiling Point	~ 212°F	Specific Gravity (H ₂ O = 1)	1.00
Vapor Pressure (mm Hg.)	~ 20	Melting Point	n/a
Vapor Density (AIR = 1)	n/d	Evaporation Rate (Butyl Acetate = 1)	n/d

Complete

Appearance and Odor **Colorless/blue tinge liquid, faint ammonical odor.**

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	n/a	Flammable Limits	n/a	LEL	UEL
---------------------------	-----	------------------	-----	-----	-----

Extinguishing Media **Water, foam, CO₂, dry chemical**

Special Fire Fighting Procedures **n/a**

Usual Fire and Explosion Hazards **None known**

Produced locally

Section V — Reactivity Data

Stability	Unstable	Conditions to Avoid	None known
	Stable		

Incompatibility (Materials to Avoid) **None known**

Hazardous Decomposition or Byproducts
 When exposed to fire, produces normal products of combustion.

Hazardous Polymerization	May Occur	Conditions to Avoid	None known
	Will Not Occur		

Section VI — Health Hazard Data

Route(s) of Entry: Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic) **Eye/skin-possible irritation Ingestion-possible nausea**

Contains Ethylene Glycol Butyl Ether which can cause liver, kidney & blood damage. Risk of damage & effects depends upon level & duration of exposure.

Carcinogenicity: NTP? **No** IARC Monographs? **No** OSHA Regulated? **No**

Signs and Symptoms of Exposure **Eyes/skin-irritation Ingestion-nausea**

Medical Conditions Generally Aggravated by Exposure **None known**

Emergency and First Aid Procedures
Eyes/skin-flush with water for at least 15 minutes, call physician if irritation persists.
Ingestion-give water or milk to drink if conscious, call physician immediately.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled
Floors may be slippery, use caution to avoid falls. Flush area with water, take up with wet vacuum, rinse and take up again. May be absorbed with inert material and containerized for disposal.

Waste Disposal Method **Follow federal/state/local regulations.**

Precautions to Be Taken in Handling and Storing
Do not store at temperatures above 120°F or below 35 °F.

Other Precautions **Keep out of reach of children**

Section VIII — Control Measures

Respiratory Protection (Specify Type) **None required**

Ventilation	Local Exhaust as necessary for normal ventilation	Special	n/a
	Mechanical (General) as necessary for normal ventilation	Other	n/a

Protective Gloves **impervious such as rubber** Eye Protection **Optional**

Other Protective Clothing or Equipment **None required**

Work/Hygienic Practices **Follow normal industrial hygiene practices.**