

#25/ #140 #200 #300 #120 #130
OPAQUE PAINT MARKERS

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

● 1759

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

9709421

3
 JAN 27 1997
 UCHIDA OF AMERICA

Manufacturer's Name UCHIDA OF AMERICA, CORP.	Emergency Telephone Number (310) 793 2200
Address (Number, Street, City, State, and ZIP Code) 3535 DEL AMO BLVD.	Telephone Number for Information (310) 993 2210 FAX
TORRANCE CALIFORNIA, 90503	Date Prepared JAN. 27, 1997
	Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	96 (optional)
PIGMENTS - COLORED PIGMENTS				10
VEHICLE: RESINS				30
SOLVENTS: XYLENE		100 (ppm)		40
OTHERS: TITANIUM OXIDE				20

CONFORMS TO CONSUMER SAFETY ACT REGULATIONS CFR-16 PART 1500

Section III — Physical/Chemical Characteristics

Boiling Point	280	Specific Gravity (H ₂ O = 1)	N/A
Vapor Pressure (mm Hg)	7	Melting Point	60-75
Vapor Density (AIR = 1)	4	Evaporation Rate (Butyl Acetate = 1)	N/A

Solubility in Water
INSOLUBLE

Appearance and Odor
PETROLEUM SOLVENT ODOR.

Section IV — Fire and Explosion Hazard Data.

Flash Point (Method Used)	105°F TAG OPEN	Flammable Limits	N/A	LEL	UEL
Extinguishing Media	CO₂ or CHEMICAL FORM				
Special Fire Fighting Procedures	N/A				
Unusual Fire and Explosion Hazards	N/A				

(Reproduce locally)

OSHA 174, Sept. 1986

V# 088106 2-16-00

#1257 #140/#200/#300/#120/#130 DECOCOLOR OPAQUE PAINT MARKERS

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid	N/A
	Stable	X	PROLONGED TEMPERATURE AT 110°F	

Incompatibility (Materials to Avoid)

Hazardous Decomposition or Byproducts

Hazardous Polymerization	May Occur		Conditions to Avoid	N/A
	Will Not Occur	X		

Section VI - Health Hazard Data

Routes of Entry: Inhalation? Skin? Ingestion?
 N/A

Health Hazards (Acute and Chronic)
N/A

Carcinogenicity: NTP? IARC Monographs? OSHA Regulated?
 N/A

Signs and Symptoms of Exposure
N/A

Medical Conditions Greatly Aggravated by Exposure
ANESTHESIA WITHOUT ADEQUATE VENTILATION WHEN USED IN VERY LARGE QUANTITIES.

Emergency and First Aid Procedures
IF INGESTED, DO NOT INDUCE VOMITING, CALL PHYSICIAN.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled
 ADEQUATE VENTILATION, TREAT AS FLAMMABLE SOLVENT OR PAINT SPILL.

Waste Disposal Method
WITH OTHER PETROLEUM PRODUCTS.

Precautions to Be Taken in Handling and Storage
DO NOT STORE NEAR HEAT SOURCE

Other Precautions
N/A

Section VIII - Control Measures

Respiratory Protection (Specify Type) AVOID PROLONGED INHALATION OF CONCENTRATED VAPOR

Ventilation	Local Exhaust	N/A	Special	N/A
	Mechanical (General)	N/A	Other	N/A

Protective Gloves: N/A
 Eye Protection: N/A

Other Protective Clothing or Equipment
N/A

Work/Hygiene Practices
N/A