

WARD'SNatural Science Establishment, Inc.
P.O. Box 92912
Rochester, NY 14692-9012
716-359-2502

K9770

MATERIAL SAFETY DATA SHEET397 Vansickle Road
St. Catharines, Ontario L2S 3T5815 Fiero Lane
San Luis Obispo, CA 93403-5010MSDS No. AA 25
Effective Date November 27, 1996**SECTION I NAME 24 HOUR EMERGENCY ASSISTANCE**

Product	ACETONE	
Chemical Synonyms	2-Propanone; Dimethyl Ketone	
Formula	CH ₃ COCH ₃	
Unit Size	Up to 20 Liters.	
C.A.S. No.	67-64-1	

SECTION II INGREDIENTS OF MIXTURES

Principal Component(s)	%	TLV Units
Acetone: (CAS No. 67-64-1)	>99.5%	See Section V.
May contain trace amounts of		
Benzene: (CAS No. 71-43-2) (suspected carcinogen).		

DANGER! EXTREMELY FLAMMABLE! CAUSES EYE IRRITATION!

SECTION III PHYSICAL DATA

Melting Point (°F)	-94°C (-137°F)	Specific Gravity (H ₂ O = 1)	0.7880 @ 25°C/25°C
Boiling Point (°F)	56.48°C (132.8°F)	Percent Volatile by Volume (%)	100%
Vapor Pressure (mm Hg)	181.7 @ 20°C.	Evaporation Rate (Butyl Ac. = 1)	>7.0
Vapor Density (Air=1)	2.00		
Solubility in Water	Completely miscible.		
Appearance & Odor	Colorless liquid, fragrant mint-like odor.		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	-18°C (0°F) TCC	Flammable Limits in Air % by Volume	Lower 2.6%	Upper 12.8%
Extinguisher Media	Carbon dioxide (CO ₂); dry chemical (ABC); water spray; alcohol foam.			

SPECIAL FIREFIGHTING PROCEDURES

Water should be used to keep fire exposed containers cool. Water spray may be used to flush spills away from exposure and to dilute spills to non-flammable mixtures. In fire conditions, wear a NIOSH-approved self-contained breathing apparatus.

(1993 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.6, GUIDE PAGE NO. 26)

UNUSUAL FIRE AND EXPLOSION HAZARDS

Acetone is extremely flammable and its vapors form explosive mixtures with air. Dangerous when exposed to heat, sparks, flame or strong oxidizing agents.

Autoignition Temperature: 1000°F (538°C).

D.O.T. ACETONE, 3, UN 1090

Approved by U.S. Department of Labor *essentially similar* to form OSHA-20

SECTION V HEALTH HAZARD DATA AA 25

Threshold Limited Value TWA (Air): 750 ppm; 1,780 mg/m³ STEL (Air): 1,000 ppm 2375 mg/m³ (ACGIH 1992-93).

Effects of Overexposure **INHALATION:** Vapors are irritating to eyes, nose, and throat. High vapor concentrations may result in headache, dizziness, and nausea. **SKIN:** Repeated contact causes defatting and chapping and drying of skin. **EYES:** Causes severe irritation, redness and swelling. **INGESTION:** Slightly toxic, causes nausea, vomiting, headache, dizziness, and unconsciousness.

Emergency and First Aid Procedures **INHALATION:** Remove to fresh air. If breathing has stopped, give artificial respiration. Give oxygen by qualified personnel, call a physician. **SKIN:** Wash contact area with soap and water. **EYES:** Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention. **INGESTION:** **DO NOT INDUCE VOMITING!** Call a physician. If conscious, give one or two glasses of water to drink. Never give anything by mouth to an unconscious person.

SECTION VI REACTIVITY DATA

Stability Unstable Stable X Excessive temperatures, heat, sparks and open flame.

Incompatibility (Materials to Avoid) Chloroform; Chromic Anhydride; Hydrogen Peroxide; Nitric Acid and Acetic Acid; Nitric and Sulfuric Acid; Sulfuric Acid and Potassium Dichromate.

Hazardous Decomposition Products Complete combustion yields carbon dioxide and water vapor; incomplete combustion can produce carbon monoxide.

Hazardous Polymerization Conditions to Avoid May Occur Will Not Occur X Not applicable.

SECTION VII SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled Eliminate all sources of ignition. **Small spill** - allow to evaporate if it can be done safely. Otherwise soak up with absorbent material and scoop into drum.

Waste Disposal Method Discharge, treatment, or disposal may be subject to Federal, State or Local laws. These disposal guidelines are intended for the disposal of catalog-size quantities only.

Burn in an approved incinerator, if local environmental regulations permit.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiration Protection (Specify Type) Work in fume hood or wear a NIOSH-approved all purpose canister mask.

Ventilation Local Exhaust Recommended Special No. Mechanical (General) Recommended Other Adequate to maintain below exposure limit.

Protective Gloves Rubber. **Eye Protection** Chemical safety glasses.

Other Protective Equipment Safety glasses, lab coat, vented hood, proper gloves, fire extinguisher, eye wash station.

SECTION IX SPECIAL PRECAUTIONS

Precautions to be Taken in Handling & Storing Keep away from heat, sparks, flame. Store in a cool, well-ventilated area. Use with adequate ventilation. Keep container tightly closed when not in use.

Other Precautions Read label on container before using. Do not wear contact lenses when working with chemicals. Avoid contact with eyes. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Remove and wash contaminated clothing.

For laboratory use only. Not for drug, food or household use. Keep out of reach of children.

Revision No. 6 Date 11/27/96 Approved Michael Raszeja Chemical Safety Coordinator MR

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. *Hazardous Materials Industrial Standards. Printed on recycled paper.