

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

000027

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)

Form Approved

OMB No. 1218-0072



IDENTITY: As Used on Label and List: 330-0525
 ELECTROSTATIC BLACK INK 330-0525

Note: Blank spaces are not permitted. If any item is not applicable, or no
 information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name

ATF Davidson Co.

Emergency Telephone Number

1-800-235-3828

Address: Number, Street, City, State, and ZIP Code:

4795-F Fulton Ind. Blvd.

Telephone Number for Information

(404) 696-7024

Date Prepared

May 1, 1986

Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components: Specific Chemical Identity: Common Name(s)	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
1. Petroleum Hydrocarbon		CAS# 64742-46-7		

Section III — Physical/Chemical Characteristics

Boiling Point 350-590 F	Specific Gravity (H ₂ O = 1) N/A
Vapor Pressure (mm Hg.) 0.01 mm Hg @ 68 F	Melting Point N/A
Vapor Density (AIR = 1) Heavier	Evaporation Rate (Butyl Acetate = 1) Slower
Solubility in Water	

Appearance and Odor

Black paste

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) Over 200 F	Flammable Limits	LEL	UEL
---	------------------	-----	-----

Extinguishing Media

Foam, CO₂, Dry Chemical, Water Fog

Special Fire Fighting Procedures

Water may be ineffective, but can be used to cool containers exposed to
 heat or flame.

Unusual Fire and Explosion Hazards

Dense smoke may be generated while burning.

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid Contact with strong oxidizing agents.
	Stable	X	

Incompatibility (Materials to Avoid)
NONEHazardous Decomposition or Byproducts
NONE

Hazardous Polymerization	May Occur		Conditions to Avoid NONE
	Will Not Occur	X	

Section VI — Health Hazard Data

Route(s) of Entry: N/A	Inhalation? N/A	Skin? N/A	Ingestion? N/A
---------------------------	--------------------	--------------	-------------------

Health Hazards (Acute and Chronic)
N/A

Carcinogenicity: N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
-------------------------	-------------	-------------------------	------------------------

Signs and Symptoms of Exposure

Skin: irritation or dermatitis. Eyes: burning or irritation
 Inhalation: Headache, dizziness, drowsiness, nausea Ingestion: irritation or
 gastric disturbance.

Medical Conditions
Generally Aggravated by Exposure**Emergency and First Aid Procedures**

Skin: wash with mild soap and water. Eyes: rinse with water, 15 min. Consult
 physician. Inhalation: Remove to fresh air.
 Ingestion: do not induce vomiting. Consult physician.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

wipe up—dispose of wipers in containers approved for oily waste.
 Prevent run-off to sewers, streams, or other waterways.

Waste Disposal Method

Landfill or incineration in accordance with Local, State, and Federal
 regulations.

Precautions to Be Taken in Handling and Storing

Keep in containers closed when not in use. Keep away from excessive heat,
 sparks, open flame. Wash hands and face with soap and water before eating or
 smoking.

Other Precautions
For industrial use only.**Section VIII — Control Measures**Respiratory Protection (Specify Type)
not normally acquired

Ventilation normal	Local Exhaust NORMAL	Special Local and State regulations Other
	Mechanical (General) N/A	

Protective Gloves
XEye Protection
Goggles or safety glasses.

Other Protective Clothing or Equipment

Gloves, apron, boots, impervious clothing is needed to avoid excessive contact

Work/Hygenic Practices

N/A