MATERIAL SAFETY DATA SHEET

SECTION 1- CHEMICAL PRODUCT AND COMPANY INDENTIFICATION

PROD JCT NAME: X91504D - DUSTER II

SUPPLIER:

KENSINGTON TECHNOLOGY GROUP

2855 CAMPUS DRIVE SAN MATEO, CA 94403

EMERGENCY TELEPHONE: 800-535-5053

24 HOUR EMERGENCY PHONE

MANUFACTURER: AEROFIL TECHNOLOGY, INC.

225 INDUSTRIAL PARK DRIVE

SULLIVAN, MO 63080

EMERGENCY TELEPHONE: 800-535-5053

24 HOUR EMERGENCY PHONE

	SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS						
ITEM —	СНЕМІ	CAL NAME	CAS NU	IMBER.	-WT/WT % LESS	THAN	
01	ETHANE, 1, 1-DIFLUORO		75-37-6		100.0%		
		· · · · · · · · · · · · · · · · · · ·	EXPOSI	JRE LIMITS			
ITEM	ACGIH TLV-TWA TLV-STEL		OSHA PEL-TWA PEL-CEILING		COMPANY TLV-TWA	SKIN	
01	NO INFO	NO INFO	NO INFO	NO INFO	1000 ppm	NO	
(Set Se	ction 16 for abbre	viation legend)					٠

SECTION 3 - HAZARDS INDENTIFICATION

*** EF IERGENCY OVERVIEW***: KEEP FROM REACH OF CHILDREN. DO NOT PUNCTURE, INCINERATE, OR PLACE AEROSOL PRODUCT CONTAINERS IN COMPACTORS. CONTAINERS OF THIS MATERIAL MAY BE HAZA LOUS WHEN EMPTIED SINCE CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLIC). ALL HAZARD PRECAUTIONS GIVEN MUST BE OBSERVED. DO NOT FLAME CUT, BRAZE, OR USE WELD NG TORCH. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THIS PRODUCT MAY BE HARMFUL OR FATAL.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: MAY CAUSE IRRITATION, REDNESS, TEARING, BLURRED VISIO I.

EFFEC IS OF OVEREXPOSURE – SKIN CONTACT: CONTACT WITH LIQUID FROM THIS PRODUCT MAY CAUSE FROST BITE. PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION DEFATTING, DERM ATITIS.

EFFEC TS OF OVEREXPOSURE – INHALATION: EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPI LATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCO SCIOUSNESS, AND EVEN ASPHYXIATION. POSSIBLE CARDIAC ARRHYTHMIAS AT HIGH CONCENTRATIONS

EFFECTS OF OVEREXPOSURE - INGESTION: THIS IS NOT AN ANTICIPATED ROUTE OF ENTRY.

EFFEC IS OF OVEREXPOSURE - CHRONIC HAZARDS: No Information.

PRIM/ RY ROUTE (S) OF ENTRY: SKIN CONTACT, INHALATION, EYE CONTACT

SECTION 4 - FIRST AID MEASURES

FIRST AID – EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCA HONALLY, GET MEDICAL ATTENTION.

FIRST AID – SKIN CONTACT: FLUSH THOROUGHLY WITH WATER TO WARM SKIN, TREAT FOR FROSTBITE IF NECE: SARY.

FIRST AID – INHALATION: REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. GIVE ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. KEEP PERSON WARM AND QUIET. GET IN EDICAL ATTENTION.

FIRST AID - INGESTION: THIS IS NOT AN ANTICIPATED ROUTE OF ENTRY.

SECTION 5 - FIRE FIGHTING MEASURES

FLASI. POINT: -58 F (PENS CY-MARTENS C.C.) LOWER EXPLOSIVE LIMIT: 3.9% UPPER EXPLOSIVE LIMIT: 16.9%

AUTO GNITION TEMPERATURE: N.D.

EXTINGUISHING MEDIA: CO2, DRY CHEMICAL, WATERFOG

UNUS JAL FIRE AND EXPLOSION HAZARDS: VAPORS ARE HEAVIER THAN AIR AND TRAVEL ALONG THE 'GRO'U ID OR MAY BE MOVED BY VENTILATION AND IGNITED BY IGNITION SOURCES AT LOCATIONS DISTANT FROM MATERIAL HANDLING POINT. FOR AEROSOL PRODUCTS – EXPOSURE TO TEMPERATURES OVER 130F MAY CAUSE CONTAINERS TO BURST, RELEASING HIGHLY FLAMMABLE GAS.

SPECIAL FIREFIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEI IECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES KEEP FIRE EXPOSED CONTAINERS COOL WITH WATER FOG.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ELIMINATE SOURCES OF IGNITION AND VENT LATE AREA. PERSONS NOT PROPERLY EQUIPPED SHOULD BE EXCLUDED FROM AREA. STOP SPILL AT SC JRCE IF POSSIBLE. AVOID INHALATION OF VAPORS. AVOID CONTACT WITH LIQUID. THIS PRODUCT CONS STS OF MATERIALS WHICH ARE GASES AT ROOM TEMPERATURE. IN THE EVENT OF AN ACCII ENTAL RELEASE, THE CONTENTS OF THIS PRODUCT WILL EVAPORATE. IF UNEMPTIED AEROSOLS ARE TO BE DISPOSED OF, DO SO IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

SECTION 7 - HANDLING AND STORAGE

HANC LING: No Information.

STOR, GE: DO NOT STORE ABOVE 120F. DO NOT STORE IN DIRECT SUNLIGHT.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

A DE REPORTO CON ELEGIO E EN ELEGIO EN ELEGIO DE PORTO DE PORTO DE PORTO DE PORTO DE PORTO DE PARTO DE PARTO D

turna sa matara, ito na alian na mata ya kaci isiki wakazia

LA MESTAGRECIONA DE LA CARROL CARROLA

ENGIP EERING CONTROLS: PROVIDE SUFFICIENT MECHANICAL VENTILATION (GENERAL AND/OR LOCAL EXHA JST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLY (S).

RESPI LATORY PROTECTION: IF WORK PLACE EXPOSURE LIMITS OF PRODUCT OR ANY COMPONENT IS EXCE. DED, USB A NIOSH/MSHA APPROVED RESPIRATOR. CONSULT YOUR SAFTEY EQUIPMENT SUPPLIER FOR R 3COMMENDATIONS.

SKIN I ROTECTION: NOT NECESSARY UNDER NORMAL CONDITIONS. WEAR INSULATED RUBBER GLOVES IF THI RE IS ANTICIPATED EXPOSURE TO LIQUID PRODUCT.

EYE P LOTECTION: SAFETY GLASSES ARE RECOMMENDED TO PROTECT AGAINST FLYING DIRT AND OTHER OBJECTS DISPLACED BY AIR DUSTER.

OTHE : PROTECTIVE EQUIPMENT: NONE KNOWN

HYGII NIC PRACTICES: WASH HANDS BEFORE EATING OR SMOKING. SMOKE IN DESIGNATED AREAS ONLY REMOVE AND LAUNDER CLOTHING IF CONTAMINATED.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILI IG RANGE

: -13 to -13 F

VAPOR DENSITY

: Is heavier than air

ODÓR :

: SLIGHT ETHER-LIKE ODOR

THRESHOLD : N.D.

APPE/RANCE

: COLORLESS GAS

EVAPORATION RATE: Is faster than Butyl

SOLU ILITY IN H2O: NEGLIGIBLE

Acetate

: N.D. FREE; E POINT VAPO I PRESSURE : N.D.

SPECIFIC GRAVITY

: 0.9006 : N.A.

pH @ 0.0% VISCOSITY

; N.D.

PHYSICAL STATE : LIQ. IN CAN

COEFI ICIENT OF WATER/OIL DISTRIBUTION: N.D.

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

COND TIONS TO AVOID: HEAT, SPARKS, WELDING ARCS, OPEN FLAME, STATIC ELECTRICITY, OR OTHER SOUR 'E OF IGNITION.

INCO! IPATIBILITY: ALKALI, ALKALINE EARTH METALS.

HAZA ROOUS DECOMPOSITION PRODUCTS: HYDROFLUORIC ACID AND POSSIBLY CARBONYL FLUORIDE. CARB IN MONOXIDE AND CARBON DIOXIDE

HAZA LDOUS POLYMERIZATION: Will not occur under normal conditions.

STABI_ITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

No pro luct or component toxicological information is available.

SECTION 12 - ECOLOGICAL INFORMATION

ECOL GICAL INFORMATION: No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPC 3AL METHOD: No Information.

SECTION 14 - TRANSPORTATION INFORMATION

DOT Froper Shipping Name

1,1 - Diffuoroethanc

Hazarc Class

Identif cation Number Packin (Group

UN 1030

Not Applicable

This product is packaged under DOT Exemption Number DOT-E 11516 and is FORBIDDEN on passenger aircraft and passen er rail.

SECTION 15 – REGULATORY INFORMATION

U.S. F :DERAL REGULATIONS: AS FOLLOWS -

OSHA Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERC .A - SARA HAZARD CATEGORY: This product has been reviewed according to the EPA 'Hazard Categories' promutated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is cons dered, under applicable definitions, to meet the following categories:

SARA SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

-CHEMICAL NAME = CAS NUMBER =

No SA LA Section 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT: This product contains the following chemical substances subject to the reporting require nents of TSCA 12(B) if exported from the United States:

CHEMICAL NAME-

No infirmation is available.

U.S. S' ATE REGULATIONS: AS FOLLOWS -

CALIF ORNIA PROPOSITION 65: WARNING: The chemical (s) noted below and contained in this product, are known to the star : of California to cause cancer, birth defects or other reproductive harm:

-CHEMICAL NAME-

= cas number -----

=== WT/WT % IS LESS THAN

No Preposition 65 chemicals exist in this product at levels above I ppm.

INTEF NATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 leadings.

CANA DIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS-HEALTH: 2

FLAMMABILITY: 4

REACTIVITY: 1

PREV. DUS MSDS REVISION DATE: 08/15/00

REASON FOR REVISION: NEW PRODUCT

VOC (ONTENT: 0.0% BY WEIGHT, 0 GRAMS/LITER TOTAL PRODUCT, 0 GRAMS/LITER LESS WATER AND EXEMPT, 0.00 LBS/GAL

LEGE ID: N.A. – Not Applicable
N.E. – Not Established
N.D. – Not Determined

DISCLAIMER

The in ormation contained on this MSOS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. The environmental information and hazardous materi is identification system have been included by Aerofil Technology, in order to provide additional health and hazard classification information. The ratings recommended are based upon the criteria supplied by the developers of these rating system, together with Aerofil Technology's interpretation of the available data. Proper personal protective equipment varies widely with conditions of use and anticipated exposure. We recommend that a supervisor or other qualified person determine proper PPE for intended use.