# MATERIAL SAFETY DATA SHEET

DATE OF PREPARATION 1987 AGL2 FOR COATINGS, RESINS AND RELATED MATERIALS (Approved by US Department of Labor "Essentially Similar" to Form OSHA-20)

#### Section 1

American Art Clay Co., Inc. Reward Ceramic Color Mfrs., Co. 4717 W. Sixteenth Street Indianapolis, IN 46222

**EMERGENCY TELEPHONE NO.:** (317) 244-6871, (800) 428-3239, (800) 358-8252, or contact your local poison control center.

TELEX 272145 AMACO IND

PRODUCT CLASS: Liquid or Dry Ceranic Glaze TRADE NAME: AMACO Packaging: 1 1b. Dry 1 Pt. Liquid, 1 Gal. Liquid

MANUFACTURERS CODE IDENTIFICATION: LG - 2, 11, 23, 26, 27, 40, 42, 44, 46, 48, 52

F - The whole series; LF - 901, 910, 920, 925, 946 CTL - 3, 9, 10, 13, 15, 22, 26, 31, 41; TH - 1, 2 SE- 701, 730, 731, 732; HF - 31, 36, 52, 53, 54 LM - The whole series; LT-3, 15, 16, 22; LUG - 30; SGS-1

Section II - HAZARDOUS INGREDIENTS					
INGREDIENT	PERCENT	PPM TI	∟Ý mg/M3	LEL	VAPOR PRESSURE
Non-Toxic	100	NA	NA	NA	NA
Bears the AP Seal					
Conforms to ASIM D4236					
See Section V					

### **SPECIAL LABELING INSTRUCTIONS**

American Art Clay Co., Inc./Reward Ceramic Color Mfrs., Co. Is a member of the Art and Craft Material Institute, 715 Boylston St., Boston MA 02116. Our art and craft materials are certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 (American Society for Testing and Materials). This product is appropriately labeled with one of the following nontoxic seals:







"Products bearing the Certified Products Seal or the AP Approved Product Seal of The Art Craft Materials Institute, Inc. are certified in a program of toxicological evaluation by a medical expert, subject to review by the Institute's Toxicological Advisory Board to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems.

In addition, products bearing the CP Seat meet specific requirements of materials, workmanship, working qualities and color described in the appropriate Product Standard issued by The Art and Craft Materials Institute, Inc. or other recognized standards organization.

## Section III - PHYSICAL DATA

BOILING RANGE: NOT APPLICABLE

VAPOR DENSITY: ☐NOT APPLICABLE, MHEAVIER, ☐LIGHTER, THAN AIR

EVAPORATION RATE: [] NOT APPLICABLE. ☐FASTER, SISLOWER, THAN ETHER

PERCENT VOLATILE BY VOLUME: () ()

specific gravity: Less than 2

#### Section IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATAGORY:

None

FLASH POINT: TO NOT APPLICABLE

N/A

EXTINGUISHING MEDIA: [X] NOT APPLICABLE - no fire or explosion hazard

UNUSUAL FIRE AND EXPLOSION HAZARDS: IXI NONE

SPECIAL FIRE FIGHTING PROCEDURES: [X] NONE

THRESHOLD LIMIT VALUE:	TLV Not established for whole product. Non-toxic - Bears AP Seal - Conforms to ASTM D4236.
EFFECTS OF OVEREXPOSURE	
	None
In	POOLED LOCAL
EMERGENCY AND FIRST AID F	
	Not applicable.
	Section VI - REACTIVITY DATA
STABILITY: [] UNSTABLE INCOMPATIBILITY (materials to	STABLE CONDITIONS TO AVOID: NOTE
HAZARDOUS DECOMPOSITION	Incovered plazes will
HAZARDOUS POLYMERIZATION	N: □ мау оссия ⊠ WILL NOT оссия сомытюмь то avoid harden up. Keep lid on liquid glaze while in storage.
	Section VII - SPILL OR LEAK PROCEDURES
STEPS TO BE TAKEN IN CASE	MATERIAL IS RELEASED OR SPILLED. Clean with paper towel and wet sponge.
WASTE DISPOSAL METHOD:	Dispose of paper towel in trash and rinse wet sponge.
	Section VIII - SPECIAL PROTECTION INFORMATION
RESPIRATORY PROTECTION:	
	N/A
VENTILATION:	Not needed
	ot necued ot needed
OTHER PROTECTIVE EQUIPME	Not needed
	Section IX - SPECIAL PRECAUTIONS
PRECAUTIONS TO BE TAKEN I	N HANDLING AND STORING:
N	one
OTHER PRECAUTIONS:	
, . N	one

Section V - HEALTH HAZARD DATA