## Ashiand Chemical Company ....

DIVISION OF ASHLAND OIL, INC.

~ MATERIAL SAFETY DATA SHEET

Lucimmin

P.O. EOX 2219, COLUMBUS, OHIO 43216 • (614) 889-3333 PAGE: SOD BICARBONATE USP 007461 ACCEPTED BY 0.5, H.A. AS ESSENTIALLY SIMILIAR TO 0.5, H.A. FORM 20 R #S
05 075
DATA SHEET NO: 0015597-001
LATEST REVISION DATE: 03/78-78060
PRODUCT: 3921007
INVOICE: ACCLOC
INVOICE DATE: 06/09/81 DISTRICT MANAGER
ASHLAND CHEMICAL COMPANY
ICRS DIVISION
P. O. BOX 302
SYRACUSE, NY 13206 ※本学学 INTERCOMPANY MAIL SECTION I-PRODUCT IDENTIFICATION GENERAL OR GENERIC ID: ALKALI HAZARD CLASSIFICATION: (99) NOT APPLICABLE SECTION II-HAZARDOUS COMPONENTS PERCENT INGREDIENT PEL >95 ( 1) SODIUM BICARBONATE ( 1): TLV NOT ESTABLISHED. SECTION III-PHYSICAL DATA REFINEMENT PROPERTY INITIAL BOILING POINT NOT APPLICABLE NOT APPLICABLE VAPOR PRESSURE NOT APPLICABLE VAPOR DENSITY NOT APPLICABLE SPECIFIC GRAVITY NOT APPLICABLE PERCENT VOLATILES NOT APPLICABLE EVAPORATION RATE SECTION IV-FIRE AND EXPLOSION DATA FLASH POINT (CLOSED CUP) NOT APPLICABLE NOT APPLICABLE LOWER EXPLOSIVE LIMIT EXTINGUISHING MEDIA: UNUSUAL FIRE & EXPLOSION HAZARDS: NOT APPLICABLE SECTION V-HEALTH HAZARD DATA PERMISSIBLE EXPOSURE LEVEL: NOT ESTABLISHED. EFFECTS OF OVEREXPOSURE: FOR PRODUCT EYES - CAN CAUSE IRRITATION.
SKIN - CAN CAUSE IRRITATION.
BREATHING - OF DUST CAN CAUSE DAMAGE TO NASAL AND RESPIRATORY PASSAGES.
IF SWALLOWED - BY NATURE OF PRODUCT PROBLEMS NOT EXPECTED, BUT INDUSTRIAL
PRODUCTS ARE NEVER MEANT TO BE SWALLOWED. FIRST AID: IF ON SKIN: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE. IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION. ALLOWED: GIVE TWO GLASSES OF WATER; INDUCE VOMITING IMMEDIATELY BY STICKING FINGER DOWN THROAT. CALL A PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IF BREATHED: REMOVE INDIVIDUAL TO FRESH AIR

HAZARDOUS POLYMERIZATION: CANNOT OCCUR STABILITY: STABLE

INCOMPATABLETY: AVOID CONTACT WITH:, STRONG MINERAL ACIDS.

SECTION VI-REACTIVITY DATA

## Ashland Chemical Company

MATERIAL SAFETY DATA SHEET

DIVISION OF ASHLAND OIL, INC.



P.O. EOX 2215, COLUMBUS, OHIO 43216 - (614) 865-3333

807461 SOD BICARBONATE, USF PAGE: SECTION VII-SPILL OR LEAK PROCEDURES STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SMALL SPILL: SWEEP UP MATERIAL ONTO PAPER. LARGE SPILL: SHOVEL MATERIAL INTO CONTAINERS. THOROUGHLY SWEEP AREA OF SPILL TO CLEAN UP ANY RESIDUAL MATERIAL WASTE DISPOSAL METHOD: SMALL SPILL: FLUSH DOWN DRAIN WITH LARGE AMOUNTS OF WATER. LARGE SPILL: DEPOSIT IN A LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL Regulations. SECTION VIII-PROTECTIVE EQUIPMENT TO BE USED RESPIRATORY PROTECTION: IF NEEDED USE A NIOSH/MSHALJOINTLY APPROVED DUST RESPIRATOR. (ASK YOUR SAFETY EQUIPMENT SUPPLIER) VENTILATION: PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST)
VENTILATION TO MAINTAIN EXPOSURE BELOW LEVEL OF OVEREXPOSURE (FROM KNOWN, SUSPECTED OR APPARENT ADVERSE EFFECTS). EYE PROTECTION: WEAR SAFETY GLASSES IN COMPLIANCE WITH OSHA REGULATIONS. (CONSULT YOUR SAFETY EQUIPMENT SUPPLIER) OTHER PROTECTIVE EQUIPMENT: NORMAL WORK CLOTHING COVERING ARMS AND LEGS. SECTION IX-SPECIAL PRECAUTIONS OR OTHER COMMENTS CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH ASHLAND OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.