INK FOR BIC® DRY ERASE MARKER (ALCOHOL BASED)

45090

FEB 2002

JAN 31 2012

SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

PRODUCT NAME:

INK FOR: BIC® DRY ERASE MARKER (all colors)

SUPPLIER:

BIC / CONTE S.A.

6, rue Gerhard Hansen

BP 349

62 205 BOULOGNE SUR MER CEDEX, France

TELEPHONE:

FAX:

33(0) 3 21 87 77 77

33(0) 3 21 87 77 09

EMERGENCY TELEPHONES:

33 (0) 3 21 87 77 77

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances classified as dangerous for the health by european directive 67/548/EEC and

amendments :

INGREDIENT NAME:

CAS No.:

CONTENT

SYMBOL

RISK :

Propyl alcohol Ethyl alcohol 71-23-8 64-17-5 10 < < 60 % 10 < < 80 % F, Xi

R11, R41, R67

R11

3. HAZARDS IDENTIFICATION

F:R11 Highly flammable.

XI: R41

in normal conditions of use, the ink contained in the marker is not classified hazardous for the health.

4. FIRST AID MEASURES

GENERAL:

Summary of first aid is as follows:

INHALATION:

Remove victim immediately from source of exposure. Get medical attention. Perform artificial

respiration if breathing has stopped.

INGESTION:

DO NOT induce vomiting. Get medical attention immediately.

SKIN:

Wash skin thoroughly with soap and water. Continue to rinse for several minutes. Get medical attention

promptly if symptoms occur after washing.

EYES:

Rinse the eye with water immediately. Continue to rinse for several minutes. Contact physician if

irritation persists.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:

Water, CO2, powder.

SPECIAL FIRE FIGHTING PROCEDURES:

Use approved self-contained breathing apparatus and other protective equipment

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS IN SPILL:

Bulk releases are not anticipated under normal conditions.

PRECAUTIONS TO PROTECT ENVIRONMENT:

None known. Treat as a highly flammable liquid.

SPILL CLEAN-UP METHODS:

Contain and absorb liquid. Take contact with specialist to clean the residues.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS:

Keep away from heat, sparks and open flame.

STORAGE PRECAUTIONS:

Keep in cool, dry, ventilated storage and closed containers. Keep away from heat, sparks and open flame.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

EXPOSURE LIMITS:

VME (Propyl Alcohol):

Short-term value: 625 mg/m3, 250 ml/m3 Long-term value: 500 mg/m3, 200 ml/m3

VME (Ethyl Alcohol):

Short-term value: 9500 mg/m3, 5000 ml/m3 Long-term value: 1900 mg/m3, 1000 ml/m3

OTHER PROTECTION:

Under normal conditions of use specific protection is not needed.

HYGIENIC WORK PRACTICES:

Wash at the end of each work shift and before eating, smoking and using the tollet.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:

Liquid

COLOUR:

Varying

ODOUR/TASTE:

Alcohol odour

SOLUBILITY IN WATER:

soluble in water

BOILING POINT : DENSITY/SPECIFIC GRAVITY (g/ml) : 78°C (173°F) 0.82 – 0.88

0.8

. .

VAPOUR PRESSURE (mmHg): EVAPORATION RATE (ethyl ether: 1):

.14.5 11

11 4000 /55

FLASH POINT (°C):

13°C (55°F)

closed cup

10. STABILITY AND REACTIVITY

STABILITY:

Normaly stable

CONDITIONS TO AVOID:

Avoid heat, flames and other sources of ignition.

HAZARDOUS POLYMERIZATION:

Will not polymerize.

pressure: 760 mmHg

temperature:20°C (68°F)

temperature: 20°C (68°F)

MATERIALS TO AVOID:

Strong oxidizing agents. Strong reducing agents.

HAZARDOUS DECOMP. PRODUCTS:

Carbon oxides and various hydrocarbons formed when burned.

11. TOXICOLOGICAL INFORMATION

For the marker using:

Under normal condition of use, the risk phrase R41 is not applicable in « hazards identification » paragraph 3 because the ink is contained in the fiber reservoir of a small capacity marker.

For the ink manipulation:

R 41 Risk of serious damage to eyes

ROUTE OF ENTRY:

Eye contact.

12. ECOTOXICOLOGICAL INFORMATION

Not known.

13. DISPOSAL CONSIDERATIONS

PACKAGING DISPOSAL METHODS:

Dispose of in accordance with Local Authority requirements.

PREPARATION DISPOSAL METHODS:

Dispose of in accordance with Local Authority requirements.

14. TRANSPORT INFORMATION

The transport regulations concern ink and not markers containing this ink.

LABEL FOR CONVEYANCE:

ADR ROAD TRANSPORT:

UN No. ROAD: 1263 ADR CLASS No. : Class 3

ADR CLASS: HAZARD No. (ADR):

33 Highly flammable liquid (flash-point below 23°C). PAINT, n.o.s., Class 3, 3°b, in limited quantities PROPER SHIPPING NAME:

IMDG SEA TRANSPORT:

UN No. SEA: 1263 IMDG CLASS : 3.2 MARINE POLLUTANT: N/A.

PAINT, n.o.s., in limited quantities PROPER SHIPPING NAME:

IATA AIR TRANSPORT:

UN No., AIR: 1263 ICAO CLASS: 3 AIR PACK GR.:

PROPER SHIPPING NAME: PAINT, n.o.s.,

15. REGULATORY INFORMATION

The labelling regulation is not applicable for the marker. Only ink in tank is concerned :

SYMBOL AND INDICATION OF DANGER: F, Highly flammable

INK FOR BIC® DRY ERASE MARKER (ALCOHOL BASED)

FEB 2002

Xi: R41

RISK PHRASES:

R 11, R 41.

SAFETY PHRASES:

S26, S39.

EU DIRECTIVES :

Dangerous Substances Directive 67/548/EEC as amended. General Preparations Directive 88/379/EEC

16. OTHER INFORMATION

INFORMATION SOURCES:

Material Safety Data Sheets, Misc. suppliers.

The information contained herein is believed to be correct and corresponds to the latest state of scientific and technical knowledge. However, no warranty is made, either express or implied, regarding its accuracy or the results obtained from the use of such information.

The user is responsible for taking the necessary measures to meet the requirements of laws and regulations in force.