## U.S. DEPARTMENT OF LABOR

Occupational Safety and Health Administration

Form Approved OMB No. 44-R1387

## MATERIAL SAFETY DATA SHEET 9000 21

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

	SECTION I
MANUFACTURER'S NAME W.M. BARR & COMPANY:	EMERGENCY TELEPHONE NO. 901-775-0100
ADDRESS (Number, Street, City, State, and ZIP Code) 2105 Channel Avenue	Memphis, TN 38101
CHEMICAL NAME AND SYNONYMS Liquid Hand Cleaner	TRADE NAME AND SYNONYMS Black & Decker KH-50
CHEMICAL FAMILY Hand Cleaner	FORMULA Proprietary (250)

SECTIO	N II—	HAZAF	RDOUS INGREDIENTS		<del>,</del>
PAINTS, PRESERVATIVES, & SOLVENTS	% Wt.	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS		PPM	BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
Order Less SOLVENTS Mineral Spirits	35	500	FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS	j	,
OTHERS Propylene Glycol	<b>&lt;</b> 5				
HAZARDOUS	MIXTUF	ES OF OT	HER LIQUIDS. SOLIDS, OR GASES	%	TLV (Units)
		,			,
		·			
				-	

		SECTION III—PHYSICAL DATA*				
176 403 <b>°</b> F	SPECIFIC GRAVITY (H₂O = 1)	.894				
± 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	C PERCENT. VOLATILE BY VOLUME (%)	95.0				
	EVAPORATION RATE (Ether = 1) Slower Than Ether					
	STONES. THESE					
1		Dirits 1 @ 37.8 °C PERCENT. VOLATILE  0.08 @ 20°C  EVAPORATION RATE				

SECTION IV	-FIRE AND EXPLOSI	ON HAZARD DATA	1	
FLASH POINT (Method used)	FLAMMA	FLAMMABLE LIMITS		Uei
121°F Via Set Flash CC	Combus	stible Class II	1.0	
EXTINGUISHING MEDIA Use NFPA Cla	s ABC Extinguishers (C	Carbon Dioxide or Dry Powd	er)	
SPECIAL FIRE FIGHTING PROCEDURES N	ne Required			
UNUSUAL FIRE AND EXPLOSION HAZARDS	ne Known			

	SECTION V—HEALTH HAZARD DATA
THRESHOLD LIMIT VALUE	See Section II
EFFECTS OF OVEREXPOSURE	Acute: None Recognized
· 人名英格兰克尔	Chronic: None Recognized
EMERGENCY AND FIRST AID PRO If swallowed - do r	CEDURES not induce vomiting. Call your Poison Control Center, hospital
emergency room or p	physician immediately. Eve contact - flush with water. If
	s, get medical attention.

SECTION VI—REACTIVITY DATA							
STABILITY	UNSTABLE		CONDITIONS	TO AVOID			
1	STABLE	XX					
INCOMPATIBILITY (Ma	terials to avoid)						
HAZARDOUS DECOM	POSITION PRODUCTS		<u></u>				
HAZARDOUS POLYMERIZATION	MAY OCCUR			CONDITIONS TO AVOID			* D
	WILL NOT O	CUR	XX			•	
				<u> </u>			

SECTION VII—SPILL OR LEAK PROCEDURES  STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED  N/A				
WASTE DISPOSAL METHOD	N/A			
	N/A			

SECTION VIII—SPECIAL PROTECTION INFORMATION				
RESPIRATORY PRO	DTECTION (Specify type) N/A			
VENTILATION	LOCAL EXHAUST	SPECIAL		
N/A	MECHANICAL (General)	OTHER	18.18.1	
PROTECTIVE GLOV	/ES N/A	EYE PROTECTION N/A		
OTHER PROTECTIV	VE EQUIPMENT N/A		-	

SECTION IX—SPECIAL PRECAUTIONS	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	
OTHER PRECAUTIONS	

PAGE (2) GPO 930-5-40 Form OSHA-20 Rev. May 72

B & D FORM 9105