MATERIAL SAFETY DATA SHEET

MANUFACTURER'S NAME: KLEAN-STRIP, DIVISION OF

W.M. BARR & COMPANY 2105 CHANNEL AVENUE

P.O. BOX 1879

-MEMPHIS, TENNESSEE

DATE PREPARED: 7-85

TELEPHONE NUMBER: (901) 775-0100

SECTION I - PRODUCT IDENTIFICATION

FORMULA NUMBER: 1660 PRODUCT NUMBER: LO-45

PRODUCT NAME : BOILED LINSEED OIL '

PRODUCT CLASS: THINNER

INGREDIENT PROSESTATION AND THE TRANSPORT OF THE PROPERTY OF T	CAS#	PERCENT WT.	OCCUPATIONAL EXPOSURE LIMITS TLV PEL		VAPOR PRESSURE MM °C
LINSEED OIL	8001-26-1	100	NE	NE	0.001 250
The state of the s		•			
SECTION III Boiling Range: 343°F Vapor Densi					

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammability Classification: LOSHA CLASS-IIIB Flash Point 250°F TCCLel. NA

DOT COMBUSTIBLE LIQUID

Extinguishing Media: Use Carbon Dioxide, Dry Powder or Foam. Westerning which see to be

Unusual Fire and Explosion Hazards: All oily clothes should be spread to dry in any airy spot or stroyed at once. They are subject to spontaneous combustion.

Special Firefighting Procedures: Self-contained respiratory protection should be provided for firefighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up.

Angle Angl

inagonal at configuration of anthropies, a minure of the property

SECTION V - HEALTH HAZARD DATA

Effects of Overexposure: Short Term Effects - Inhalation - None recognized. Ingestion - Not determined. Dermal - None recognized. Long Term Effects - None recognized.

Primary Route(s) of Entry: Dermal Inhalation Ingestion X

Medical Conditions Prone To Aggravation By Exposure: None recognized.

Emergency and First Aid Procedures: Eye Contact - Flush with large quantities of water for at least 15 minutes. If irritation persists, get medical attention. If Swallowed - Call your hospital emergency room, poison control center or physician immediately for instructions.

SECTION VI - REACTIVITY DATA

Stability: Unstable Stable X
Hazardous Polymerization: May Occur Will Not Occur X

Hazardous Decomposition Products: None recognized.

Incompatibility (Material to Avoid): Strong oxidizing agents.

SECTION VII - SPILL AND LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released or Spilled: Flush large spills of material into suitable retaining area or containers with large quantities of water. Small spills can be absorbed by appropriate inert absorbent.

Waste Disposal Method: Dispose in accordance with applicable local, State and Federal regulations See Unusual Fire and Explosion Hazards under Section IV.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection: Usually none required.

Ventilation: Usually none required.

Protective Gloves: Usually none required.

Eye Protection: Safety glasses, chemical goggles and/or face shields are recommended to safeguard against potential eye contact, irritation or injury.

Other Protective Equipment: Usually none required.

Hygienic Practices: Before reuse, thoroughly clean any clothing or protective equipment which has been containated by prior use. See Unusual Fire and Explosion Hazards under Section IV.

SECTION IX - SPECIAL PRECAUTIONS TAXABLE FOR SECTION OF THE SECTIO

Precautions To Be Taken In Handling And Storage: Do not store near flames or at elevated

temperatures.

Other Precautions: Read carefully all cautions and directions on product label before use.

Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to local regulations.