

M A T E R I A L S A F E T Y D A T A S H E E T

MANUFACTURER: KLEAN-STRIP, DIVISION OF
W.M. BARR & COMPANY
2105 CHANNEL AVENUE
P.O. BOX 1879
MEMPHIS, TENNESSEE

DATE PREPARED: 10/01/85

TELEPHONE NUMBER: (901) 775-0100

BILL JEVIS
ONONDAGA WALLPAPER AND
PAINT COMPANY, INC.
124 HEADSON DRIVE
SYRACUSE NY 13214

SECTION I - PRODUCT IDENTIFICATION

FORMULA NUMBER: 1675
PRODUCT NUMBER: PLA-98
PRODUCT NAME : PLASTIC JUG PAINT THNR-SUPER FLEXI
PRODUCT CLASS : ~~WATER-BASED~~ PAINT-SOLVENT

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS#	PERC WT	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE
			TLV	REL IMM	
1. MINERAL SPIRITS	164741-41-9	<100	100 ppm	500 ppm	2
					20

SECTION III - PHYSICAL DATA

BOILING RANGE: 310 THRU 405 F
EVAPORATION RATE: Slower Than Ether.
VAPOR DENSITY: Heavier Than Air.
% VOLATILE: 100.0 LBS/Gal : 6.450

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASS: OSHA-Class II
DOT-Not Regulated.
FLASH POINT: 105F Seto LEL: 1.0
c/c

EXTINGUISHING MEDIA: Use Carbon Dioxide, Dry Powder or Foam.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep container tightly closed. Isolate from heat, electrical equipment, sparks, open flames and hot surfaces.

SPECIAL FIREFIGHTING PROCEDURES: Self-contained respiratory protection should be provided for firefighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up.

SECTION V - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Inhalation X Ingestion X Dermal X

EFFECTS OF OVEREXPOSURE - SHORT TERM EFFECTS:

INHALATION - May cause watering of eyes, headache, dizziness, nausea and irritation of respiratory tract. Severe overexposure may cause anesthesia, unconsciousness and death.
INGESTION - May be harmful or fatal if ingested. May cause nausea and gastrointestinal irritation.

SKIN CONTACT - None expected.

EYE CONTACT - May cause irritation. May cause conjunctivitis of eyes.

EFFECTS OF OVEREXPOSURE - LONG TERM EFFECTS:

May cause skin irritation on prolonged or repeated contact. Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY OVEREXPOSURE: None recognized.

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION - If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

INGESTION - DO NOT induce vomiting. Call your poison control center, hospital emergency room or physician immediately.

SKIN CONTACT - Wash with soap and large quantities of water and seek medical attention if irritation from contact persists.

EYE CONTACT - Flush with large quantities of water for at least 15 minutes. If irritation from contact persists, get medical attention.

SECTION VI - REACTIVITY DATA

STABILITY: Stable.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and carbon dioxide.

INCOMPATIBILITY (MATERIAL TO AVOID): Strong oxidizing agents.

SECTION VII - SPILL AND LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Avoid breathing vapors. Ventilate area. Flush large spills of material into suitable retaining area or containers with large quantities of water. Small spills can be absorbed by appropriate inert absorbent.

WASTE DISPOSAL: Dispose in accordance with applicable local, state and federal regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: For OSHA controlled work place, use only with adequate ventilation under engineered air control systems designed to provide maximum appropriate TLV. For occasional use where engineered air control is not feasible, use NIOSH approved respirators. For occasional consumer use, use only with adequate ventilation.

VENTILATION: Adequate ventilation must be provided. See respiratory protection above.

PROTECTIVE GLOVES: Use impermeable gloves to prevent skin irritation.

EYE PROTECTION: Safety glasses, chemical goggles and/or face shields are recommended to safeguard against potential eye contact, irritation or injury.

OTHER PROTECTIVE EQUIPMENT: Varying application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc.

HYGIENIC PRACTICES: Wash hands thoroughly after use.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not store near flames or at elevated temperatures.

OTHER PRECAUTIONS: Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to local regulations.

NOTE: THE INFORMATION CONTAINED HEREIN IS FURNISHED WITHOUT WARRANTY OF ANY KIND. EMPLOYERS SHOULD USE THIS INFORMATION ONLY AS A SUPPLEMENT TO OTHER INFORMATION GATHERED BY THEM AND MUST MAKE INDEPENDENT DETERMINATION OF SUITABILITY AND COMPLETENESS OF INFORMATION FROM ALL SOURCES TO ASSURE PROPER USE OF THESE MATERIALS AND THE SAFETY AND HEALTH OF EMPLOYEES. ANY USE OF THIS DATA AND INFORMATION MUST BE DETERMINED BY THE USER TO BE IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

89145538916000