U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

Form Approved OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

806461

| | | | neg (29 CFR 1915, 1916, 1917) | | | |
|--|---------------------------------------|----------------|---|---------------------------------------|--------------|--|
| | | SECT | TION I | | | |
| MANUFACTURER'S NAME | EMERGENCY T | ELEPHONE N | 0. | | | |
| BECT CHEMICAL COMPAN | NC. | (315) 432-0023 | | | | |
| ADDRESS (Number, Street City, State, and ZIP 6100 Mautz Road, P.O. Box | Code) 6488 | | Syracuse, New York | | | |
| CHEMICAL NAME AND SYNONYMS | | <u> </u> | TRADE NAME AND SYNOR | NYM5 | | |
| CHEMICAL FAMILY Blend of Surfactants | & Sc | lvent | Professional G | lass Cle | aner | |
| | ···· | | | | | |
| | N II - | | RDOUS INGREDIENTS | | | |
| PAINTS, PRESERVATIVES, & SOLVENTS | % | TLV (Units) | ALLOYS AND METALLIC COAT | INGS 9 | 6 (Units) | |
| PIGMENTS | N/A | | BASE METAL | N/ | 'A | |
| CATALYST | N/A | | ÁLLOYS | N/ | 'A | |
| VEHICLE | N/A | | METALLIC COATINGS | N/ | 'A | |
| SOLVENTS | 8.5 | 50 | FILLER METAL PLUS COATING OR CORE FLUX | N/ | : | |
| ADDITIVES | N/A | | OTHERS | 7 | | |
| OTHERS | | | | | | |
| HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES | | | | | | |
| | · · · · · · · · · · · · · · · · · · · | | | * | (0.11,10) | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| SEC | TION | III - P | HYSICAL DATA | | | |
| BOILING POINT (°F.) | 21 | 2° F | SPECIFIC GRAVITY (H2O=1) | | 008 | |
| VAPOR PRESSURE (mm Hg.) | | | PERCENT, VOLATILE BY VOLUME (%) | | •998 •900 | |
| VAPOR DENSITY (AIR=1) | | | EVAPORATION RATE | | 100 | |
| SOLUBILITY IN WATER | | plete | (1) | | | |
| APPEARANCE AND ODOR Clear Blue | | *********** | Slight Solvent Odor | <u> </u> | | |
| | | | | | | |
| | FIRE | AND E | XPLOSION HAZARD DATA | | | |
| FLASH POINT (Method used) None | | | FLAMMABLE LIMITS | Lei | Uel | |
| EXTINGUISHING MEDIA | | | | | | |
| SPECIAL FIRE FIGHTING PROCEDURES | | | | · · · · · · · · · · · · · · · · · · · | | |
| | | | | | | |
| JNUSUAL FIRE AND EXPLOSION HAZARDS | <u>`</u> | | | | | |

| | | SECTION | V · HEA | LTH HAZARD D | DATA | | |
|---|----------------------|---|---------------------|---------------------------------------|-----------------------|--|--|
| THRESHOLD LIMIT | 767 1 | Establ | ished. | | | | |
| EFFECTS OF OVER | # | | | kin contact. | -may dry skin. | | |
| | | 2 E | | | | | |
| EMERGENCY AND | FIRST AID PROCEL | oures In | case o | f eye contac | ct, flush thoroughly. | | |
| <u> </u> | | · | | · · · · · · · · · · · · · · · · · · · | | | |
| • | , | | | | | | |
| | | SECTIO | ON VI - P | EACTIVITY DA | TA | | |
| STABILITY | UNSTABLE | | CONDITIONS TO AVOID | | | | |
| | STABLE | XX | | • | | | |
| INCOMPATABILITY | (Materials to avoid) | | | | | | |
| HAZARDOUS DECO | MPOSITION PROD | UCTS | | | | | |
| HAZARDOUS | MAY OCC | UR | | CONDITIONS TO | AVOID | | |
| POLYMERIZATION | WILL NOT | OCCUR | XX | | | | |
| | | | | | | | |
| | 050 | T-1011111 | | OD LEAK BROOK | PEDITIES | | |
| STEPS TO BE TAKE | | | | OR LEAK PROC | | | |
| STEPS TO BE NAME. | | | | Мор ир | to avoid slipping. | | |
| | | | | | | | |
| WASTE DISPOSAL | METHOD | | <u> </u> | | - | | |
| | Norm | al met | hods. | | | | |
| | | | | | | | |
| | | ··· ·································· | | | | | |
| | SECTIO | N VIII - | SPECIAL | PROTECTION IN | IFORMATION | | |
| RESPIRATORY PRO | TECTION (Specify | type) No | t Neede | d . | | | |
| VENTILATION | LOCAL EXHAUS | | | • | SPECIAL | | |
| | MECHANICAL (| General) | - | | OTHER | | |
| PROTECTIVE GLO | VES Normally | Not N | eeded. | EYE PROTECTION | Normally Not Needed. | | |
| OTHER PROTECTIV | | | | | | | |
| | | | | 7 | | | |
| SECTION IX - SPECIAL PRECAUTIONS | | | | | | | |
| PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Avoid freezing and overheating. | | | | | | | |
| | | | | | | | |
| OTHER PRECAUTION | ONS | | | | | | |
| | | | | | | | |

PAGE (2) 6P0 930-540 Form OSHA-20 Rev. May 72