

# MOORE'S INTERIOR WOOD FINISHES

## QUICK DRY SANDING SEALER

A Varnish Product for Interior Use

Features fast dry, easy sanding without gumming, exceptional sealing and holdout. Does double duty on all types of unfinished or stained interior wood surfaces. Can be used as a sanding sealer under enamel or varnish (except urethane based products). It is especially suited as a filler, wash coat sealer or full sealer on new or resanded wood floors to be finished with any of Moore's Interior Clear Finishes (except urethane based products). Can also be used as an independent and complete finishing system for doors, cabinets and paneling (not for use as a finish coat on floors).

### COVERAGE

Approximately 400-450 sq. ft. (37.1-41.8 sq. meters) per gallon.

### SURFACE PREPARATION

Surfaces to be finished must be clean, smooth, and dry. Fill open-grained

woods with BENWOOD Paste Wood Filler according to label directions before applying sealer.

### APPLICATION

Brush on Sanding Sealer liberally in an even coat and allow to dry thoroughly. Sand lightly between coats with very fine sand paper. Two to three coats are necessary when used as a complete finishing system—one to two coats when used as a sealer under varnish or enamel. Apply as received in the container. Do not thin. Quick Dry Sanding Sealer produces a clear, durable, satin finish.

### DRYING

Dries for sanding in two to three hours.

### CLEAN UP

Clean brushes and equipment in mineral spirits.

MOORE'S and BENWOOD are registered trademarks of Benjamin Moore & Co.

E-413 00-J  
Non-Volatile (Zinc Stearate, Vinyl Toluene-Inseed  
Copolymer, Driers) 40.0%  
Volatile (Naphthalene) 60.0%

(P)


BENJAMIN MOORE & CO., MONTVALE, NJ 07645 - NEW YORK OFFICE, 511 CANAL STREET - MANUFACTURING LOCATIONS IN NEWARK • BOSTON • RICHMOND • JACKSONVILLE • CLEVELAND • CHICAGO • ST. LOUIS • HOUSTON • BIRMINGHAM • DENVER • LOS ANGELES • SANTA CLARA • TORONTO • MONTREAL • VANCOUVER

**CONTAINS PETROLEUM SOLVENTS:** Keep away from heat, sparks and open flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Avoid prolonged contact with skin. Do not take internally. Close container after each use.

**Use only with adequate ventilation.**

**KEEP OUT OF THE REACH OF CHILDREN. (12T)**

**NOTICE:** Reports have associated permanent brain and nervous system damage with repeated, prolonged overexposure to solvents among persons engaged in the painting trade. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.



# Wood Finishes


## Quick-Dry Sanding Sealer

**Seals  
Sands Easily  
Dries Quickly**

**CLEAR 413 00**  
32 FL. OZ. (1 QUART) 946 ml.

# Benjamin Moore & Co.

**WARNING!**  
FLAMMABLE  
See cautions on back panel.



FEB 23 1990

Grassroots Construction Co.  
941 Spencer St.  
Syracuse, NY 13204

FEB 23 1990

Grassroots Construction Co.  
941 Spencer St.  
Syracuse, NY 13204