

800755

MATERIAL SAFETY DATA SHEET

For Coating, Resins, and Related Materials NPCA 1-84

MANUFACTURER'S NAME
BENJAMIN MOORE & CO.
51 CHESTNUT RIDGE RD.
MONTVALE, NJ 07645EMERGENCY TELEPHONE NO.
201-344-1200DATE OF PREPARATION
30-NOV-88INFORMATION TELEPHONE NO.
201-344-1200**SECTION I - PRODUCT ID**

PRODUCT CODE: 251-03,4A,70,73,76

HMIS - Health: 0

CLASS: WATER THINNED PAINT

Flammability: 0

NAME: MOORCRAFT VINYL LATEX FLAT

Reactivity: 0

COLOR: BASE 4 AND COLORS

Personal Prot.: B

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	CAS NO.	TLV	PEL	MM HG	TEMP
Ethylene Glycol	2.3 - 2.5	107-21-1	50 ppm	Not	.1	@ 77 F
Crystalline Silica*	1.1 - 1.3	14808-60-7	.1 mg/m3	Estab. mg/m3	.1	Not Applicable

* Hazardous only as dust when product is sanded.

Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the report requirements of sect. 313 of the Emergency Planning & Community Right-To-Know Act of 1986 and of 40 CFR 372:

CAS #	Chemical Name	Percent by Weight
107-21-1	Ethylene Glycol	2.5% max

SECTION III - PHYSICAL DATABOILING RANGE: N/A VAPOR DENSITY: HEAVIER THAN AIR WEIGHT PER GALLON: 10.8
EVAPORATION RATE: SLOWER THAN ETHER % VOLATILE VOLUME: 68.0 - 72.6**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**FLAMMABILITY CLASSIFICATION: NOT REGULATED FLASH POINT: >250°F PMCC LEL: Not Applicable
EXTINGUISHING MEDIA: FOAM CO2 DRY CHEMICAL WATER FOGUNUSUAL FIRE AND EXPLOSION HAZARDS:
Closed containers may burst if exposed to extreme heat or fire.
Toxic gases may form when product burns.SPECIAL FIREFIGHTING PROCEDURES:
Cool exposed containers with water. Use self-contained breathing apparatus.**SECTION V - HEALTH HAZARD DATA**EFFECTS OF OVEREXPOSURE - ACUTE:
Inhalation - Irritation of the respiratory tract.
Skin and Eye Contact - Primary irritation.
Ingestion of large amounts could cause serious injury.

EFFECTS OF OVEREXPOSURE - CHRONIC:
None Known

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:
None expected when used in accordance with Safe Handling and Use Information (Section VIII).

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION INGESTION

EMERGENCY AND FIRST AID PROCEDURES:

Inhalation - Remove to fresh air. Get medical help for any breathing difficulty.

Eye Contact - Flush thoroughly with water. Call physician.

Skin Contact - Wash with soap and water.

Ingestion - Drink 1 or 2 glasses of water to dilute. Do NOT induce vomiting. Call physician.

SECTION VI - REACTIVITY DATA

STABILITY: STABLE

HAZARDOUS POLYMERIZATION WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Burning may produce carbon dioxide and carbon monoxide.

CONDITIONS TO AVOID: Elevated temperatures

INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
Flush with water. Absorb with sawdust or rags.

WASTE DISPOSAL METHOD:
Conventional procedures in compliance with local, state and federal regulations.
Do not incinerate sealed containers.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:
Use NIOSH approved respirator specified for protection against paint spray mist and sanding dust in restricted or confined areas.

VENTILATION:
Adequate to maintain working atmosphere below T.L.V. and L.E.L. (See Sect. II for ingredient data and concentrations). Mechanical exhaust may be required in confined areas.

PROTECTIVE GLOVES: Waterproof during repeated contact.

EYE PROTECTION: Splash goggles or safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: Clothing adequate to protect skin.

HYGIENIC PRACTICES:
Remove and wash clothing before reuse. Wash hands before eating, smoking or using the washroom.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:
Do not throw or drop containers.

OTHER PRECAUTIONS:
Avoid contact with eyes and prolonged contact with skin or breathing of spray mist or sanding dust.
Close container after each use. Keep out of reach of children. Do not take internally.