Rev. 05B DATA SHEET MATERIAL SAFETY For Coating, Resins, and Related Materials NPCA 1-84 Manufacturer's Name Emergency Telephone No. 800-424-9300 (CHEMTREC) BENJAMIN MOORE & CO.

51 CHESTNUT RIDGE RD MONTVALE, NJ 07645

Date Prepared Last Rev Date Information Telephone No.

12-15**-**97

201-573-9600

For the most up-to-date MSDS information please vieit our website www.benjaminmoore.com/mads/go.html

SECTION I - PRODUCT ID

** HMIS CODE **

PRODUCT* 276 n276

HEALTH: 1

CLASS: WATER THINNED PAINT

FLAMMABILITY: 0

NAME: MOORCRAFT SUPER SPEC LATEX SEMI-GLOSS ENAMEL

REACTIVITY: 0

COLOR: ALL

PERSONAL PROT:

** SARA TITLE 312 **

ACUTE: N CHRONIC: N FIRE: N PRESSURE: N REACTIVITY: N For a complete description of HMIS and an explanation of the PERSONAL PROT: code, see Section XX. *NOTE: In the PRODUCT code a little n can be any capital letter of the

alphabet except P or Q.

SECTION II HAZARDOUS INGREDIENTS

INGREDIENT STEL CEIL MM Hg \mathtt{TLV} PELHAZ SARA MAX & CAS #

Titanium Dioxide

Y N 19.3 013463-67-7 10 mg/M3 10 mg/M3 N/E N/E N/A

Hydrous Alum Silicates

v N 7.4 001332-58-7 10 mg/M3 10 mg/M3 N/E N/E N/A

NOTE: This product contains no reported or suspected carcinogens Note: This product contains pigments which may become a dust nuisance when removed by abrasive blasting, sanding, or grinding. This product may contain small amounts of materials known to the State of California to cause cancer and reproductive harm.

SECTION III PHYSICAL DATA

BOILING RANGE: N/A WT/GALLON: 9.1 to 10.2 %VOL BY VOLUME: 67.6 to 68.8 EVAPORATION RATE: SLOWER THAN ETHER VAPOR DENSITY: HEAVIER THAN AIR

SECTION IV FIRE AND EXPLOSION HAZARD DATA

D.O.T. FLAMMABILITY CLASS. NOT REGULATED FLASH POINT: > 250 F PMCC

LEL: Not Applicable

EXTINGUISHING MEDIA: FOAM CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Toxic gases may form when product burns.

Closed containers may burst if exposed to extreme heat or fire.

SPECIAL FIRE FIGHTING PROCEDURES:

Cool exposed containers with water. Use self-contained breathing apparatus.

Page 2

MSDS#: 276, n276

SECTION V HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE - ACUTE:

Inhalation - Irritation of the respiratory tract.

Skin and Eye Contact - Primary irritation.

Ingestion of large amounts could cause serious injury.

EFFECTS OF OVEREXPOSURE - CHRONIC:

None Known

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

None expected when used in accordance with Safe Handling and Use

Information (Section VIII) -

DERMAL INHALATION INCESTION PRIMARY ROUTE(S) OF ENTRY:

EMERGENCY AND FIRST AID PROCEDURES :

Inhalation - Remove to fresh air. Get medical help for any breathing

difficulty.

Eye Contact - Flush thoroughly with water. Call physician.

Skin Contact - Wash with soap and water.

Ingestion - Drink 1 or 2 glasses of water to dilute.

DO NOT induce vomiting. Call physician.

SECTION VI REACTIVITY DATA

STABILITY: STABLE HAZARDOUS POLYMERIZATION WILL NOT OCCUR

CONDITIONS TO AVOID: Elevated temperatures

HAZARDOUS DECOMPOSITION PRODUCTS:

Burning may produce carbon dioxide and carbon monoxide.

INCOMPATABILITY (MATERIALS TO AVOID); None reasonably foreseeable.

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Flush with water. Absorb with sawdust or rags.

WASTE DISPOSAL METHOD:

Conventional procedures in compliance with local, state and federal regulations. Do not incinerate sealed containers.

SECTION VIII SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:

Use NIOSH approved respirator specified for protection against paint spray mist and sanding dust in restricted or confined areas.

VENTILATION:

Adequate to maintain working atmosphere below T.L.V. and L.E.L.

(See Sect. II for ingredient data and concentrations). Mechanical exhaust

may be required in confined areas.

PROTECTIVE GLOVES: Waterproof during repeated contact.

EYE PROTECTION : Splash goggles or safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: Clothing adequate to protect skin.

HYGIENIC PRACTICES:

Remove and wash clothing before reuse. Wash hands before eating, smoking or using the washroom.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not throw or drop containers.

MSDS#: 276, n276

Page 3

OTHER PRECAUTIONS :

Avoid contact with eyes and prolonged contact with skin or breathing of spray mist or sending dust.

Close container after each use. Keep out of reach of children. Do not take internally.

SECTION XX

HMIS (Hazardous Materials Identification System) (R) NPCA
HMIS is a recognized workplace Hazard Communications System as required by
OSHA (29 CFR 1910.1200). Information on establishing a compliant hazardous
communication program using HMIS is available from:

American Labelmark Co., Inc., Labelmaster Division 5724 N. Pulaski Rd., Chicago, IL 60646 1-800-621-5808

The ratings assigned by Benjamin Moore & Co. are only suggested ratings; the contractor/employer has ultimate responsibility for HMIS rating where this system is used.

PERSONAL PROTECTION: This code is left blank on Benjamin Moore & Co. MSDS's as it depends on application technique and the workplace ventilation. Please read Sections II through IX of this MSDS before deciding on appropriate protective equipment and beginning work. There are codes available for this section which can be obtained from Labelmaster. Note: There are no SARA reportable materials in this product.

DISCLAIMER

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For additional information, contact the USEPA/Lead Information Hotline at 1-800-LEAD-FYI.