

Material Safety Data Sheet 97-5254
QUICK IDENTIFIER (In Plant Common Name)
BEROL PRISMACOLOR 900 Series

Manufacturer's Name: Berol USA, Division of Empire Berol Corp.
Address: Pencil St., Shelbyville, TN 37160
Emergency Telephone No.: (615) 684-4133
Other Information: (615) 684-4133
Signature of Person Responsible for Preparation: [Signature]
Date Prepared: February 18, 1988

SECTION 1 - IDENTITY

Common Name (used on label): BEROL PRISMACOLOR 900 Series Pencil
Trade Name & Synonyms: Not Applicable
Chemical Name: Not Applicable
Chemical Family: Not Applicable
Formula: Proprietary

SECTION 2 - HAZARDOUS INGREDIENTS

Principal Hazardous Component(s) (chemical & common name(s))
Pencil products bearing the PMA Certification Mark of the Pencil Makers Association, Inc., are not within the scope of the OSHA Hazard Communication Standard. Pencils are articles, not chemicals, 29 CFR 1910.1200 (b) (5).
Pencil products bearing the PMA Certification Mark are certified in a program of toxicological evaluation by a medical expert subject to review by the program's Toxicological Review Board to contain no materials in sufficient quantities to offer an acute or chronic health hazard to humans.
No acute or chronic health labeling is required under provisions of federal law, the Federal Hazardous Substances Act or under ASTM Standard D4236, a standard for labeling art materials for chronic hazard.
Pencils are certified as non-toxic under the PMA Program.

SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS (Fire & Explosion Data)

Boiling Point: Not Applicable
Specific Gravity (11.0 = 1): Not Applicable
Vapor Pressure (mm Hg): Not Applicable
Percent Volatile by Volume (%): Not Applicable
Vapor Density (Air = 1): Not Applicable
Evaporation Rate: Not Applicable
Solubility in Water: Not Applicable
Reactivity in Water: Not Applicable
Appearance and Odor: Colored extruded rod in painted wood case.

Flash Point: Not Applicable
Flammable Limits: Not Applicable
Lower: Not Applicable
Upper: Not Applicable
Extinguisher Media: Not Applicable
Auto Ignition Temperature: Not Applicable
Special Fire Fighting Procedures: Pencil Products stored in bulk are subject to ignition by fire and may, in the case of fire, release toxic and other irritating gases. A self-contained breathing apparatus should be used when there is a potential exposure to combustion products of pencils burning in bulk.
Unusual Fire and Explosion Hazards: Not Applicable

011290

2 #600

SECTION 4 - PHYSICAL HAZARDS

Stability Unstable ☐ Conditions Stable ☒ to Avoid

Incompatibility (Materials to Avoid) None

Hazardous Decomposition Products See Fire and Explosion Data

Hazardous Polymerization May Occur ☐ Conditions Will Not Occur ☒ to Avoid

SECTION 5 - HEALTH HAZARDS

Threshold Limit Value Not Applicable

Signs and Symptoms of Exposure 1. Acute Overexposure None

2. Chronic Overexposure None

Medical Conditions Generally Aggravated by Exposure None

Chemical Listed as Carcinogen or Potential Carcinogen

National Toxicology Program Yes ☐ No ☒

I.A.R.C. Monographs Yes ☐ No ☒

OSHA Yes ☐ No ☒

OSHA Permissible Exposure Limit Not Applicable

ACGIH Threshold Limit Value Not Applicable

Other Exposure Limit Used Not Applicable

Emergency and First Aid Procedures SEE HEALTH HAZARD DATA

1. Inhalation

2. Eyes

3. Skin

4. Ingestion

SECTION 6 - SPECIAL PROTECTION INFORMATION

Respiratory Protection (Specify Type) None

Ventilation None Local Exhaust None Mechanical (General) None Special None Other None

Protective Gloves None Eye Protection None

Other Protective Clothing or Equipment None

SECTION 7 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions to be Taken in Handling and Storage Store away from high temperatures and open flames.

Other Precautions None

Steps to be Taken in Case Material is Released or Spilled Sweep up.

Waste Disposal Methods Normal trash disposal.

IMPORTANT

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

1 0 2 3 9 0

IDENTITY (As Used on Label and List)
Createx Poster/Fabrics - All colors & extender

Manufacturer's Name
Color Craft Ltd.
Address (Number, Street, City, State, and ZIP Code)
P.O. Box 936
Avon, CT 06001

Emergency Telephone Number
203-282-0020

Telephone Number for Information
203-282-0020

Date Prepared
August 15, 1987

Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information			Other Limits Recommended	% (optional)
Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV		
None				

Section III — Physical/Chemical Characteristics			
Boiling Point	200-210°F	Specific Gravity (H ₂ O = 1)	1.3
Vapor Pressure (mm Hg.)	N/A	Melting Point	52%
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1) vs. Ether	Slower

Water extendable

Paste: odor-free or slight acrylic odor

Flash Point (Method Used)				
None				

Water or CO₂ Foam

Special Fire Fighting Procedures

Special Fire Fighting Procedures
None; standard fire fighting procedures

Unusual Fire and Explosion Hazards
None; product itself is non-flammable and will not support combustion

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

733
U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)
Pearlescent Pigments-All Colors

Note: Blank spaces are not permitted. If any item is not applicable, or no
information is available, the space must be marked to indicate that.

Section I	
Manufacturer's Name Color Craft Ltd.	Emergency Telephone Number 203-282-0020
Address (Number, Street, City, State, and ZIP Code) P.O. Box 936	Telephone Number for Information 203-282-0020
Avon, CT 06001	Date Prepared August 15, 1987
	Signature of Preparer (optional) <i>James Simbo</i>

Section II — Hazardous Ingredients/Identity Information				
Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
None				

PH of 10% Solution=8.5			
Section III — Physical/Chemical Characteristics			
Boiling Point	200-210°F	Specific Gravity (H ₂ O = 1)	1.3
Vapor Pressure (mm Hg.)	N/A	Melting Point	52%
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1) vs. Ether	Slower

Solubility in Water Water extendable			
Appearance and Odor Paste; odor-free or slight acrylic odor			
Section IV — Fire and Explosion Hazard Data			
Flash Point (Method Used) None	Flammable Limits	LEL	UEL
Extinguishing Media Water or CO ₂ Foam			
Special Fire Fighting Procedures None; standard fire fighting procedures			

Unusual Fire and Explosion Hazards None; product itself is non-flammable and will not support combustion			
---	--	--	--