

MATERIAL SAFETY DATA SHEET

608
TRANSPORTATION

PRODUCT NAME	Super Undercoating (Aerosol) #05034	#	MSDS005034
MANUFACTURED BY:	CRC CHEMICALS	Phone	(215) 674-4300
885 LOUIS DRIVE, WARMINSTER, PA. 18974			

1. INGREDIENTS	CAS #	ACGIH TLV	OSHA PEL	Other Limits	%
Asphalt	8052-42-4	NA	NA	5mg/M ³	53
Mineral Spirits	8030-30-6	NA	NA	100	27
Propane	74-98-6	NA	1000		20
Propane functions as propellant for this aerosol package.					
Pressure = 55 psig at 70°F.					
Contains no chemicals found in Section 313 of SARA Title III.					

2. PHYSICAL DATA

Specific Gravity	NA	Vapor Pressure	NA	% Volatile	47
Boiling Point	NA	Evaporation Rate	Moderate		
Freezing Point	NA	Vapor Density	Heavier than air		
Appearance and Odor Black viscous material - solvent odor					
Solubility Limited solubility in water - less than 1%					

3. FIRE AND EXPLOSION DATA

Flashpoint	<20°F	Method	TOC	Flammable Limits	NA
Extinguishing Media	Fog, foam, Carbon dioxide			LEL	UEL
Unusual Hazards	Aerosol containers may burst at temperatures above 130°F.				

4. REACTIVITY AND STABILITY

Stability	Stable
Hazardous decomposition products	Thermal - Carbon monoxide
Materials to avoid	Strong oxidizing agents

5. PROTECTION INFORMATION

Ventilation	Mechanical if vapor conc. above TLV.		
Respiratory	Self-contained breathing apparatus for concentration above TLV.		
Gloves	Solvent Resistant	Eye & Face	Safety goggles
Other Protective Equipment	Not required for aerosol usage.		

6. HEALTH HAZARD DATAPrimary Routes of Entry Inhalation & Skin

Signs and Symptoms of Exposure

1. Acute Overexposure Inhalation - headaches and nausea. Mist may cause breathing problems. Skin - may cause drying of skin. Eyes - Vapors may cause burning and irritation.
2. Chronic Overexposure Prolonged exposure to skin may cause burning problems.

Medical Conditions Generally Aggravated by Exposure NAChemical Listed as Carcinogen
or Potential CarcinogenNational Toxicology
ProgramYes ☐
No ☒IARC
MonographsYes ☐
No ☒

OSHA

Yes ☐
No ☒Emergency and First Aid Procedures (If symptoms persist call a physician)

1. Inhalation Remove to fresh air - apply artificial respiration if necessary.
2. Eyes Flush with water for at least 15 minutes.
3. Skin Wash with soap and water.
4. Ingestion Do not induce vomiting - call a physician.

7. SPILL OR LEAK PROCEDURESPrecautions to be taken in
Handling and StorageStore in a cool dry area.

Steps to be taken in case

Materials is released or spilled Usually not an aerosol problem. Ventilate area, remove sources of ignition. Use absorbant material to pick up waste material.Waste Disposal Discarded filled cans or partially used cans are hazardous waste. Observe Federal, State and Local regulations.**8. SPECIAL PRECAUTIONS AND USE DIRECTIONS**Aerosol cans may explode if their contents are heated above 130°F.PREPARED BY: A. B. Reed

ORIGINAL DATE OR DATE OF REVISION

9-89