

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration

(Non-Mandatory Form)

Form Approved

OMB No. 1218-0072

102390

IDENTITY (As Used on Label and List)

Creutex Poster/Fabrics - All colors & extender

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name

Color Craft Ltd.

Emergency Telephone Number

203-282-0020

Address (Number, Street, City, State, and ZIP Code)

P.O. Box 936

Telephone Number for Information

203-282-0020

Date Prepared

Avon, CT 06001

August 15, 1987

Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))

OSHA PEL

ACGIH TLV

Other Limits
Recommended

% (optional)

None

Section III — Physical/Chemical Characteristics

Boiling Point

200-210°F

Specific Gravity (H₂O = 1)

1.3

Vapor Pressure (mm Hg.)

N/A

Melting Point

52%

Vapor Density (AIR = 1)

N/A

Evaporation Rate

(Butyl Acetate = 1) vs. Ether

Slower

Solubility in Water

Water extendable

Appearance and Odor

Paste; odor-free or slight acrylic odor

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)

None

Flammable Limits

LEL

UEL

Extinguishing Media

Water or CO₂ Foam

Special Fire Fighting Procedures

None; standard fire fighting procedures

Unusual Fire and Explosion Hazards

None; product itself is non-flammable and will not support combustion

