

## Here's a new idea in floor cleaners...

## NO-RINSE non-alkaline FLOOR CLEANER

More than a highly efficient cleaner, it's a money saver, too. Saves money because it saves labor by eliminating the need for rinsing required by most other types of cleaners. Fool-proof. Can't dull floor finish when used at recommended dilutions. Contains optical brighteners to give floors a bright, sparkling, "clean as a whistle" look.

Thoroughly cleans dirt, grease, grime, and traffic soil—even including black heel marks. Will not mar or damage floor finish; will not cause blushing, hazing or dulling of shine and sheen. Original floor

lustre snaps back like new with each cleaning.

Specifically recommended for resilient flooring where modern high gloss, metal interlocked finishes have been used. For routine cleaning by damp mopping or light scrubbing dilute with 40 parts water. For heavier floor cleaning with automatic scrubbers dilute with 20 parts water.

(See other side for specifications, use directions, and packaging details.)

UNITED CLEANING & MAINTENANCE

SYRACUSE, NY 13206

#### NON-ALKALINE FLOOR CLEANER

#### Description:

A new idea in floor cleaners designed to solve a "people problem" and save money at the same time. Severe dulling of floor finish after cleaning usually occurs with most cleaners because of insufficient rinsing. Morever, the rinsing step itself is time consuming and thereby costly. This new product eliminates those problems because it eliminates rinsing.

A non-alkaline cleaner, it efficiently removes dirt, grease, grime, and traffic soil. Dries film-free. Non-streaking. Leaves no "blush" or film as many all-purpose cleaners do when not properly rinsed. Unlike most cleaners, it can't mar, damage, or dull a floor's finish. Not designed for floor stripping or extremely heavy duty cleaning requiring high potency. Specifically recommended for use on high gloss, metal interlocked finishes and in routine floor maintenance programs involving regularly scheduled and frequent floor cleaning.

#### **Directions for Use:**

For routine cleaning by damp mopping or light scrubbing:

Use 1 part cleaner with 40 parts water.

For heavier floor cleaning with automatic scrubbers:

Use 1 part cleaner with 20 parts water.

Can be used with automatic equipment in any dilution. Low sudsing. Never needs rinsing. Dries without streaking. Contains OPTICAL BRIGHTENERS to give floors a bright, sparkling "clean as a whistle" look.

#### Specifications:

Form Clear yellow liquid
Specific Gravity 1.004
Lbs./Gal. 8.38
pH 7.3 ± .01
Detergent Non-ionic
Solvent None
Free Fatty Acid as Oleic .056%

### Packaging:

55 gallon drums30 gallon drums5 gallon poly pails1 gallon poly jugs 6/case

## MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I	
Harley Chemicals Div., Concord Chemical Co., Inc.	EMERGENCY TELEPHONE NO. 609-966-1526
ADDRESS (Number, Street, City, State, and ZIP Code) 17th & Federal Streets, Camden, New Jersey 08105	
N/A TRADE	NAME AND SYNONYMS
Nonylphenoxypoly(Ethyleneoxy)Ethanol FORMULA N/	

SECTION II - HAZARDOUS INGREDIENTS  PAINTS, PRESERVATIVES, & SOLVENTS   *   TLV   ALLOYS AND METALLIS COATINGS				1	TLV
TAMES, MESERVATIVES, & BULVERIS		(Units)	ALLOYS AND METALLIC COATINGS	*	(Units
PIGMENTS			BASE METAL		
CATALYST	·		ALLOYS	7	
/EHICLE			METALLIC COATINGS		
OLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		<u> </u>
ADDITIVES			OTHERS		
OTHERS				_	
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES					TLV (Units
					101111

•	SEC	TION III - P	HYSICAL DATA		
BOILING POINT (°F.)		212	SPECIFIC GRAVITY (H20=1)	-	1.0
VAPOR PRESSURE (mm,Hg.)	same	as water	PERCENT, VOLATILE BY VOLUME (%)		95.8
VAPOR DENSITY (AIR-1)	same	as water	EVAPORATION RATE	same	as water
SOLUBILITY IN WATER		complete			
APPEARANCE AND ODOR		<del></del>	•	<u> </u>	L


	SECTION IV - FIRE AND	EXPENSION HAZARD DAT	ſΑ	
FLASH POINT (Method used)		FLAMMABLE LIMITS	Lei	Uei
EXTINGUISHING MEDIA	Nonflammable			
SPECIAL FIRE FIGHTING PE				
UNUSUAL FIRE AND EXPLO	osion hazards None			· · · · · · · · · · · · · · · · · · ·
				· · · · · · · · · · · · · · · · · · ·

		5	FCLION	١٧.	HEA	LTH HAZARD DATA	13
THRESHOLD LIME	-	N/A					
EFFECTS OF OVER	REXPO	SURE N/A					
•		- <u></u>			<del></del> -		
EMERGENCY AND	FIRST	AID PHOCEDU	RES				<del> </del>
	······································	li sp	lashed	in.	eyes	, flush with water.	
			<del></del>				
	·	<del></del>					
			SECTIO	ON V	l . R	EACTIVITY DATA	
STABILITY	UNS	TABLE				NS TO AVOID	
	<b> </b>	BLE	<b>-</b>	<del> </del>			
INCOMPATABILITY	1		X		·		
HAZARDOUS DECO		·-					
	MPUSI	TION PRODUC	:T <b>5</b>				
HAZARDOUS POLYMERIZATION				,-		CONDITIONS TO AVOID	
· · · · · · · · · · · · · · · · · · ·	•	WILL NOT O	CCUR		Х		
		*					
		SECTI	ON VII	- SI	PILL (	OR LEAK PROCEDURES	
TEPS TO BE TAKE	N IN C	ASE MATERIA	L IS REL	EASE	DORS	PILLED	<u> </u>
Mop ur	ori	flush with	water		<del></del>	•	
			Water	<u>.                                    </u>			
VASTE DISPOSAL M	ETHO	<u> </u>					
<u> </u>	<del></del> -			<u> </u>			
Bury or	pou	r into sew	er.				
•		<del></del>	····				
		SECTIONA					
ESPIRATORY PROT	· ·	SECTION V	111 - Si	,ECI	AL PI	ROTECTION INFORMATION	
NOTE OF	2(11112	en	,				:
ENTILATION '	LOCA	L EXHAUST None	requir	ed	-	SPECIAL	
	MECH	ANICAL (Gene None	ral) reguir	ed		OTHER	
None re	:5	· · · · · · · · · · · · · · · · · · ·				EYE PROTECTION None required	
THER PROTECTIVE	d an	eu	<del></del>			None required	1
Nia	EQUI	PMENT					
None re	quir	PMENT ed		-	·		
None re	equir		CTION I	Y .	SDEC		
RECAUTIONS TO BE	TAKE	SEC	CTION I	X ·	SPEC	IAL PRECAUTIONS	
	TAKE	SEC	CTION I	X .	SPEC		
	ТАКЕ	SEC	CTION I	X -	SPEC		
ECAUTIONS TO BE	E TAKE	SEC EN IN HANDLI Ed	CTION I	X -	SPEC		

PAGE (2)

GPC 934.1%

Form OSHA-20 Rev. May 72



The gloss of shimmering satin with the toughness of a coat of mail

# HI-BRITE LIQUID POLYMER FLOOR FINISH

It forms an invisible mesh of thousands of crosslinked metal-ions to give floors a finish of long lasting, lustrous beauty with superior resistance to wear, black marks, scuffing, and slipping. Like laying mesh over mesh, 2nd and 3rd coats make this durable finish stronger, more unyielding, and actually improves gloss. Great for high traffic areas in schools, hospitals, and institutions; banks, office and commercial buildings. The tough finish is so durable, it requires minimal maintenance, making it one of the most economical floor care products on the market today.

(See other side for specifications, use directions, and packaging details)

ror terrazzo, asphalt tile, vinyl, vinyl asbestos, rubber, linoleum, and other resilient flooring

- Self-polishing. No buffing required
- Gives a long lasting, beautiful, high gloss plastic finish to flooring.
- Superior resistance to wear, black marks, scuffing, and slipping.
- Easy to maintain. Needs only sweeping or damp mopping.
   Can be spray buffed.
- Can be cleaned repeatedly with detergent solutions (except those containing ammonia or amine compounds).
- Can be removed with Wax Stripper or ammoniated cleaners.

UNITED CLEANING & MAINTENANCE

SYRACUSE, NY 13206