



**SECTION 5. REACTIVITY DATA**

**Stability/Polymerization:** This product is stable under routine conditions of use and does not undergo hazardous polymerization.

**Chemical Incompatibilities:** Do not mix CORCRAFT Cross Link Floor Sealer with any other cleaning products. Do not use on aluminum. Carefully read and follow all directions and recommendations printed on this product's label. This product should not be used for any purpose other than its intended use.

**SECTION 6. HEALTH HAZARD INFORMATION**

**Carcinogenicity:** Neither the NTP, IARC, nor OSHA lists CORCRAFT Cross Link Floor Sealer or its ingredients as carcinogens.

**Summary of Risks:** Inhalation of misted or sprayed CORCRAFT Cross Link Floor Sealer may result in transient irritation of the nose, throat, and respiratory tract of sensitive individuals. Simply removing oneself from this exposure and breathing in fresh air for a few minutes should be sufficient to clear away the initial discomfort. Accidental splashes of this product into your eyes will cause irritation, redness, and discomfort. Possible allergic reactions from prolonged skin contact are possible in sensitive individuals.

**Medical Conditions Aggravated by Long-Term Exposure:** None reported.

**Target Organs:** Eyes, skin.

**Primary Entry:** Inhalation, skin contact/absorption.

**Acute Effects:** Eye irritation from accidental splashes and possible coughing from breathing in mists of this product.

**Chronic Effects:** Allergic skin reactions.

**FIRST AID**

**Eyes:** Immediately flush, including under the eyelids, gently but thoroughly with flooding amounts of running water for at least 15 minutes.

**Skin:** Prevent prolonged or repeated contact between this maintenance product and your skin, especially your hands, wrists, and forearms, because slight irritation may develop.

**Inhalation:** Walk to the nearest area of fresh air.

**Ingestion:** Do not ingest. Induce vomiting by sticking your finger to the back of the victim's throat or by giving him an emetic such as Syrup of Ipecac.

**SECTION 7. SPILL, LEAK, AND DISPOSAL PROCEDURES**

**Spill/Leak:** Spills of this product should be quickly mopped up because wet floors could cause people to accidentally slip and fall.

**Waste Disposal:** If this product becomes unusable for any reason, it must be disposed of in a manner consistent with all applicable Federal, state, and local regulations.

**SECTION 8. SPECIAL PROTECTION INFORMATION**

**Goggles:** In certain industrial situations wearing protective glasses is suggested to prevent accidental eye contact. Be especially careful not to get sprayed or misted product into your eyes.

**Gloves:** In certain industrial situations wearing protective rubber gloves is suggested when scrubbing floors with CORCRAFT Cross Link Floor Sealer to prevent chapping or drying of the skin on your hands.

**Respirator:** During routine situations where this product is used with excellent ventilation, a respirator is not usually used. Avoid intentionally or accidentally concentrating an airborne cloud of this product (from coating operations) and then breathing in these intense fumes from the airborne mist.

**Comments:** If used carefully, and not intentionally or accidentally misused, this product should present no unusual exposure effects to the user. Read and follow all directions and suggestions printed on the label of CORCRAFT Cross Link Floor Sealer. Never eat, drink, or smoke as you work with this product. Practice good personal hygiene procedures that prevent transferring this liquid from your hands to your mouth while eating, drinking, or smoking. Always wash carefully after using CORCRAFT Cross Link Floor Sealer and before eating, drinking, smoking, using the toilet facilities, or applying cosmetics.

**SECTION 9. SPECIAL PRECAUTIONS AND COMMENTS**

**Storage/Segregation:** Store this product in its original containers in a cool, dry, well-ventilated area. Protect these containers of CORCRAFT Cross Link Floor Sealer from physical damage and/or excessive heat. Do not transfer any of this liquid into other containers unless they are carefully labeled. Keep from freezing.

**Special Handling/Storage:** Use a first-in/first-out inventory rotation schedule to ensure this product is used in the same order it is received from the manufacturer or distributor. Do not transfer this floor sealer to aluminum containers because the active ingredients of CORCRAFT Cross Link Floor Sealer may be affected by prolonged contact with the inner aluminum surface.

Prepared by: PJ Igoe, BS; Industrial Hygiene Review: DJ Wilson, CIH; Medical Review: W Silverman, MD