MATERIAL SAFETY DATA SHEET

20157- all codes 20766-66 20767-44 20168-44 20182-66

Date Prepared: 06/28/91

I. PRODUCT IDENTITY

Product Name DEKA-PermAir

Description airbrush formulated fabric paint (waterbased)

24 hour Emergency Phone: 800-468-6942

II. HAZARDOUS INGREDIENTS

Following testing and formula evaluation, this product has been determined to be free of acute and chronic health hazards. This product and labeling conform to ASTM D4236.

III. PHYSICAL CHARACTERISTICS

Appearance Colored Liquid (paint)

Odor Slight Odor of Ammonia/fruity floral mask

Solubility in Water . . Dispersible

Specific Gravity . . . Greater than 1

Ph 8.5

Top Five Ingredients . . Water, Waterbased Binder (Polymer Mixture), Pigment Dispersion, Pearlescent Powder, Textile

Softener

IV. FIRE & EXPLOSION DATA

Flash Point Greater than 200 F

Extinguishing Media . . Water, Dry Chemical, CO2, Foam

Fire Fighting Procedure: While no special procedures are required

this product, firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and

irritating fumes.

Explosion Hazards . . . None Likely

V. REACTIVITY DATA

Stability Stable

Polymerization Not Applicable

Incompatibility . . . Oxidizing and reducing agents

Hazardous Decomposition Products: Burning may release CO; CO2; HCN; oxides of sulfur, nitrogen, or titanium; or

other potentially toxic fumes.

VI. HUMAN HEALTH DATA

When used in accordance with manufacturer's instructions in either home hobby or occupational setting, this product is believed to pose no acute or chronic health hazards.

VII. EMERGENCY & FIRST AID PROCEDURES

Eye Contact .		.Wash eyes carefully but immediately with large
		amounts of lukewarm water, occasionally lifting
·.		the upper and lower lids until no evidence of
		material remains. If discomfort continues or
	4	redness is observed, seek medical attention.

Skin Contact Wash skin with soap and water. Seek medical attention if irritation occurs.

Ingestion Seek medical advice if ingested. Qualified medical personnel may choose to remove the product by gastric levage and catharsis. Do not induce vomiting.

Inhalation Remove to fresh air. If breathing difficulty persists, call a physician.

VIII. RECOMMENDED HYGENIC PRACTICES

Whenever working with a special material such as this paint, users must take due precautions to protect their health. Avoid ingestion or eye contact. Avoid widespread prolonged skin contact. Wash hands before eating. Provide ventilation whenever spraying, and if heatsetting this product for extended periods in a confined area.

IX. PERSONNEL PROTECTION RECOMMENDATIONS

Eye Protection None normally required. Wear protective goggles if use is likely to cause spattering of product in the direction of the eyes.

Skin Protection None normally required, as minor short-term skin contact incidental to normal application should not be harmful. If use is likely to result in widespread prolonged skin contact, wear gloves and other protective clothing.

Ventilation Use local ventilation or a NIOSH-approved mask (for particulates) to avoid inhalation of paint mists. Provide ventilation if heatsetting in a confined area.

X. SPILL OR LEAK PROCEDURES

Spills should be confined and liquid taken up with absorbent materials and placed in containers for proper disposal.

Waste Disposal Method . Small consumer quantities may be poured out onto paper, allowed to dry, and disposed of with normal solid waste. Industrial quantities must be disposed of in accordance with existing federal, state and local environmental laws.

This information is based on data provided by our suppliers, and is accurate to the best of our current knowledge. The user must judge the suitability of this information for any particular purpose. No other warranty is given.