

MATERIAL SAFETY DATA SHEET

4144-00
4189-00

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

4131-20
-30

SECTION I

MANUFACTURER'S NAME DRI MARK PRODUCTS, INC.		EMERGENCY TELEPHONE NO. (516) 484-6200
ADDRESS (Number, Street, City, State, and ZIP Code) 15 HARBOR PARK DRIVE PORT WASHINGTON, NY 11050		
CHEMICAL NAME AND SYNONYMS N/A	TRADE NAME AND SYNONYMS MR. DOODLER & COLORMARKS MRKRS	
CHEMICAL FAMILY N/A	FORMULA WATER BASED	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS water soluble dyes up to	12		BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS water (approx)	75-84 %		FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS: surfactants	<1				
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
PROPYLENE GLYCOL (U.S.P.)				13	15%
Synthetic fiber reservoir and nib, plastic body					

SECTION III - PHYSICAL DATA

BOILING POINT (°F.) approximately	214°	SPECIFIC GRAVITY (H ₂ O=1)	>1.0
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT VOLATILE BY VOLUME (%)	N/A
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____ =1)	negligible
SOLUBILITY IN WATER	Complete		
APPEARANCE AND ODOR Colored, faint odor liquid			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	N/A	FLAMMABLE LIMITS	N/A	Lel	Uel
EXTINGUISHING MEDIA	Co ₂ , foam, water; ink is nonflammable				
SPECIAL FIRE FIGHTING PROCEDURES	Fire protective equipment				
UNUSUAL FIRE AND EXPLOSION HAZARDS	None				

V-1380