Tox: 014449 Product: BLACK PAINT (M17246) FNH1 : M1724GSE2 (1 QT CAN) APPROVED to ACTIVE NAAO prod. spec ESN-MIJ101-A. ----- Chemical and Physical Properties ---This material is a LIQUID under normal conditions. The results for Specific Gravity are not available. The Boiling Point is +110-+198 C. The Flash Point is +005 C (Setaflash). The results for pH are not available. * * * * * * Toxicology Review * * * * * Tox: 014449 Tox Status: C2 (COMPLETE TOX REVIEW) Last Revised: 03/19/87 ------ Hazardous Ingredients (HAZCOM) ---------- TLV --CAS number Chemical name 3.5mg/m3 TWA 1333-86-4 * CARBON BLACK 10mg/m3 (total dust) 7727-43-7 BARIUM SULFATE 2.5mg/m3 (FORD) TWA 8012-95-1 * PARAFFIN OIL 2mg/m3 (resp dust) 14807-96-6 * TALC * See chemical fact sheets (CFS) for additional details on these ingredients. ------ Signal Word --------WARNING FLAMMABLE IRRITATING TO EYES AND SKIN ---- Safe Handling and Storage ------AVOID CONTACT WITH EYES AVOID PROLONGED OR REPEATED SKIN CONTACT USE WITH ADEQUATE VENTILATION KEEP FROM HEAT, SPARKS, OR OPEN FLAME ---- Protective Measures and Treatments- --IMPERVIOUS GLOVES SAFETY GLASSES VENTILATION (CONTACT INDUSTRIAL HYGIENE FOR SPECIFIC DETAILS) THIS MATERIAL CONTAINS A SUBSTANCE REGULATED UNDER A SPECIFIC OSHA STANDARD. SEE CHEMICAL FACT SHEET FOR DETAILS IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK MEDICAL ADVICE WASH THOROUGHLY AFTER HANDLING ---- Toxicology Bulletins-------BARIUM COMPOUNDS

BARIUM COMPOUNDS
PETROLEUM LUBRICATING OILS (TB 101)

Tox: 014449 Product: BLACK PAINT (M1724G)

FNH1 : M1724GSE2 (1 QT CAN)

The chemical identification and properties for this material were provided by the manufacturer. Health and safety information has been evaluated by:

Environmental & Occupational Toxicology, Occupational Health & Safety, Ford Motor Company 900 Parklane Towers West, Dearborn, MI 48126

For emergency call: (313) 337-3182 -or- (313) 323-0045 (for 24 hour service)