

DATE OF PREPARATION **JAN 10 1986**

The information contained herein is based on data available to us and is believed to be correct. Since this information may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and Buyer may rely thereon only at Buyer's risk. We make no guarantee that the health and safety precautions we have suggested will be adequate for all individuals and/or situations involving its handling and use. No warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.

Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet.

HAZARD RATING

Section I

MANUFACTURER'S NAME

H.B. Fuller Company

STREET ADDRESS

1200 Wolters Boulevard

CITY, STATE, AND ZIP CODE

Vadnais Heights, Minnesota 55110

EMERGENCY TELEPHONE NO.

612-481-3300

PRODUCT CLASS

Epoxy Resin

MANUFACTURER'S CODE IDENTIFICATION

TRADE NAME

Resiweld®

FE-7235, Part A

DOT PROPER SHIPPING NAME Not a regulated material.

HEALTH

FIRE

SPECIFIC

REACTIVITY

PERSONAL PROTECTION: **B**

Section II - HAZARDOUS INGREDIENTS

INGREDIENT/CAS NUMBER	PERCENTAGE RANGE	OSHA PEL	ACGIH TLV	LEL	VAPOR PRESSURE mm Hg, 20°C
Epoxy resin	> 10	NE	NE	-	Nil

NA - NOT APPLICABLE

Section III - PHYSICAL DATA

NE - NOT ESTABLISHED

BOILING RANGE NA pH NA PERCENT VOLATILE BY WEIGHT 0.5 max. WEIGHT PER GALLON 9.7 lbs.

Section IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT

Greater than 200°F SETA.

EXTINGUISHING MEDIA

Carbon dioxide, foam, dry chemical.

UNUSUAL FIRE AND EXPLOSION HAZARDS

None known.

SPECIAL FIRE FIGHTING PROCEDURES

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

Section V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE

ACUTE Prolonged or repeated skin contact may cause moderate irritation. Eye contact may cause irritation. Potential dermal sensitizer. Inhalation is not a route of exposure.

CHRONIC

No anticipated chronic effects.

FIRST AID PROCEDURES

If in eyes: Flush immediately with water for at least 15 minutes. Consult a physician if irritation persists.

If on skin: Wash contact area with soap and water.

Section IV - REACTIVITY DATA

STABILITY: ☐ UNSTABLE ☒ STABLE

CONDITIONS TO AVOID Not established.

INCOMPATIBILITY (Materials to avoid)

Strong oxidizing agents.

HAZARDOUS COMBUSTION PRODUCTS

Incomplete combustion can yield low molecular weight hydrocarbons and carbon monoxide.

HAZARDOUS POLYMERIZATION ☐ MAY OCCUR ☒ WILL NOT OCCUR

CONDITIONS TO AVOID

Not established.

Section VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Wear rubber gloves and wipe up with absorbent material. Residue may be removed with chlorinated solvent.

WASTE DISPOSAL METHOD This product does not meet the definition of hazardous waste under 40 CFR 261. Landfill or incinerate in accordance with local and state regulations.

Section VIII - SPECIAL PROTECTION INFORMATION

EYE PROTECTION

Safety glasses.

SKIN PROTECTION

Rubber or polyethylene gloves.

Contaminated clothing should be laundered before reuse.

RESPIRATORY PROTECTION

Normally not required.

VENTILATION

Standard industrial ventilation.

Section IX - ADDITIONAL INFORMATION

No additional information.