MATERIAL SAFETY DATA SHEET

• Section 1 - PRODUCT IDENTIFICATION			
Manufacturer's Name			Emergency Phone
DEARBORN DIVISION, W. R. Grace & Company			312/438-8241
Address		-	
300 Genesee St., Lake Zurich, IL 60047			
Synonyms			Trade Name or Code Ide
Cooling water microbicide and	slimicide		DASA-105
• Section 2 -HAZARDOUS INGREDIENTS	CAS	NO. %	EXPOSURE CRITERIA
	•		
Alkyl Dimethyl Benzyl Ammonium Chloride	1075	00.0 - 10.5%	
Ammonlum Chloride	18/5	-92-9 12.5%	-
		-	
bis (Tri-n-Butyltin) Oxide	56	-35-9 2.25%	_
(i. 200) 2011 ,	3.0	20 3	
Tours Tours Hours		- 82.25%	
Inert Ingredients		02.25%	×
			NFPA: 2-0-0
Project Car Dama			
• Section 3 - PHYSICAL DATA		1	
Dadid Dad 760 Va	No data	Melting Point	NA.
Boiling Point, 760mm Hg Specific Gravity(H20=1)	1.0	Vapor Pressure@ 25	°C approx 21 mm Hg
Vapor Density (Air=1)	No data	Solubility in H ₂ O(
% Volatiles by Volume	No data	Evaporation Rate ,	
Appearance & Odor: Colorless liquid with			9 - 10
	aromatic o		
	aromacre o		
• Section 4 - FIRE & EXPLOSION HAZARD DATA			
Flash Point(and Method Used) Flammable	Limits in	Air, % by Volume	Auto Ignition Temperatu
Lowe	r	Upper	
None NA		NA NA	NA NA
EXTINGUISHING	 		_
MEDIA MACCE 1 VA	39 co₂ (3	Dry Chemical O	Other
SPECIAL FIRE FIGHTING PROCEDURES	1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -		in determinant og som en er
Fire fighters show	ıld wear fu	ll protective gear i	including breathing
apparatus.	TIC MEST 10	it protective gear .	
UNUSUAL FIRE AND EXPLOSION HAZARD	Company of the Compan		The second secon
None			 A fine control of the c
Hono			
			
• Section 5 - REACTIVITY DATA	. mr.Ov.c	TOTA	
CCDTTTO) (Manual comments)	TIONS TO A	AOTD	
O Stable O Unstable			
INCOMPATIBILITY (Materials to Avoid)			and the second second second
Strong	oxidizing	agents	
			
HAZARDOUS DECOMPOSITION PRODUCTS		en e	ان کے معاملے کی بھائے ہوئے ہوئے ہوئے۔ معمولاً میں بھائے کے انتہام کا انتہام کی انتہام کی انتہام کا انتہام کی انتہام کی جائے ہے۔
CO, CO	2, NH3	the state of the s	attention of the transfer of the same to
	<u>-</u>	OTD	,
HAZARDOUS POLYMERIZATION CONDIT	CIONS TO AV	OTH	
Ov. a Own New Occurs	* · · · ·		
O May Occur Will Not Occur	<u> </u>		(over)
•		· ·	

Continued)	
MATERIAL SAFETY DATA SHEET (Continued)	9.7
• Section 6 - HEALTH HAZARD INFORMATION	
EXPOSURE LIMIT	
Not established	
COURT	
EFFECTS OF OVEREXPOSURE	
INHALATION - Avoid prolonged exposure to vapors which	h may irritate nasal passages.
	to the second contractors
INGESTION - Harmful or fatal if swallowed. Avoid co	ntamination of food. Ural toxicity,
ID (match 2 008 mg/kg If indested contact Dhy	sician and give promptly milk, egg whites,
or gelatin solution. If these are not available	, give large quantity of water.
Induce vomiting by giving syrup of ipecac.	
CUIN OR EVE CONTACT - Causes eve damage and skin irri	tation.
Skin contact: Wash off area of	skin contact with soap and water.
Eyes: Flood eyes with water and	seek medical attention.
nyes: F1000 cycs	
EMERGENCY AND FIRST AID PROCEDURES	
See above	en e
•Section 7 - SPECIAL PROTECTION INFORMATION	
•Section / - SPECIAL PROTECTION IN OU	
VENTILATION REQUIREMENTS Mechanical exhaust should be	adequate.
Medianical emission onedate 4.	
RESPIRATORY PROTECTION (Specify Type) None special -	Do not breathe mist or vapors
	GLOVES (Specify Type)
FVF PROTECTION	
Goggles or face shield	Chemical gloves
OTHER PROTECTIVE CLOTHING AND EQUIPMENT (Specify Type)
Wear protective clothing to minimize skin	contact.
• Section 8 - SPILL OR LEAK PROCEDURES	1 1 1 - 1 - 1 - 1
THE WATER AS TO THE WATER AS IN KELLADED OR SELECTED	- Collect using absorbent, place in
container for proper disposal. Use up to	equal amounts of sodium oleate to
detoxify.	
WASTE DISPOSAL METHOD -Do not flush large quantities	to drain that could upset waste treatment
average Material should be disposed according to Era	LESCICIDE TUDET TUBETOCCTORS
treated with DAS A-105 should not be used for food p	processing, irrigation or in the manufactur
a c c t t museum a ffluent char	.14 not be discharged where it will drain
of paper used for food packaging. Treated effluent shou into lakes, streams, ponds, or public water. Do not con	ntaminate water by cleaning of equipment,
into lakes, streams, bonds, or photos	al of wastes. Apply this product only as
•Section 9 - SPECIAL PRECAUTIONS or dispose	
THE PROPERTY OF THE TAKEN IN MANULLING AND DIVING IN	drum. Rinse thoroughly with water and retu to drum reconditioner, or destroy by perfo-
Keep container closed and protect from freezing.	rating or crushing. Keep this product away
Freeze point, 24°F.	from heat or open flames.
OTHER PRECAUTIONS	
For industrial use only. Keep away from children.	
	u muundin Tilonii
Shipping Name: DOT Compound Industrial Process Wat	er Treating, Liquid
IATA	
	S. Morss
The data included herein are presented according to W. R. Grace & Co.'s	Prepared by
practices current at the time of preparation hereof, are made available solely for the consideration, investigation and verification of the	
and size a resistance hereof and do not constitute a respiesentation of	
warranty for which Grace assumes legal responsibility. It is the responsibility of a recipient of this data to remain currently informed	-100
	Date 5/86
was and to comply with all national, Inderel, State, and local laws	
regulations applicable to safety, occupational health, right to know	