MATERIA SALE DATA SHEET OSHA Ha ird Communication Standard (29 CFR 1910.1200



SIMILAR TO OSHA FORMS 20 AND 174 US Department of Labor Printed on 7/30/92 at 15:06:54

Material/Product Identity
Incredible White Mask Liquid Frisket

Color White Liquid

N/A

Seq. No. 4 ASTM D4236-89 Certification Regulatory Stātus

an bankan dalah dan perindakan memban bankan bankan berah diangkan berah dan berah dan berah dan berah dan ber

Rev. No. A Certified Product Not known to be regulated

MANUFACTURER'S NAME AND LOCATION SECTION I Graphic Arts Systems Inc. 19499 Miles Road Manufact. Name Address line 1 Address line 2 Address line 3 Info. Tel. No. Prep. Date Cleveland, OH 44128 USA Emerg. Tel. No. (800)468-6942 USA (800)447-2349 Contact Lawrence USA Katz Current per Brenda, Title 7/23/92 President

SECTION II

HAZARDOUS COMPONENTS/IDENTITY/STANDARDS/CONTENT INFORMATION

ACGIH TLV N/L 25 ppm CAS No. OSHA PEL STEL % COMP Ingredient Listing Mixture Latex Emulsion N/L/ 25 ppm 7664-41-7 Ammonia

This is a professional artist's product. It consists of a polymer solution with a small quantity of ammonia. The product has been evaluated for expected hazards that may occur in normal use by professional artists. Avoi excessive heat, avoid breathing mists and use with adequate ventilation. Avoid

PHYSICAL/CHEMICAL CHARACTERISTICS SECTION III

Deg. F Spec. Grav. (H2O=1) Boiling Point Melting Point Not App. Less than 1 N/K Vapor Density Same as Water Solubility Soluble Vapor Pressure Water-like Same as Water Evaporation Rate Water-like Odor slight ammonia odor Appearance Milky Aqueous Liquid

FIRE and EXPLOSION HAZARD DATA SECTION IV

Flash Point Not App. Deg. F. (Cel) Flash Pt. Mechod Limit Not App. Upper Flam. Limit Not App. Wepper Flam. Limit Not App. Water spray, dry chemical, CO2

Specialized Fire Burning dry latex produces dense black clouds of smoke. Fighting Proc. Wear self-contained breathing apparatus and protective clothing to prevent exposure to usual and expected combustion fumes. No unusual toxic gases are expected.

Unusual Fire & Expect the usual toxic gases to be produced; dried rubber Explosion Hazard may produce large amounts of black smoke.

SECTION V REACTIVITY DATA (Unstable) (yes/no) (Stable) Conditions Excessive Heat; freezing to avoid Incompat. (Avoid)
Haz. Decomp. (y/n)
Cond. to Avoid.

Solvents, acids, metals, salts may coagulate latex.

No Haz. Polym. (yes/no) No

As with any other organic material, combustion and flame in air may produce nitrogen oxides, carbon dioxide and carbon monoxide.

Confirm all information prior to use
Abbreviations: Not Applicable N/A.. Not Flammable N/F
Not Known N/K Ceiling Value Not Determined Not Listed N/D Respirable Fraction R
Permissible Exposure Limit PEL UNKWN Unknown Permissible Exposure Limit PEL ACGIH Threshold Limit Value TLV The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any intention or purpose. No other warranty is given. (TLV Reg. TM, ACGIH)



Enclosed to the second material and a first first for the second of the second second

SIMILAR TO OSHA FORMS 20 AND 174 US Department of Labor Printed on 7/30/92 at 15:06:58

Incredible White Mask Liquid Frisket quid ID # N/A Material Identity Incre Color

SECTION VI

HEALTH HAZARD DATA

Routes of Entry: Inhalation Low hazard; avoid inhaling mist if sprayed.
Skin Not likely to be absorbed Ingest. Not likely to be ingested
Health Hazards None expected from ordinary uses of the product; ammonia
content, while low, could irritate eyes if vaporized. Avoid
eye and skin contact. If sprayed, use adequate cross
ventilation. If sprayed or applied by air brush or air gun,
avoid breathing mist. Use a NIOSH approved mask suitable for eye and skin contact. If sprayed, use adequed ventilation. If sprayed or applied by air beavoid breathing mist. Use a NIOSH approved liquid aerosols.

NTP Carcinogen N/L OSHA C Signs/Symptoms None expected but eye irritation may occur..

OSHA Carcinogen N/L of Exposure Medical Conditions None known. Avoid wearing contact lenses if eye contact

to Avoid First Aid is possible. If contact with eyes occurs, rinse with lukewarm, clean water for 15 minutes; contact a physician if irritation occurs. Skin contact, wash with water. Measures

PRECAUTIONS FOR SAFE HANDLING AND USE SECTION VII

Contain and collect for disposal.
Observe all federal, state and local laws concerning Spill Waste Disp health and environment. None known; use caution as spill area may be slippery. None known. Precautions

Other Precautions

CONTROL MEASURES

SECTION VIII

Not usually required but a suitable mask for aerosls and mists should be worn if material is to be sprayed in Resp. Protect.

large quantity.
Not usually required but required if sprayed..
None usually required.
None required except if sprayed.

Local Exhaust Spec. Local. Exh.

Mech. Exhaust Other Mech. Exhaust Protect. Gloves None

Vinyl or rubber gloves.
Not required for ordinary uses of this product
None specifically required; artist smock suggested.
Standard industrial practice for the handling of artist
materials should be used.. Eye Protect Protect. Clothing Work Practices

LABEL STATEMENTS
Acute Toxicity Signal Word 1 No Acute Health Labeling Required
Acute Phrase 1 DO NOT TAKE INTERNALLY. AVOID CONTACT WITH EYES.
Acute Phrase 2 KEEP OUT OF REACH OF CHILDREN.
Acute Phrase 3 Refer to MSDS for additional information.

Refer to MSDS for additional information. Acute Phrase 2 KEEP OUT OF REACH OF CHILDREN.
Acute Phrase 3 Refer to MSDS for additional information.
Chronic Toxicity Chronic Signal No chronic health labeling required Chronic Phrase 1 Chronic Phrase 2 Chronic Phrase 3

ASTM D4236 Complies with ASTM D4236-89 Certification Assurance

Confirm all information prior to use
Abbreviations: Not Applicable N/A.. Not Flammable N/F
Not Known N/K
Respirable Fraction R Ceiling Value Not Determined Not Listed N/D UNKWN N\L Unknown Permissible Exposure Limit PEL ACGIH Threshold Limit Value TLV The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any intention or purpose. No other warranty is given. (TLV Reg. TM, ACGIH)

POISINDEX INFORMATION SYSTEM PRODUCT INFORMATION FORM - SUBMITTED ON 7/30/92

Brand/Product Name Incredible White Mask Liquid Frisket White Liquid Color Name Product Sizes 4.5 and 8.5 Fluid Ounce; Larger sizes may be ordered. Use/Application Art Material Catalog/Reg. # N/A Color I.D. Name Index # N/A N/A Product Color(s) N/A Formula Date Prior to 1992 State (pH if Liq.) 9.20 Industr Use (Y/N) Yes Unknown Consumer Use (Y/N) **Viscosity** Yes Entry into Market Before 1992 Children's Use (Y/N) Unlikely Graphic Arts Systems Inc. Manufacturer's Name, Address & 19499 Miles Road , Cleveland Telephone Number OH 44128 USA (800) 447-2349

Toxicity Information, Contact Dr. Jaeger at 201-666-7929 or 800-468-6943

Chemical Ingredients

Latex Emulsion

Ammonia

CAS #/ID #/Color Index # % H/L or Range
Mixture < 100%
7664-41-7 < 5 %

2



Material/Product Identity Incredible White Mask Liquid Frisket

White Liquid

N/A

Seq. No. 4
ASTM D4236-89
Certification
Regulatory Stātus

Rev. No. A Certified Product Not known to be regulated

Manufact. Name Address line 1 Address line 2 Address line 3 Info. Tel. No. Prep. Date

Graphic Arts Systems Inc.
19499 Miles Road
Cleveland, OH 44128
USA Emerg. Tel. No. (800) 468-6942 USA
(800) 447-2349 Contact Lawrence
7/23/92 Title President

是是在"大大","是是是这个时间,我们就是**是是他们的现在,我们是是一个工作的。**但是这种的人的,但是是一个人的人,他们就是我们的,他们也不是一个人的人的人,他们就

Katz

REQUIRED LABEL STATEMENTS

Conformity Phrase

Complies with ASTM D4236-89

Acute Signal Word Acute Phrase 1 Acute Phrase 2

No Acute Health Labeling Required DO NOT TAKE INTERNALLY. AVOID CONTACT WITH EYES. KEEP OUT OF REACH OF CHILDREN.

Refer to MSDS for additional information.

Chronic Signal Word No chronic health labeling required Chronic Phrase 1 Chronic Phrase 2 Chronic Phrase 3

Acute Phrase 3

Mis'c Warning Word KEEP OUT OF REACH OF CHILDREN

