MATERIAL SAFETY DATA SHEET

3632-02

MANUFACTURER: HOUSTON ART & FRAME

DATE: 3-30-88

ADDRESS: CITY, STATE, ZIP

P. O. Box 56146 Houston, Tx 77256

EMERGENCY PH. NO. (713) 622-7042

-----SECTION 01 -- IDENTIFICATION OF PRODUCT-----

TRADE NAME: Gold Leaf Sealer

PROD #218

PRODUCT CLASS: Solvent Thinned | Coating

------SECTION 02 --- HAZARDOUS COMPONENTS OF MIXTURES-----

Components

Percent

TLV-ACGIH

Vap.Pres.

Mineral Spirits Petroleum Naptha

21.6 100 ppm 1mm Hg @ 68F 52.1 300 ppm 1mm Hg @ 68F

-----SECTION 03 --- PHYSICAL DATA ----

ODOR: Ketone BOILING POINT: 135 E310 F BOILING POINT: 135 E310 F VAPOR PRESSURE: 1 mm Hg @68 F VAPOR DENSITY: Heavier than air SOLUBILITY IN WATER: Insoluble MELTING POINT: SPECIFIC GRAVITY: PERCENT VOLATILE: 75.7 EVAP. RATE: Slower than ether WT/ GALLON: 7.06

------SECTION 04 --- FIRE AND EXPLOSION HAZARD DATA-----

FLASH POINT: 85 F-P.M.C.C. Dry LEL 1.0% Combustible FIRE EXTINGUISHER MEDIA: Foamm Dry Chem. CO2, 820 spray SPECIAL FIRE FIGHTING PROCEDURE: Do not use water stream on burning liquid. Cool exposed containers with water. UNUSUAL FIRE AND EXPLOSION HAZARDS: Extremely flammable. Keep containers closed when notin use. Isolate from flame and sparks. Avoid tobacco smoking when working with this material.

-----SECTION 05 --- HEALTH HAZARD DATA -----

ACGIH TLV (OSHA PEL): SEE SECTION O2 EFFECTS OF OVER EXPOSURE: METHANGL VAPORS CAUSE LOCAL IRRITATION OF EYES, HEADACHE, SENSATION OF HEAT, FATIGUE AND DROWINESS. CAUTION -- MAY BE HARMFUL IF SWALLOWED. INHALATION OF VAPORS IN EXCESS OF TLV CAUSES RESPIRATORY IRRITATION AND CENTRAL NERVOUS SYSTEM EFFECT. IRRITATING TO EYES AND SKIN.

'EMERGENCY FIRST AID PROCEDURE: INHALATION -- REMOVE TO FRESH AIR AND GIVE ARTIFICIAL RESPRIATION OR OXYGEN IF NEEDED. INGESTION-INDUCE VOMITING IF VICTIM IS CONSCIOUS. CALL A PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS BETSON GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. CONTACT -- WASH SKIN WITH SOAP AND WATER. FLUSH EYES WITH PLENTY OF WATER FOR 15 MIN. CALL A PHYSICIAN IF IRRITATION PERSISTS.

PAGE 2

- - SECTION 06 - - REACTIVITY DATA - -

STABILITY: STABLE INCOMPATIBILITY: N/A

HAZARDOUS DECOMPOSITION: BURNING WILL PRODUCE TOXIC FUMES

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

--- SECTION 07 - - SPILL OR LEAK PROCEDURE ---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE SOURCES OF IGNITION AND VENTILATE AREA. COVER WITH INERT, ABSORBENT MATERIAL AND REMOVE TO DISPOSAL CONTAINER. WASTE DISPOSAL: OBSERVE ALL RELEVANT FEDERAL, STATE AND LOCAL LAWS. DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS OR UNDERGOUND WATER SUPPLY.

- - SECTION OB - + - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: IF EXPOSURE EXCEEDS TLV, USE APPROPRIATE NIOSH APPROVED PROTECTIVE EQUIPMENT. VENTILATION: LOCAL EXHAUST RECOMMENDED. MECHANICAL VENTILATION RECOMMENDED. PROTECTIVE GLOVES: IMPERMEABLE GLOVES TO MINIMIZE SKIN CONTACT. EYE PROTECTION: CHEMICAL SPLASH GOGGLES OR FACE SHIELD. OTHER PROTECTIVE EQUIPMENT: EYE WASH FOUNTAIN, SAFETY SHOWER. WASH CONTAMINATED CLOTHING BEFORE REUSE.

- - SECTION 09 - - SPECIAL PRECAUTIONS - -

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE. CAUTION--MAY BE HARMFUL IF SWALLOWED. BREATHING VAPOR OR MIST MAY BE HARMFUL. USE WITH ADEQUATE VENTILATION. AVOID EYE AND SKIN CONTACT. KEEP FROM SOURCE OF HEAT AND OPEN FLAME. KEEP OUT OF REACH OF CHILDREN.

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY. REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT THAT IT IS ACCURATE TO THE BEST OF OUR KNOWLEDGE OR OBTAINED FROM SOURCES BELIEVED TO BE ACCURATE AND OUR COMPANY DOES NOT ASSUME ANY LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON THE SAME. CUSTOMERS ARE ENCOURAGED TO CONDUCT THEIR OWN TESTS. BEFORE USING ANY PRODUCT READ ITS LABEL.