MATERIAL SAFETY DATA SHEET

PRODUCT NAME: DESIGN MASTER CRANBERRY 713

HMIS CODES: H F R F

PRODUCT CODE: L-10538

1 4 0

MANUFACTURER'S NAME: HYDROSOL INC.

ADDRESS: 455 FRONTAGE ROAD, BURR RIDGE, IL 60521

EMERGENCY PHONE: 312-598-5448

DATE PREPARED : 08-19-87

INFORMATION PHONE: 312-598-5448

NAME OF PREPARER : ESP

REASON REVISED : UPDATE

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

- ·			OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE	WEIGHT
HAZARDOUS COMPONENTS		CAS NUMBER	OSHA PEL	ACGIH TEV	se Hg 2 TEMP	PERCENT
ETHYL ACETATE		141-78=6	400	400	73.0 68F	⟨ 5.0%
2-PROPANOL, ISOPROPYL ALCOHOL		67-63-0	400	400	33.0 69F	< 5.0%
2-BUTOXYETHANOL, GLYCOL ETHER EB		111-76-2	50	25	0.5 68F	< 5.0%
ISOBUTYL ACETATE	'	110-19-0	200	150	13.0 ABF	5
ACETONE		67-64-1	1000	750	181.0 6EF	. 65
PROPANE		74-98-6	1000	ASPHYXIANT	6350.0 66F	. 15

======== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =========

BOILING POINT: NOT APPLICABLE

VAPOR DENSITY: N/A

SPECIFIC GRAVITY (H20=1):

EVAPORATION RATE: N/A

V.O.C.: N/A

SOLUBILITY IN WATER: SLIGHT TO MODERATE

APPEARANCE AND ODOR: AEROSOL PRODUCT

FLASH POINT: N/A

METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.1% UPPER: 13.0%

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP AND EXPLOSION WHEN EX-POSED TO EXTREME HEAT. IF WATER IS USED, FOS MOZZLES PREFERRED. WEAR SOGGLES AND SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE FROM INTERNAL PRESSURE BUILD-UP WHEN EXPOSED TO EXTREME HEAT AND DISCHARGE CONTENTS. VAPOR ACCUMULATION CAN FLASH OR EXPLODE IF IGNITED. OVEREXPOSURE TO DECOMPOSITION FRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTCMS MAY NOT BE READILY APPARENT. DETAIN MEDICAL ATTENTION.

SECTION V - REACTIVITY DATA

STABILITY: STABLE CONDITIONS TO AVOID

APPLICATION TO HOT SURFACES. STORAGE ABOVE 120 DEG F. EXPOSURE TO OPEN FLAME.

INCOMPATIBILITY (MATERIALS TO AVOID)

STRONG DXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY PRODUCE FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON MONOXIDE AND DXIDES OF NITROGEN.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

RESPIRATORY IRRITATION, DIZZINESS, HEADACHE, NAUSEA, FATIGUE, DROWSINESS, IMPAIRED CO-ORDINATION, EYE WATERING.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN: CONTACT MAY DRY THE SKIN; PROLONGED CONTACT MAY CAUSE IRRITION.

EYES: LIQUID OR VAPOR CAN IRRITATE.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

CAN BE ABSORBED THROUGH SKIN. SOLVENT ACTION CAN DRY AND DEFAT THE SKIN CAUSING SKIN TO CRACK. LEADING TO DEFMATITIS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

NOT A LIKELY ROUTE OF EXPOSURE. IF SWALLOWED, SEEK IMMEDIATE MEDICAL ADVICE AND/OR ATTENTION.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: EYE, SKIN, AND RESPIRATORY SYSTEM IRRITANT. MARCOTIC IN HIGH CONCENTRATIONS. SEVERE OVEREXPOSURE MAY CAUSE DAMAGE TO THE BLOOD.

CHRONIC: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL EXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERV-DUS SYSTEM AND OTHER INTERNAL ORGAN DAMAGE.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

LIVER AND KIDNEY DISEASE, ANEMIA, CORONARY DISEASE. PREGNANT MOMEN SHOULD AVOID EXPOSURE TO SOLVENTS.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. ADMINISTER DXYGEN IF NEEDED. APPLY ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. GET MEDICAL ATTENTION.

SKIN: REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE. WIPE OFF WITH TOWEL. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

EYES: JASH IMMEDIATELY WITH LARGE VOLUMES OF FRESH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

13:17

======== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORBENT MATERIAL AND PLACE IN CLOSED CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. BEFORE ATTEMPTING CLEAN UP, REFER TO OTHER SECTIONS OF THIS MEDS FOR HAZARD CAUTION INFORMATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE AND USE IN COOL, DRY, WELL-VENTILATED AREAS. DO NOT STORE ABOVE 120 DEG F. DO NOT PUNCTURE OR INCINERATE (BURN) CANS. DO NOT STICK PIN, HAIL OR ANY OTHER SHARP OBJECT INTO OPENING ON TOP OF CAN. DO NOT SPRAY IN EYES. DO NOT TAKE IN-TERNALLY. SEE PRODUCT LABEL FOR ADDITIONAL INFORMATION.

OTHER PRECAUTIONS

SMALL PRESSURIZED CONTAINERS OF FLAMMABLE PRODUCTS MAY BE STORED IN AREAS SUITABLE FOR ORDINARY COMBUSTIBLES WITH RE-SPECT TO CONSTRUCTION, DRAINAGE, CONTROL OF IGNITION SOURCES, AND VENTILATION EXCEPT THAT THEY SHOULD NOT BE STORED IN BASEMENTS.

======================================	-2572777257777	SECTION VIII		CONTROL MEASURES	
--	----------------	--------------	--	------------------	--

RESPIRATORY PROTECTION

NONE UNDER NORMAL USE. AVOID BREATHING VAPORS. IN RESTRICTED AREAS, USE APPROVED CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICLES AND VAPOR. IN CONFINED AREAS, USE APPROVED AIR LINE TYPE RESPIRATOR OR HOOD. SELF-CON-TAINED BREATHING APPARATUS IS REQUIRED FOR VAPOR CONCENTRATIONS ABOVE PEL/TLV LIMITS.

VENTILATION

SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS. GENERAL DILUTION AND/OR LOCAL EXHAUST VENTILATION IN VOLUME OR PAT-TERN TO KEEP PEL/TLV OF MOST HAZARDOUS INGREDIENT BELOW ACCEPTABLE LIMIT AND LEL BELOW STATED LIMIT.

PROTECTIVE GLOVES

NONE UNDER NORMAL USE. SOLVENT RESISTANT GLOVES REQUIRED FOR PROLONGED OR REPEATED CONTACT.

EYE PROTECTION

NONE UNDER NORMAL USE; HOWEVER, USE OF SAFETY GLASSES WITH SPLASH GUARDS OR FULL FACE SHIELD IS RECOMMENDED.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NONE UNDER NORMAL USE; HOWEVER, USE OF SOLVENT RESISTANT APRONS OR OTHER CLOTHING IS RECOMMENDED.

WORK/HYGIENIC PRACTICES

EYE WASHES AND SAFETY SHOWERS IN THE WORKPLACE ARE RECOMMENDED.

 SECTION IX	_	DISCLAIMER	

DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED RE-BARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, HYDROSOL, INC. ASSUMES NO RESPONSIBILITY FOR ITS USE.