LIABILITY IS EXPRESSLY DISCLAIMED FOR ANY LOSS OR INJURY ARISING OUT OF THE

	U.S.	DEPAR	TMEN	IT OF	LABOR
Occi	upationa	al Safety	and	Health	Administration

Form Approved OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, and Shipbreaking (29 CFR 1915, 1916, 1917)

66874		SECTI	ON I			
MANUFACTURER'S CHAMCER Key Mainter	ance	Produc	to Inc	EMERGENCY TELE (315)474-87	PHONE NO.	
Rey Ma Miles ADDRESS (Number, Strect, City, Speed and 71P C EY 10	of Cal	Fast.	Syracuse, New	York 13210		
CHEMICAL NAME AND SYNONYMS	J 1 4 4 5		TRADE N	AME AND SYNONYN Plan Shampoo	oncentrai	te
			EORMIN A	PRIETARY		
SYNTHETIC DELI						
SECTION	<u> </u>	HAZAR	DOUS INGREDI	ENTS		TLV
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)		METALLIC COATING	3S %	(Units)
	 	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	BASE METAL			
PIGMENTS	_	<u> </u>	ALLOYS		<u>v'</u>	
CATALYST	-	 	METALLIC COATIN	igs		
VEHICLE Y		ļ	FILLER METAL PLUS COATING OR	70		
SOLVENTS (0"		ļ - -	OTHERS	/		
ADDITIVES /		ļ				
OTHERS.	l	<u> </u>	<u> </u>		·	TLV (Unit
HAZARDOUS MIXTUR	EȘ OF	OTHER LI	QUIDS, SOLIDS, OR	GASES		10
						<u> </u>
NONE						
		 				
S	ECTIO	N III -	PHYSICAL DAT	Ā		
			SPECIFIC GRAVIT		1	.02
BOILING POINT (°F.) T.O.C.	FGG	212° THAN	PERCENT, VOLA	TILE	NON VOI	ΑΨTI
VAPOR PRESSURE (mm Hg.) @ 20° C LESS THAN				VAPORATION RATE		
· · · · · · · · · · · · · · · · · · ·	LATI	T.E	(<u>H₀</u>	=1)		
VAPOR DENSITY (AIR=1) NON VOI					3	
		100%	FREEZE	POINT		32°F
SOLUBILITY IN WATER		100%				32°F
SOLUBILITY IN WATER APPEARANCE AND ODOR BLUE-	-GRE	100% EN COL	OR MI	NT ODOR		32°F
SOLUBILITY IN WATER APPEARANCE AND ODOR BLUE-	-GRE	100% EN COL	OR MI	NT ODOR	Lei	
SOLUBILITY IN WATER APPEARANCE AND ODOR BLUE- SECTION IV	-GRE	100% EN COL	EXPLOSION HA	NT ODOR		32°F
SOLUBILITY IN WATER APPEARANCE AND ODOR BLUE- SECTION IV FLASH POINT (Method used) T.O.C	-GRE	100% EN COL RE AND	EXPLOSION HA	NT ODOR		
SOLUBILITY IN WATER APPEARANCE AND ODOR BLUE- SECTION IV FLASH POINT (Method used) T.O.C	-GRE	100% EN COL RE AND NONE	EXPLOSION HA	NT ODOR		
SOLUBILITY IN WATER APPEARANCE AND ODOR BLUE- SECTION IV FLASH POINT (Method used) T.O.C EXTINGUISHING MEDIA	-GRE	100% EN COL RE AND NONE	EXPLOSION HA	NT ODOR		
SOLUBILITY IN WATER APPEARANCE AND ODOR BLUE- SECTION IV FLASH POINT (Method used) T.O.C EXTINGUISHING MEDIA	- GRE	100% EN COL RE AND NONE PPLICAL	EXPLOSION HA	NT ODOR		· · · · ·

5 V 1 (1) 18 19 (1) 11 (1) 11 (1) 12 (1) 12 (1) 12 (1) 12 (1) 12 (1) 12 (1) 12 (1) 12 (1) 12 (1) 12 (1) 12 (1)		FLAMMABLE LIMITS	
ASH POINT (Method used)	T.O.C. NONE		,
TINGUISHING MEDIA	NOT APPLICAB	T.E.	
ECIAL FIRE FIGHTING PRO	NOT APPLI		
		4	<u> </u>
NUSUAL FIRE AND EXPLOS	NOT APP	LICABLE	
GE (1)	(Continued on	reverse side)	Form OSHA-20 Rev. May 72
		and the second second	

2	S	ECTION	VV - HE	ALTH HAZARD DATA		
THRESHOLD LIMI	TVALUE					
EFFECTS OF OVEREXPOSURE NOT ESTABLISHED						
		NON	E			
EMERGENCY AND	FIRST AID PROCEDS	URES				
CONTAINS S	YNTHETIC DE	TERCE	NT & MI	LLD ALKALINE BUILDERS		
INTERNAL:	DRINK PEEN	EXX P	LENTY C	OF WATER AND SEE PHYSICIAN		
EYES & SKI	N: FLUSH W	ITH W	ATER FO	OR 15 MINUTES .		
						
SECTION VI - REACTIVITY DATA						
STABILITY	UNSTABLE	LE CONDITIONS TO AVOID		NS TO AVOID		
	STABLE	х				
INCOMPATABILITY			<u> </u>			
HAZARDOUS DECO	MPOSITION PRODUC	HE MAN	WFACTU	RER IS UNAWARE OF ANY INCOMPATABILITIES		
			24 CO.	SMOKE CONDITIONS TO AVOID		
HAZARDOUS POLYMERIZATION	MAY OCCUR			CONDITIONS TO AVOID		
	WILL NOT O	CCUR	x			
· · · · · · · · · · · · · · · · · · ·						
· · · · · · · · · · · · · · · · · · ·	0507					
TEPS TO BE TAKE	SECTI	ON VII	- SPILL	OR LEAK PROCEDURES		
TENS TO BE TAKE	N IN CASE MATERIA	L IS RELI	EASED OR S	PILLED		
WIPE UP AND	RINSE_WITH	TAT A TYPE	ъ			
ASTE DISPOSAL M	ETHOD					
MODMAT	DD000000000000000000000000000000000000					
- NORMAL	PROCEDURE					
	SECTION V	'III - SP	PECIAL PI	ROTECTION INFORMATION		
ESPIRATORY PROT	ECTION (Specify type	77		TO LOTTON INTONIATION		
_	LOCAL EXHAUST		IS NE	CESSARY		
Ļ	MECHANICAL //			SPECIAL		
NONE MECHANICAL (General) OTHER						
		EVTRI		EYE PROTECTION		
HE PROTECTIVE	DRYING TO	NECE SVIN		NONE		
	NON	N. INEKLIP	SSARY			
	SEC	TION I	· SPECI	IAL PRECAUTIONS		
ECAUTIONS TO BE	TAKEN IN HANDLIN	IG AND S	TORING			
EAD DITTER						
HER PRECAUTIONS	LABEL BEFOR	E USE	I	KEEP AWAY FROM CHILDREN		
						
OR INDUSTRI	AL & INSTIT	UTION	AL USE	ONLY.		

PAGE (2)

Form OSHA-20 Rev. May 72

LIABILITY IS EXPRESSLY DISCLAIMED FOR ANY LOSS OR INJURY ARISING OUT OF THE USE OF THIS INFORMATION