

7-3627A-M; 61-344A-M;
1-389A-M; 61-345; 61-346;
Material Safety Data Sheet
97-5915 97 3627A,N

Manufactured for:

NASCO

Address

901 Janesville Ave.

Ft. Atkinson, WI 53538

Phone Number (For Information)

414-563-2446

Emergency Phone Number

Telex*

COUNTRY SCHOOL TEMPERA

Identity (Trade Name As Used On Label)

102390

MSDS Number*

397

CAS Number*

OCTOBER 1, 1990

Date Prepared

Prepared By*

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS — Chemical Name & Common Names (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	%	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
AS PER ASTM D-4236 AND AS PER THE ART				
AND CRAFT MATERIALS INSTITUTE, INC. (ACMI),				
THIS PAINT HAS BEEN CERTIFIED NON-TOXIC				
UNDER CURRENT OSHA CRITERIA THIS PRODUCT				
IS CONSIDERED TO BE NON-HAZARDOUS.				
Non-Hazardous Ingredients				
TOTAL	100			

SECTION 2 - PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point	ABOUT 212 F	Specific Gravity (H ₂ O = 1)	ABOUT 9 LBS/GAL
Vapor Pressure (mm Hg and Temperature)	17 mmHG	Melting Point	32 F
Vapor Density (Air = 1)	LIGHTER	Evaporation Rate (WATER = 1)	SLOWER
Solubility in Water	DILUTABLE	Water Reactive	N/A

Appearance and Odor SLIGHT AMMONIA ODOR, OR NO ODOR PRESENT

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

Flash Point and Method Used	N/A	Auto-Ignition Temperature	N/A	Flammability Limits in Air % by Volume	N/A	LEL	UEL
Extinguisher Media	FOAM, DRY CHEMICAL, CO ₂ , WATER SPRAY OR FOG						
Special Fire Fighting Procedures	N/A						

Unusual Fire and Explosion Hazards N/A

*Optional

Proprietary

REACTIVITY HAZARD DATA

STABILITY ☒ Stable ☐ Unstable	Conditions To Avoid NONE KNOWN
Incompatibility (Materials to Avoid) NONE KNOWN-HOWEVER PRODUCT PROPERTIES MAY BE ALTERED BY MIXING WITH SOME MATERIALS.	
Hazardous Decomposition Products THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE AND TRACES OF MONOMER.	
HAZARDOUS POLYMERIZATION ☐ May Occur ☒ Will Not Occur	Conditions To Avoid

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY ☐ Inhalation ☐ Skin Absorption ☒ Ingestion ☒ Not Hazardous	CARCINOGEN LISTED IN ☐ NTP ☐ IARC Monograph ☐ OSHA ☐ Not Listed
HEALTH HAZARDS Acute Chronic	
Signs and Symptoms of Exposure Medical Conditions Generally Aggravated by Exposure	
EMERGENCY FIRST AID PROCEDURES - Seek medical assistance for further treatment, observation and support if necessary.	
Eye Contact DIRECT CONTACT WITH EMULSION MAY RESULT IN IRRITATION. FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN. REMOVE CONTACTS FROM VICTIM.	
Skin Contact PROLONGED OR REPEATED CONTACT WITH EMULSION MAY CAUSE SOME SKIN IRRITATION. WASH SKIN THOROUGHLY WITH SOAP AND WATER; IF DRENCHED, REMOVE AND WASH CLOTHING BEFORE REUSE.	
Inhalation N/A	
Ingestion IF VICTIM IS CONSCIOUS, GIVE TWO GLASSES OF WATER TO DRINK AND CALL A PHYSICIAN.	

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (Specify Type) Protective Gloves RUBBER GLOVES RECOMMENDED	Eye Protection CHEMICAL GOGGLES WITH EYE GUARD.
VENTILATION TO BE USED ☐ Local Exhaust ☐ Other (specify)	☐ Mechanical (general) ☐ Special
Other Protective Clothing and Equipment N/A	
Hygienic Work Practices	

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES

Steps to be Taken if Material is Spilled Or Released ABSORB WITH DRYING MATERIAL OR FLUSH SPILLED MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINER. PREVENT SPILLED LIQUID FROM ENTERING SEWERS, STORM DRAINS, DRAINAGE SYSTEMS AND NATURAL WATERWAYS.
Waste Disposal Methods DISPOSE OF PRODUCT IN ACCORDANCE WITH APPLICABLE LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.
Precautions to be Taken Handling and Storage SHOULD BE STORED AT ROOM TEMPERATURE TO PROLONG SHELF LIFE. KEEP FROM FREEZING AND AWAY FROM EXCESSIVE HEAT.
Other Precautions and/or Special Hazards

PA ing* Health onal	Flammability Reactivity Special	HMIS Rating* Health Flammability Reactivity Personal Protection
---------------------------	---------------------------------------	---

© Copyright 1986, Science Related Materials, Inc. All Rights Reserved.

Material Safety Data Sheet

BULK-KRYLIC

Manufactured for:

NASCO

901 Janesville Ave.

Ft. Atkinson, WI 53538

Phone Number (For Information)

414-563-2446

Emergency Phone Number

Telex

Identity (Trade Name As Used On Label)

102390

MSDS Number

CAS Number

OCTOBER 1, 1990

Date Prepared

Prepared By

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS — Chemical Name & Common Names (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	%	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
AS PER ASTM D-4236 AND AS PER THE ART				
AND CRAFT MATERIALS INSTITUTE, INC. (ACMI),				
THIS PAINT HAS BEEN CERTIFIED NON-TOXIC				
UNDER CURRENT OSHA CRITERIA THIS PRODUCT				
IS CONSIDERED TO BE NON-HAZARDOUS.				
Non-Hazardous Ingredients				
TOTAL	100			

SECTION 2 - PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point	ABOUT 212 F	Specific Gravity (H ₂ O = 1)	ABOUT 9 LBS/GAL
Vapor Pressure (mm Hg and Temperature)	17 mmHg	Melting Point	32 F
Vapor Density (Air = 1)	LIGHTER	Evaporation Rate (WATER = 1)	SLOWER
Solubility in Water	DILUTABLE	Water Reactive	N/A

Appearance and Odor SLIGHT AMMONIA ODOR, OR NO ODOR PRESENT

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

Flash Point and Method Used	N/A	Auto-Ignition Temperature	N/A	Flammability Limits in Air % by Volume	N/A	LEL	UEL
Extinguisher Media	FOAM, DRY CHEMICAL, CO ₂ , WATER SPRAY OR FOG						
Special Fire Fighting Procedures	N/A						

Unusual Fire and Explosion Hazards N/A

*Optional

Proprietary 073960

N-4. REACTIVITY HAZARD DATA

STABILITY ☒ Stable ☐ Unstable	Conditions To Avoid NONE KNOWN	(2)
Incompatibility NONE KNOWN-HOWEVER PRODUCT PROPERTIES MAY BE ALTERED BY MIXING WITH SOME MATERIALS.		
Hazardous Decomposition Products THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE AND TRACES OF MONOMER.		
HAZARDOUS POLYMERIZATION ☐ May Occur ☒ Will Not Occur	Conditions To Avoid	

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY ☐ Inhalation ☐ Skin Absorption	☐ Ingestion ☒ Not Hazardous	CARCINOGEN LISTED IN ☐ IITP ☐ IARC Monograph	☐ OSHA ☐ Not Listed
HEALTH HAZARDS Acute Chronic			

Signs and Symptoms of Exposure

Medical Conditions

Generally Aggravated by Exposure

EMERGENCY FIRST AID PROCEDURES - Seek medical assistance for further treatment, observation and support if necessary.

Eye Contact DIRECT CONTACT WITH EMULSION MAY RESULT IN IRRITATION. FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT PHYSICIAN. REMOVE CONTACTS FROM VICTIM.

Skin Contact PROLONGED OR REPEATED CONTACT WITH EMULSION MAY CAUSE SOME SKIN IRRITATION. WASH SKIN THOROUGHLY WITH SOAP AND WATER. IF DRENCHED, REMOVE AND WASH CLOTHING BEFORE REUSE.

Inhalation N/A

Ingestion IF VICTIM IS CONSCIOUS, GIVE TWO GLASSES OF WATER TO DRINK AND CALL A PHYSICIAN.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection
(Specify Type)

Protective Gloves RUBBER GLOVES RECOMMENDED **Eye Protection** CHEMICAL GOGGLES WITH EYE GUARD.

VENTILATION TO BE USED
☐ Local Exhaust
☐ Mechanical (general)
☐ Special
☐ Other (specify)

Other Protective Clothing and Equipment N/A
Hygienic Work Practices

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES

Steps to be Taken if Material is Spilled or Released ADSORB WITH DRYING MATERIAL OR FLUSH SPILLED MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINER. PREVENT SPILLED LIQUID FROM ENTERING SEWERS, STORM DRAINS, DRAINAGE SYSTEMS AND NATURAL WATERWAYS.

Waste Disposal Methods DISPOSE OF PRODUCT IN ACCORDANCE WITH APPLICABLE LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.

Precautions to be Taken in Handling and Storage SHOULD BE STORED AT ROOM TEMPERATURE TO PROLONG SHELF LIFE. KEEP FROM FREEZING AND AWAY FROM EXCESSIVE HEAT.

Other Precautions and/or Special Hazards