Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard,

U.S. Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form)



29 CFR 1910.1200. Standard must be Form Approved consulted for specific requirements. OMB No. 1218-0072 IDENTITY (As, Used on Label and List) Note Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that. S-58 HAMMER Grease - 36 Section I Emergency Telephone Number 201-344-3451 Manufacturer's Name NONFLUID OIL CORP. Address (Number, Street, City, State, and ZIP Code) Telephone Number for Information 201-344-3451 298 DELANCY STREET, NEWARK, N.J. 07105 Date Prepared June 1986 Signature of Preparer (optional) Section II — Hazardous Ingredients/Identity Information Other Limits Hazardous Components (Specific Chemical Identity: Common Name(s)) OSHA PEL **ACGIH TLV** Recommended % (optional) THIS PRODUCT IS NOT CONSIDERED A HAZARDOUS MATERIAL IN NORMAL USE AS DEFINED IN U.S. DEPARTMENT OF LABOR REGULATIONS 29CFR 1910:1200 Section III - Physical/Chemical Characteristics

Boiling Point (CF) IBP-FBP	600/900	Specific Gravity (H ₂ O = 1)		0.91
Vapor Pressure (mm Hg.) @ 25 ^C C	< 0.01	Melting Point	· .	Negligible
Vapor Density (AIR = 1)	> 10	Evaporation Rate (Butyl Acetate = 1)		<0.01
Solubility in Water Dispersible	**			

Appearance and Odor

Light tan opaque grease

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) Flammable Limits UEL 375^C F 6% of base oils

Extinguishing Media

CO2, DRY CHEMICAL, FOAM & WATER FOG (CAREFULLY TO PREVENT FROTHING)

Special Fire Fighting Procedures

USE SELF CONTAINED BREATHING APPARATUS WITH FACE SHIELD IN ENCLOSED AREAS.

Unusual Fire and Explosion Hazards NONE

Section V -	Reactivity Dat	a		
Stability	Unstable		Conditions to Avoid	LEAT AND ODEN BLANCE
	Stable	 	EVCESSIAL	HEAT AND OPEN FLAMES
Incompatibility	(Materials to Avoid)	X		
-		AVU.	ID CONTACT WITH STRONG	OXIDIZING AGENTS
Hazardous Deco	mposition or Byprod	ucts OX:	DES OF CARBON MAY FORM	ON INCOMPLETE COMBUSTION
Hazardous Polymerization	May Occur		Conditions to Avoid N/A	
, ,	Will Not Occur	T_{x}	White the transfer and an article and the transfer and th	
Section VI -	- Health Hazard	Data		
Route(s) of Entry		alation?	Skin?	Ingestion?
Health Hazards /	Acute and Chronic)	N/A	AVOID DERMA	L CONTACT SEEK MEDICAL HELP
AS WIT	H ALL PETROI	EUM 1	PRODUCTS, PROLONGED OR	REPEATEDLY FREQUENT SKIN CONTACT MAY
CAUSE	MILD IRRITAT	CION.	DEFATTING ON SKIN IS	POSSIBLE. EXPOSURE TO FUMES OR MISTS
MAY CA	USE MUCOUS N	ŒMBR/	NE IRRITATION.	
Carcinogenicity:	NT/		IARC Mo N /A	nographs? OSHA Regulated?
and the second s	· · · · · · · · · · · · · · · · · · ·	********************	:	***
Signs and Sympt	oms of Exposure	w w	LD IRRITATION OF SKIN	AND MICCOUS MEMBRANE
	militaria de la composição	¥1.	TID TIGHTIATION OF BRIN	AND HOUSE HEIDRAND
Medical Condition	1\$			
Generally Aggrav	ated by Exposure	L/A		
		·	-	
	First Aid Procedures ONTACT: WIF	E OF	AND WASH WITH SOAP &	WATER. EYE CONTACT: FLUSH WITH COPIUS
AMOUNT INGEST	S OF WATER A	ND SI	E A DOCTOR. INHALATION TER AND SERK MEDICAL A	: REMOVE FROM EXPOSURE TO FRESH AIR.
			Handling and Use	
•	n in Case Material I		•	TO THEE BROWLET AND ADCORDANG MARCHTAL
	S CLAY TO SI			R FREE PRODUCT. ADD ABSORBANT MATERIAL
SUUM A	D CLAI TO SI	TLU C	MCA. SWEET ON SCRAFE	UE •
Waste Disposal N	lethod			
		L LA	IS PERMIT FOR PETROLEUM	HYDROCARBONS
	50 -12-14-14-14-14-14-14-14-14-14-14-14-14-14-			
Precautions to Be KEEP C	Taken in Handling ONTAINERS CI	and Sto	ing HANDLE AND STORE USIN	G METHODS GENERALLY ADVOCATED FOR
PETROL	EUM PRODUCTS			OXIDIZING MATERIALS. AVOID EXCESSIVE
Other Precautions			**************************************	timatina aliantia an amona don an amona de mana de men
				CT WITH EYES AND INHALATION OF FIMES,
		extractivity and an extractivity of the contractivity of the contractivi	INGEST. WASH THOROUGHL	Y AFTER HANDLING,
Sanda, sala, in 1885 al maria da sana d	- Control Meas	ures		
	ction (Specify Type) LY NOT REOUT	RED.	RECOMMENDED IF FIMING	OR MISTING
Ventilation	Local Exhaust		PTURE HOT FUMES	Special N/A
·	Mechanical (General	7 5 511	MING OR MISTING	Other N/A
Protective Gloves	CECOTITE ADED	IF PU	Eye Pi	ofection
			EPEATED CONTACT REC	OMMENDED IF SPLASHING OR MISTING
Other Protective Clothing or Equipment NORMALLY NOT REQUIRED, PROTECTIVE GARMENT RECOMMENDED WHEN APPLICABLE (AS WHEN SPLASHING)				
Work/Hygienic Pra WASH HANDS	ctices BEFORE EATI	NG OR	DRINKGING. DO NOT WEA	R CONTAMINATED CLOTHING. REMOVE THAN AND
	FORE RE-USE.		Page 2	# USGPO 1886-491-529/45775