North American Adhesives & Coatings Company 530 Industrial Drive West Chicago, IL 601859

MSDS NO. 402 PRODUCT NO. 0050350100

CONTACT FOR FURTHER INFORMATION MSDS COORDINATOR (708-231-7175) Emergency Poisoning Information (708-801-4200)

PRODUCT IDENTIFICATION:

PRODUCT NAME: DS-50 ACRYLIC CERAMIC FLOOR AND WALL TILE ADHESIVE

PRODUCT CLASS: CERAMIC TILE ADHESIVE

CHEMICAL FAMILY: AQUEOUS, SYNTHETIC LATEX/RESINS

DOT HAZARD CLASSIFICATION: NON HAZARDOUS

SECTION I	HAZARDOUS	INGREDIENT	S: EXPOSURE	LIMITS		
CHEMICAL		PERCENT	CAS NO	TLV UNITS	AGENCY	TYPE
VMP NAPTH		3.0%	8032-32-4	300 ppm OR	ACGIH	TWA
		ografikati Nasola sa		1350 mg/	m3	
METHANOL		1-2%	67-56-1	200 ppm	ACGIH	TWA

NO COMPONENT OF THIS PRODUCT HAS BEEN IDENTIFIED AS A CARCINOGEN OR PROBABLE CARCINOGEN BY NTP, IARC OR OSHA.

PHYSICAL DATA SECTION II

BOILING POINT: 209 F FREEZING POINT: APPROXIMATELY 32 F SPECIFIC GRAVITY: 1.38 VAPOR PRESSURE: SAME AS WATER VAPOR DENSITY: SAME AS WATER EVAPORATION RATE: SAME AS WATER PERCENT VOLATILES: 33-35% SOLUBILITY IN WATER: INFINITELY-DILUTETABLE

APPEARANCE AND ODOR: WHITE HEAVY PASTE, ACRYLIC ODOR

HAZARD RATING (HMIS) HAZARD RATING SCALE

HEALTH 0=MINIMAL = ī FLAMMABILITY 1≃SLIGHT REACTIVITY 2=MODERATE 3=SERIOUS

4=SEVERE

Page 2 of 5

Product Name: DS-50 ACRYLIC CERAMIC FLOOR AND WALL

TILE ADHESIVE

Product Code No: 0050350100

SECTION III- EMERGENCY AND FIRST AID PROCEDURES ****EMERGENCY****

EYE CONTACT: FLUSH EYES WITH COPIOUS AMOUNTS OF CLEAN WATER. SEEK PROMPT MEDICAL ATTENTION.

SKIN CONTACT: WASH AFFECTED AREAS THOROUGHLY WITH MILD SOAP AND WATER. IF IRRITATION OR REDNESS DEVELOPS AND PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION (BREATHING): REMOVE PATIENT TO FRESH AIR.

这个人想到在1967年

Balling to the Balling of the Control of the Contro

INGESTION (SWALLOWING): GIVE 3 TO 4 GLASSES OF WATER. INDUCE VOMITING, (if victim is conscious) UNDER DIRECTIONS FROM A PHYSICIAN OR POISION CONTROL CENTER. VOMITTING CAN BE INDUCED BY HAVING THE VICTIM DRINK 3 TABLESPOONS OF LIQUID DISHWASHING SOAP MIXED IN A GLASS OF WATER. SEEK MEDICAL ATTENTION. DO NOT LEAVE VICTIM UNATTENDED.

COMMENTS: NONE

SECTION IV - HEALTH HAZARDS/ROUTES OF ENTRY

grade a contract contract of

EYE CONTACT: THIS PRODUCT MAY CAUSE EYE IRRITATION. DIRECT CONTACT CAN CAUSE BURNING, TEARING AND REDNESS.

SKIN CONTACT: MAY CAUSE SLIGHT SKIN IRRITATION, PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO EFFECTS OF THIS MATERIAL. REPEATED, LONG-TERM EXPOSURE MAY RESULT IN DERMATITIS.

INHALATION (BREATHING): EXCESSIVE VAPOR CONCENTRATIONS IN CONFINED WORK AREAS WITH POOR VENTILATION, MAY CAUSE IRRITATION TO NOSE AND THROAT.

Product Name: DS-50 ACRYLIC CERAMIC FLOOR AND WALL Page 3 of 5

TILE ADHESIVE Product Code No: 0050350100

SECTION IV - HEALTH HAZARDS/ROUTES OF ENTRY

INGESTION (SWALLOWING): THIS PRODUCT CAN CAUSE SEVERE ABDOMINAL PAIN, DISTRESS AND NAUSEA.

COMMENTS: PRODUCT IS NOT CONSIDERED TOXIC. NO CHRONIC HEALTH EFFECTS ARE KNOWN AT THIS TIME RELATIVE TO REPEATED OVEREXPOSURE.

SECTION V - SPECIAL PROTECTION INFORMATION

VENTILATION: GENERAL VENTILATION, AND/OR LOCAL EXHAUST.

RESPIRATORY PROTECTION: NONE REQUIRED

PROTECTIVE GLOVES: IMPERVIOUS GLOVES (RUBBER OR BETTER)

EYE PROTECTION: SAFETY GLASSES

OTHER PROTECTIVE EQUIPMENT: N/A

SECTION VI- REACTIVITY DATA

STABILITY: PRODUCT IS STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): NONE

的 医性脑膜膜炎 原始 化二次

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE, TRACES OF NITROGEN

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

Product Name: DS-50 ACRYLIC CERAMIC FLOOR AND WALL TILE ADHESIVE

Page 4 of 5

Product Code No: 0050350100

SECTION VII- SPILL OR LEAK PROCEDURES

PRECAUTIONS IN CASE OF RELEASE OR SPILL: COVER WITH ABSORBENT MATERIAL, TRANSFER TO CLOSED CONTAINER.

WASTE DISPOSAL METHOD: DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.

SECTION VIII- STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS:

KEEP FROM FREEZING - CLOSE CONTAINER AFTER USE.

SECTION IX - FIRE AND EXPLOSION HAZARD DATA

HAZARD RANKING

NFPA HEALTH HAZARD: 1
HAZARD FLAMMABILITY: 0
CLASS REACTIVITY: 0

OTHER:

0 = LEAST

1 = SLIGHT

2 = MODERATE 3 = HIGH

4 = EXTREME

Soft Comment Soft and we

LOWER EXPLOSIVE LIMIT (% VOL.)

UPPER EXPLOSIVE LIMIT (% VOL.)

N/A

N/A

FLASH POINT

OVER 200 F AQUEOUS SYSTEM WILL NOT PROPAGATE FLAME

EXTINGUISHING MEDIA:

PRODUCT WILL NOT BURN UNTIL ALL WATER CONTENT HAS EVAPORATED, USE CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER SPRAY AND HALON 1211.

FIRE & EXPLOSION HAZARDS:

DECOMPOSITION BY PRODUCTS MAY BE TOXIC.

Product Name: DS-50 ACRYLIC CERAMIC FLOOR AND WALL Page 5 of 5

TILE ADHESIVE

Product Code No: __0050350100

SECTION IX - FIRE AND EXPLOSION HAZARD DATA

Richard Bur agreement on the second

FIRE FIGHTING PROCEDURES:

AS A PRECAUTION FIRE FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING EOUIPMENT.

SECTION X - DOCUMENTARY INFORMATION

ISSUE DATE: 6-03-87
REVISION DATE: 03-27-90
MSDS NO: 400

MSDS NO: 402

0050350100

PRODUCT CODE NO. PREV. PROD. CODE NO.

PREV. NO:

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.