

TERIAL SAFETY DATA SHEET

396
PAINT DISTRIBUTING CORPORATION

ACTURER
UNNYSIDE DR. P.O. BOX 482

SS
ON, WI 53563

888-6873 (414) 563 8545

NUMBER (FOR INFORMATION)

BULK-KRYLIC

31-445 - 31-464, 91-127-91-156,

TRADE NAME ON LABEL

97-14736A-D 31-501-31-508,

97-14737A-D 31-514-31-520

MSDS NUMBER

97-14718A-Y 91-268, 91-269, 97-149,

97-3018-97-3022,

CAS NUMBER

97-3037, 97-3922-97-3927

MARCH 10, 1994

DATE PREPARED

97-14719A-Y

97-14720A-Y

PREPARED BY

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS	CHEMICAL NAME & COMMON NAMES	%	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
WATER					
VA EMULSION					
PIGMENT: ASSORTED NON-TOXIC COLORS					
ALC					
PROPYLENE GLYCOL					

PER ASTM D-4236 AND AS PER THE ART AND CRAFT MATERIALS INSTITUTE (ACMI), INC. THIS PAINT HAS BEEN CERTIFIED NON-TOXIC.

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

FREEZING POINT ABOUT 212 F	SPECIFIC GRAVITY (H2O = 1) ABOUT 8 LBS/GAL
VAPOR PRESSURE (mm Hg & TEMPERATURE) 17 mmHG	MELTING POINT 32 F
VAPOR DENSITY (AIR=1) LIGHTER	EVAPORATION RATE (WATER=1) SLOWER
SOLUBILITY IN WATER DILUTABLE	WATER REACTIVE N/A

APPEARANCE & ODOR SLIGHT AMMONIA ODOR, OR NO ODOR PRESENT

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

TEST POINT & METHOD USED N/A	AUTO - IGNITION TEMPERATURE N/A	FLAMMABILITY LIMITS IN AIR % BY VOLUME N/A	LEL	UEL
---------------------------------	------------------------------------	---	-----	-----

EXTINGUISHING MEDIA FOAM, DRY CHEMICAL, CO2, WATER SPRAY OR FOG

ADDITIONAL FIRE FIGHTING PROCEDURES

N/A

ADDITIONAL FIRE AND EXPLOSION HAZARDS

N/A

v#073960 10/19/94