

Rev'd Nov 2001

467816/193-015

PAGE 1 OF 4

SECTION I

MANUFACTURER'S NAME	Parks Corporation	CHEMICAL NAME & SYNONYMS	Petroleum Solvent
STREET ADDRESS	One West Street	CHEMICAL FAMILY	Hydrocarbon Mixture
CITY, STATE & ZIP	Fall River, MA 02720	TRADE NAME	PARKS MINERAL SPIRITS
EMERGENCY TELEPHONE	(508) 679-5938	SIZES/CODES	5 Gallon #2032
			Gallon #2033
			Quart #2035

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES & SOLVENTS

<u>SOLVENTS</u>	<u>CAS #</u>	<u>%</u>	<u>AGENCY</u>	<u>UNITS TLV</u>	<u>TYPE</u>
Stoddard Solvent	8052-41-3	100	ACGIH	100	TWA
			ACGIH	200	STEL
			OSHA	100	TWA

This component may contain 3.5% of

*1,2,4 Tri Methyl Benzene	95-63-6
---------------------------	---------

*SECTION 313 OF SARA TITLE III.

SECTION III - PHYSICAL DATA

BOILING POINT (°F)	310 - 405°F	SPECIFIC GRAVITY (H₂O = 1)	0.789
VAPOR PRESSURE (mmHg)	2 mmHg	PERCENT VOLATILE BY VOLUME (%)	100
VAPOR DENSITY (AIR = 1)	4.9	EVAPORATION RATE (ETHER = 1)	Less than 1
SOLUBILITY IN WATER	Negligible (<5%)	V.O.C.	773 g/l
APPEARANCE	Water white clear		
ODOR	Hydrocarbon type		

FLASH POINT (METHOD USED): 105°F, TCC.

FLAMMABLE LIMITS (% VOL)

LEL: 1.0

UEL: 6.0

EXTINGUISHING MEDIA: Extinguish with dry chemical, CO₂ or a universal type foam.

SPECIAL FIRE FIGHTING PROCEDURES AND FIRE AND EXPLOSION HAZARDS: Self-contained breathing apparatus recommended for fire fighters. Water spray may be useful in minimizing vapors and cooling containers exposed to heat and flame. Avoid spreading burning with water used for cooling purposes. This material is combustible and may be ignited by heat or flame. Never use welding or cutting torch on or near containers (even empty) because product (even just residue) can ignite explosively. All 5 gallon pails and drums should be grounded and/or bonded when material is transferred. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point.

SECTION IV – FIRE AND EXPLOSION HAZARD DATA (CONT'D)**UNUSUAL FIRE AND EXPLOSION HAZARDS DATA****HAZARD RANKING****0 Least; 1 Slight; 2 Moderate; 3 High; 4 Extreme****NFPA HAZARD CLASS**

Health Hazard	0
Flammability	2
Reactivity	0

HMIS HAZARD CLASS

Health Hazard	1
Flammability	2
Reactivity	0

SECTION V – HEALTH HAZARD DATA**THRESHOLD LIMIT VALUE:** See Section II.**EFFECTS OF OVEREXPOSURE****EYE CONTACT:** Exposure may cause mild eye irritation. Symptoms may include stinging, tearing and redness.**SKIN CONTACT:** Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying and cracking and skin burns. Preexisting skin disorders may be aggravated by exposure to this material. Skin absorption is possible but harmful effects are not expected from this route of exposure under normal conditions of handling and use.**INHALATION (BREATHING):** Exposure to vapor or mist is possible. Short term inhalation toxicity is low. Breathing small amounts during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are more typically seen at air concentrations exceeding the recommended exposure limits. Symptoms of exposure may include irritation (nose, throat, respiratory tract), pre-existing lung disorders (e.g. asthma-like conditions may be aggravated by exposure to this material) and central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).**INGESTION (SWALLOWING):** Single dose oral toxicity is low. Swallowing small amounts during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. Symptoms may include gastrointestinal irritation (nausea, vomiting, diarrhea) and central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness). This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.**EMERGENCY AND FIRST AID PROCEDURES****EYE CONTACT:** Flush with water for 15 minutes. Seek medical help.**SKIN CONTACT:** Wash with mild soap and water solution and seek medical attention.**INHALATION:** Remove to fresh air. Apply artificial respiration if breathing stops. Seek medical attention immediately.**INGESTION:** If swallowed, do not induce vomiting. Seek medical attention immediately.**PRIMARY ROUTE(S) OF ENTRY:** Inhalation, skin contact and eye contact.**EFFECTS OF CHRONIC EXPOSURE:** Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by IARC, NTP or OSHA.**SECTION VI – REACTIVITY DATA****STABILITY:** Stable.**CONDITION TO AVOID:** Heat, sparks, fire, open flame and all other sources of ignition.**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents. Strong acids or bases and selected amines.**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may yield carbon monoxide and/or CO₂.**HAZARDOUS POLYMERIZATION:** Will not occur.**CONDITIONS TO AVOID:** N.A.

SECTION VII – SPILL OR LEAK PROCEDURES**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

SMALL SPILL: Absorb liquid on vermiculite, floor absorbent or other absorbent material.

LARGE SPILL: Eliminate all ignition sources (flares, flames, including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until cleanup has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product, transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent runoff to sewers, streams or other bodies of water. If runoff occurs, notify proper authorities, as required, that a spill has occurred.

WASTE DISPOSAL METHOD

SMALL SPILL: Dispose of in accordance with all local, state and federal regulations.

LARGE SPILL: Dispose of in accordance with all applicable local, state and federal regulations.

SECTION VIII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFIC TYPE): Self-contained breathing apparatus for concentrations above TLV limits.

VENTILATION

LOCAL EXHAUST: Adequate ventilation required.

MECHANICAL (GENERAL): Yes

SPECIAL: No smoking.

OTHER: N.A.

PROTECTIVE GLOVES: Impermeable gloves.

EYE PROTECTION: Safety goggles.

OTHER PROTECTIVE EQUIPMENT: It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

SECTION IX – STORAGE AND SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep away from heat, sparks and open flame. Use with adequate ventilation. Keep container closed.

OTHER PRECAUTIONS: Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected areas with water.

OTHER REGULATORY INFORMATION: The State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65) develops a list of chemicals that require specific warnings relating to cancer and/or reproductive toxicity. This product contains the following chemicals subject to the reporting requirements of the State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65).

<u>CHEMICAL</u>	<u>CAS #</u>	<u>QUANTITY</u>
Toluene**	108-88-3	500 PPM
Benzene**	71-43-2	<10 PPM

The warning on the product states:

WARNING: USE OF THIS PRODUCT WILL EXPOSE YOU TO BENZENE WHICH IS KNOWN TO CAUSE CANCER AND TO TOLUENE WHICH IS KNOWN TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

****Not included in Section II as this chemical is less than .1% of the formula.**

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

THE INFORMATION IN THIS DOCUMENT IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT OR THE HAZARDS RELATED TO ITS USE. THIS INFORMATION AND PRODUCT ARE FURNISHED ON THE CONDITION THAT THE PERSON RECEIVING THEM SHALL MAKE HIS OWN DETERMINATION AS TO THE SUITABILITY OF THE PRODUCT FOR HIS PARTICULAR PURPOSE AND ON THE CONDITION THAT HE ASSUME THE RISK OF HIS USE THEREOF.