123460 1011127 A 1986 PEDELL'ELL 28

## U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

Form Approved OMB No. 44-R1387

## MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917) 20750-00

£15026181		SECT	ION I				
MANUFACTURER'S NAME	3,0110141			EMERGENCY TELEPHONE NO.			
PENTEL COMPANY, LTD., Head Office USA: (21)					13) 320-3831		
ADDRESS (Number, Street, Cit); State, and ZIP Co 7-2 Koami-cho, Nihonbashi, C CHEMICAL NAME AND SYNONYMS	ode) huo-	ku, Tok	TRADE NAME AND	SYNONYMS		<u></u>	
CHEMICAL FAMILY			PTS-7, PTS-	15			
Mixture			<u> </u>	· <del>·····</del>			
SECTION	111 -	HAZAF	DOUS INGREDIENTS	<u> </u>			
PAINTS, PRESERVATIVES, & SOLVENTS	*	TLV (Units)				TLV (Units)	
PIGMENTS			BASE METAL			·	
CATALYST			ALLOYS				
VEHICLE	ľ		METALLIC COATINGS	METALLIC COATINGS			
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX				
ADDITIVES			OTHERS	<u> </u>		·	
OTHERS						TLV	
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES							
This product has been evaluate	din	accord	lance with ASTM D-423	6			
PTS Pastel Dye Sticks are cert	ifie	d to co	ntain no materials i	n sufficier	nt		
quantities to be toxic or inju	riou	s to h	mans or to cause acu	te or			
chronic health problems.							
SE	CTIO	N III - I	PHYSICAL DATA		· <u>·</u>		
BOILING POINT (°F.)	SPECIFIC GRA		SPECIFIC GRAVITY (H20=1)	VITY (H <sub>2</sub> 0=1)			
VAPOR PRESSURE (mm Hg.)	PERCENT, VOLATILE BY VOLUME (%)						
VAPOR DENSITY (AIR=1)			EVAPORATION RATE				
SOLUBILITY IN WATER					<u> </u>		
APPEARANCE AND ODOR							
SECTION IV	FIR	E AND	XPLOSION HAZARD D	ATA			
Q_Q.,Q.						Uel	
FLASH POINT (Method used)			FLAMMABLE LIMITS	Le!		<u> </u>	
FLASH POINT (Method used)  EXTINGUISHING MEDIA			FLAMMABLE LIMITS	Lei			
· · · · · · · · · · · · · · · · · · ·			FLAMMABLE LIMITS	Le!			
EXTINGUISHING MEDIA			FLAMMABLE LIMITS	Lel			
EXTINGUISHING MEDIA			FLAMMABLE LIMITS	Le!			

		SECTION V	/ · HEA	LTH HAZARD	DATA		
THRESHOLD LIMIT	T VALUE						
EFFECTS OF OVER	EXPOSURE						
EMERGENCY AND	FIRST AID PROCES	DURES			-		
<del></del>		<del> </del>					
		<del></del>					
· ·			·				
•		SECTION	VI - R	EACTIVITY DA	ATA		
STABILITY	UNSTABLE	CONDITIONS TO AVOID					
	STABLE		· · · · · ·				
INCOMPATABILITY		<del>, 1</del>	1.				
HAZARDOUS DEC			-				
	<del></del>			CONDITIONS TO	AVOID		
HAZARDOUS		MAY OCCUR					
	WILL NOT	L NOT DECUR					
		<del></del>	·				
	SEC	TION VII	. SPILI	OR LEAK PRO	CEDURES		
STEPS TO BE TAKE							
3,2,3,0,00				<u></u>			
<u> </u>	<u>.                                    </u>		<u>.</u>	·			
	METHOD.	<u></u>			· · · · · · · · · · · · · · · · · · ·		
WASTE DISPOSAL	ME I HOD						
					· · · · · · · · · · · · · · · · · · ·		
	SECTION	17/111 65	ECIAL P	ROTECTION I	NFORMATION		
0500:00700V DD			COIAL				
RESPIRATORY PROTECTION (Specify type)				SPECIAL			
VENTILATION				·	OTHER		
	MECHANICAL (General)			T EVE SPOTECTIC	PROTECTION		
PROTECTIVE GLO				EVE PAOTECTIC			
OTHER PROTECTIV	VE EQUIPMENT			<u></u>			
			V 005	CIAL DECAM	TIONS		
BOTCOLITICAL				CIAL PRECAU	TIONS		
PRECAUTIONS TO	BE TAKEN IN HAN	IDLING AND	SICKING				
OT JED 6	<u> </u>	·					
OTHER PRECAUTI	ONS			·			
	•			·			

PAGE (2)

PREPARED BY: Quality Assurance Department

DATE: April 15, 1986

Form OSHA-20 Res. May 72