9719134 9722022 1150165 9722021 9722022X 1150170 9722021X 1150172 9719130 9719132 9715477A,C,D,E,F,H

525.

MATERIAL SAFETY DATA ŞHEET 150185 1150190 1150195 720316-19

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product Name: Original Sculpey®, Sculpey III®, Super Sculpey®, Super Sculpey® Firm,

Sculpey® MOLDMAKER™ & POLYMER CLAY CONDITIONER, Granitex™, Premo! Sculpey®, Sculpey SuperFlex BAKE & BEND®, Amazing! Eraser Clay!®,

Sculpey® UltraLight™, Sculpey® Keepsake Clay

**Product Use:** 

Oven hardening modeling material for hobby use

Manufacturer:

Polyform Products Company

1901 Estes Avenue Elk Grove Village, IL 60007 USA

Phone: 1-847-427-0020

**Emergency Telephone Number:** 

1-847-427-0020

available only during office hours

Date of Preparation: 01-21-2008

### 2. HAZARD IDENTIFICATION

# **Emergency Overview**

Do not inhale furnes during baking. Overheating oven hardening polymer clays will result in blackening and release of irritating gases including hydrogen chloride vapor.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Components** 

CAS number

Weight %

Oven hardening modeling material composed of polyvinyl chloride, plasticizer, fillers and colorants. This material contains no dangerous substances to be declared.

# FIRST AID MEASURES

Eye Contact:

Rinse eye thoroughly with plenty of water. If symptoms persist, seek medical attention.

Skin Contact:

Wash with soap and water.

ingestion:

Wash out mouth with water. If symptoms persist, seek medical attention.

Inhalation:

Seek fresh air after inhalation of fumes in the case of overheating material in oven.

#### 5. FIRE-FIGHTING MEASURES

Flash Point:

**Autoignition Temperature:** 

**Explosion Limits in Air:** 

**Extinguishing Agents:** 

**Hazardous Decomposition Products:** 

n/a

n/a Not explosive

Use water spray jet, foam, carbon dioxide, dry chemical. In the case of overheating in oven, carbon monoxide,

carbon dioxide and noxious hydrochloric acid vapors. Wear self-contained breathing apparatus with full face

piece and protective clothing.

Special Protective Equipment for Fire Fighters:

APR 16 2009

HEALTH AND SAFETY

Page 1 of 3 Facilities Management

original Sculpsy®, Sculpsy III®, Super Sculpsy®, Super Sculpsy® Firm, Sculpsy® MOLDMAKER™ & POLYMER CLAY CONDITIONER, Granitex™, Prame! Sculpsy®, Sculpsy®, Sculpsy SuperFlex BAKE & BEND®, Amazing! Eraser Clayl® Sculpsy® UltraLight™, Sculpsy® Kespsake Clay

### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:

None. In case of overheating material, turn off oven. Ventilate area by

opening nearest window. Seek fresh air, if fumes are inhaled.

**Environmental Precautions:** 

Contain spill.

Methods for Cleaning Up:

Collect and reuse or dispose with domestic refuse.

### 7. HANDLING AND STORAGE

Handling: Do not heat above 175°C (350°F), allow to come in contact with an open flame or use with a hot knife or wire. Use oven thermometer when hardening material in oven. Do not use microwave oven for baking. Do not overbake. Do not exceed the recommended baking temperature or time.

Wash hands with soap and water after use.

Store unused material in a cool, dry place preferably in a sealed non-reactive container.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Limits:** 

No threshold exposure limit values known.

Eye Protection:

Skin and Body Protection: n/a Respiratory Protection:

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Color:

Various

pH:

n/a

Appearance: Solid, malleable

Solubility in Water:

Not soluble

Odor:

Characteristic

Reactivity in Water:

Non-reactive

Boiling Point: n/a Melting Point: n/a

Specific Vapor Density (Air=1): n/a Vapor Pressure:

n/a

# 10. STABILITY AND REACTIVITY

Stability:

Product is stable.

Polymerization:

Not known to occur.

Hazardous Decomposition Products: Hydrochloric acid vapors

Materials to Avoid:

None

**Conditions to Avoid:** 

None when used as intended.

#### 11. TOXICOLOGICAL INFORMATION

Effects and Symptoms of Acute Exposure:

None expected.

Effects and Symptoms of Chronic Exposure: None expected.

Carcinogen Listing

NTP: No

IARC: No

OSHA: No

# 12. ECOLOGICAL INFORMATION

No harmful effects to the environment are known if material is used as intended and disposed of in the appropriate manner.

### 13. DISPOSAL CONSIDERATIONS

If recycling is not available, dispose with domestic refuse. Observe all federal, state and local regulations.

### 14. TRANSPORT INFORMATION

Not regulated by US DOT.

#### 15. REGULATORY INFORMATION

Material is non-hazardous and not to be labeled.

This product has been reviewed by a toxicologist and carries the AP seal.

The labeling conforms to ASTM D-4236.

### **16. OTHER INFORMATION**

n/a: not applicable

This MSDS applies to the following colors which are associated with hazardous and/or non-hazardous ingredients.

**Products Colors with Hazardous Ingredients** Original Sculpey® None None Sculpey III® Sculpey® MOLDMAKER™ & POLYMER CLAY CONDITIONER None Granitex™ None Premo! Sculpey® None Sculpey SuperFlex BAKE & BEND® None Amazing! Eraser Clay!® None Sculpey® UltraLight™ None

The MSDS supersedes a previous MSDS dated: 8/23/2007

Prepared by: K. Rausch 1/21/2008

The information contained herein is provided in good faith and is subject to change without notice. It is believed to be accurate and represents the best information currently available to us. However, we make no warranty, fitness for a particular purpose or of any other type, expressed or implied, with respect to products described or data or information provided. We assume no liability resulting from the use of such products, data or information. Users should determine the suitability of the information for their particular purpose. The user assumes all risk arising from their use of the material. The user is required to comply with all laws and regulations relating to the purchase, use, storage and disposal of the material and must be familiar with and follow generally accepted safe handling procedures.