

MATERIAL SAFETY DATA SHEET

NPCA, 1-7

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

000358

D. PREP. 4-15-85

Section I

MANUFACTURER'S NAME

SONNEBORN BUILDING PRODUCTS, REXNORD CHEMICAL PRODUCTS INC.

STREET ADDRESS

7711 Computer Avenue

CITY, STATE, AND ZIP CODE

Minneapolis, Minnesota 55435

EMERGENCY TELEPHONE NO.

612/835-3434

PRODUCT CLASS

MANUFACTURER'S CODE IDENTIFICATION

TRADE NAME

KURE-N-SEAL 0800

Product #496

Section II - HAZARDOUS INGREDIENTS

INGREDIENT	(CAS#)	PERCENT	TLV		LEL	VAPOR PRESSURE
			PPM	mg/m ³		
Xylene	(1330-20-7)	82	100		1.1	

Section III - PHYSICAL DATA

BOILING RANGE 135-145°C

VAPOR DENSITY



HEAVIER.



LIGHTER THAN AIR

EVAPORATION RATE



FASTER



SLOWER THAN ETHER

PERCENT VOLATILE BY VOLUME

85.3%

WEIGHT PER GALLON

7.57 lbs.

Section IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY

Flammable

FLASH POINT

81°

LEL 1.1

EXTINGUISHING MEDIA

Foam, carbon dioxide, dry chemical.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed container may explode when heated.

SPECIAL FIRE FIGHTING PROCEDURES

Contains solvents. Do not use water to extinguish fire.

KURE-N+SEAL 0800

Section V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE 100 PPM

EFFECTS OF OVEREXPOSURE

Inhalation: lightheadedness, dizziness, unconsciousness.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove patient to fresh air.

SKIN CONTACT: Wash thoroughly with soap and water.

EYE CONTACT: Flush with clean water for a minimum of 15 minutes.

INGESTION: DO NOT induce vomiting. CALL A PHYSICIAN IMMEDIATELY!

Section VI - REACTIVITY DATA

STABILITY ☐ UNSTABLE ☒ STABLE

CONDITIONS TO AVOID

INCOMPATIBILITY (Materials to avoid)

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION ☐ MAY OCCUR ☒ WILL NOT OCCUR

CONDITIONS TO AVOID

Section VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Avoid prolonged breathing of vapors. Remove sources of ignition. Blot up with paper or rags.

WASTE DISPOSAL METHOD

In accordance with federal, state and local regulations.

Section VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION

None required if ventilation is adequate. If used in confined areas with no ventilation, use NIOSH/MSHA approved organic vapor respirator such as 3M Brand #8712 or approved equal.

VENTILATION

Positive air ventilation. Use portable fans if working in small enclosed areas.

PROTECTIVE GLOVES

Rubber gloves

EYE PROTECTION

Goggles or face shield

OTHER PROTECTIVE EQUIPMENT

Section IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat, sparks, and open flame. Keep container tightly closed when not in use.

OTHER PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN.