## **MATERIAL SAFETY DATA SHEET**

PRODUCT NAME: Roberts 3300 Max Performance + Premium M/P Carpet & Sheet Vinyl Adhesive

PRODUCT USES: For installing a wide variety of floorcovering materials

W.H.M.I.S. CLASSIFICATION: NON-CONTOLLED

V.O.C. CONTENT: 0 calculated

**SECTION 1 - MANUFACTURER IDENTIFICATION** 

MANUFACTURER'S NAME: ROBERTS COMPANY CANADA LTD. ADDRESS: 2070 Steeles Ave. Bramalea, Ontario 16T 1A7

24 HOUR (CANUTEC) PHONE: (613) 996-6666

DATE REVISED: 06/01/02 NAME OF PREPARER: Peter Sharko

INFORMATION PHONE: (905) 791-4444

SOURCES USED: Raw material supplier M.S.D.S., US M.S.D.S.

SECTION II - HAZARDOUS INGREDIENTS INFORMATION

	COMPONENT	APPROX. %	UN#	CAS#	LD50	LC50
	NO REPORTABLE					
	INGREDIENTS					

SECTION III - PHYSICAL DATA

BOILING POINT: 100° C

FREEZING POINT: N/A

SPECIFIC GRAVITY (H20=1): 1.2

pH: 9-10

VAPOUR DENSITY (AIR=1);

Heavier than air

As for water.

**EVAPORATION RATE (BUTYL ACETATE=1): Slower** 

**VAPOUR PRESSURE (MM OF MERCURY):** 

EVAPORATION RATE (ETHYL ACETATE=1): Slower

**SOLUBILITY IN WATER:** 

Miscible

PERCENT VOLATILE: 34

APPEARANCE AND ODOUR: Beige, soft buttery paste, very mild resinous odour.

ODOUR THRESHOLD (PPM): Not available

SECTION IV - FIRE AND EXPLOSION DATA

FLASHPOINT (specify method): None

METHOD USED:

**IMPACT SENSITIVITY:** Insensitive

FLAMMABLE LIMITS (% BY VOLUME):

LOWER: N/A UPPER: N/A SENSITIVITY TO STATIC DISCHARGE: Insensitive

FIRE EXTINGUISHING MEDIA: Foam, CO2, Dry Chemical AUTO IGNITION TEMP: N/A TDG FLAMMABILITY CLASSIFICATION: Not requiated. SPECIAL FIRE-FIGHTING PROCEDURES: Self-contained breathing apparatus should be worn for fires involving this product.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION V - REACTIVITY DATA

STABILITY:

Stable

**CONDITIONS TO AVOID: Excessive Heat** 

INCOMPATIBILITY (Materials to avoid): Strong oxidizers and caustics

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2, and Hydrocarbons upon combustion.

HAZARDOUS POLYMERIZATION: Will not occur

**CONDITIONS TO AVOID: None** 

SECTION VI - TOXICOLOGICAL PROPERTIES			ENTRY ROUTE TABLE					
SKIN CONTACT		SKIN	EYE CONTACT		INHALATION ACUTE	INHALATION	INGESTION	
		ABSORPTION				CHRONIC	 [	

EFFECTS OF ACUTE EXPOSURE TO MATERIAL: Product may irritate eyes and skin. Ingestion causes vomiting, diarrhea, depressed respiration. EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: Skin chapping.

١	LD50 (SPECIFY SPECIES &	LC50 (SPECIFY SPECIES):	EXPOSURE LIMIT:	IRRITANCY:	
l	ROUTE):	Not available	Not available	None	
Į	Not available			1	
ſ	SENSITIZING CAPACITY:	CARCINOGENICITY:	REPRODUCTIVITY EFFECTS:	SYNERGISTIC MATERIALS:	
Į	None	None	None	None known	

SECTION VII - PREVENTATIVE MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE): None

VENTILATION: None should be required.

PROTECTIVE GLOVES: None

**EYE PROTECTION:** Goggles

OTHER PROTECTIVE EQUIPMENT: None required.

SPILL PROCEDURES: Mechanically collect. Wash area with water. Prevent from entering sewers or waterways. Spilled material may cause slippery conditions. Promptly report significant spills to appropriate authorities. Consult local regulations.

WASTE DISPOSAL METHOD: Destroy by incineration at an approved facility. Dried material only may be landfilled. Consult local regulations.

STORAGE & HANDLING PRECAUTIONS: Keep containers from excessive heat and freezing. Keep out of reach of children.

OTHER PRECAUTIONS: None.

## SECTION VIII - FIRST AID MEASURES

EYES: Flush with water for 20 minutes, holding eyelids open. Seek medical attention.

SKIN: Wash with soap and water, Seek medical attention if irritation develops.

INGESTION: Do not induce vomiting. If victim is conscious, give milk or water, Contact physician immediately.