•	1/10	1011		_		
* * * * * * * * * * * * * * * * * * * *	7-69	1174				
MATERIAL SAFETY DATA SHEET	FABRI	-PRINT	75-1	35(A-	-R)	
609	TRADE NA	AME ON LABEL	75-17 85-17	36 - 79	5-138	
ROCK PAINT DISTRIBUTING CORPORATION						
MANUFACTURER	MSDS NUMBER		97-5771(A-R) 97-5995, 97-6462			
365 SUNNYSIDE DR. P.O. BOX 482	<u> </u>	9 1-3 1-13, -17-8 180				
ADDRESS	CAS NUM					
MILTON, WI 53563		1 10, 1994	<u></u>			
	DATE PR	EPARED				
(608) 868-6873 (414) 563 8545				·		
PHONE NUMBER (FOR INFORMATION)	PREPARE				<u></u>	
SECTION 1 - MATERIAL IDENTIFICATION A	ND INFO	RMATION	T		· · · · · · · · · · · · · · · · · · ·	
COMPONENTS CHEMICAL NAME & COMMON NAMES		%	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMEN	
WATER LOW CROCK			_	- .		
AMMONIUM POLY ACRYLATE SALT						
NON-TOXIC COLORANT		,			, _	
ISOTHIAZOLINE		· · · · · · · · · · · · · · · · · · ·			· ·	
150 1111 2021 (3		<u></u>				
<u> </u>						
			, -			
AS PER ASTM D-4236 AND AS PER THE ART AND CRAFT M INSTITUTE (ACMI), INC. THIS PAINT HAS BEEN CERTIFIE						
SECTION 2 - PHYSICAL/CHEMICAL CHARACT	ERISTICS	3				
BOILING POINT ABOUT 212 F	SPECIFI	PECIFIC GRAVITY (H20 = 1) ABOUT 9 LBS/GAL				
VAPOR PRESSURE(mm Hg & TEMPERATURE) 17 mmHG ME		MELTING POINT 32 F				
VAPOR DENSITY (AIR=1) LIGHTER EV		EVAPORATION RATE (WATER=1) SLOWER				
SOLUBULITY IN WATER DILUTABLE	WATER	WATER REACTIVE N/A				
APPEARANCE & ODOR SLIGHT AMMONIA ODOR, OR NO ODO	OR PRESEN	T				
SECTION 3 - FIRE AND EXPLOSION HAZARD	DATA					
FLASH POINT & METHOD USED AUTO - IGNITION TEMPERATURE N/A	FLAMMABILI	TY LIMITS IN AIR N/A	% BY VOLUME	LEL	UEL	
EXTINGUISHER MEDIA FOAM, DRY CHEMICAL, CO2, WATER SPRAY	OR FOG					
SPECIAL FIRE FIGHTING PROCEDURES					· 	
N/A						
UNUSUAL FIRE AND EXPLOSION HAZARDS		<u></u>				
27/4			~ .	-1000		

			· 1			
SECTION 4 - REACTI	VITY HAZARD DATA					
STABILITY CONDITIONS TO UNSTABLE						
NCOMPATABILITY (MATERIALS TO AV	OID) NONE KOWN-HOWEVER PROD	UCT PROPERTIES MAY BE ALTERI	ED BY MIXING WITH SOME MATERIALS			
HAZARDOUS DECOMPOSITION PRODU	UCTS THERMAL DECOMPOSITION IN THE I	PRESENCE OF AIR MAY YIELD CARBO	N MONOXIDE AND/OR CARBON DIOXIDE			
HAZARDOUS POLYMERIZATION MAY OCCUR WILL NOT OCCUR	CONDITIONS TO AVOID)				
SECTION 5 - HEALTH	HAZARD DATA					
	ALATION INGESTION N ABSORTION NOT HAZARDOU	CARCINOGEN LISTED IN N	P GSHA RC MONOGRAPH NOT LISTED			
HEALTH HAZARDS	ACUTE					
	CHRONIC		,			
SIGNS AND SYMPTONS			<u> </u>			
MEDICAL CONDITIONS GENERALLY AGGI	RAVATED BY EXPOSURE					
EMERGENCY FIRST AID PROCEDURES - SEEK MEDICAL ASSISTANCE FOR FURTHER TREATMENT, OBSERVATION AND SUPPORT IF NECESSARY.						
EYE CONTACT WITH EMULSION MAY RESULT IN IRRITATION. FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN. REMOVE CONTACTS FROM VICTIM.						
SKIN CONTACT PROLONGED OR REPEATED CONTACT WITH EMULSION MAY CAUSE SOME SKIN IRRITATION. WASH SKIN THOROUGHLY WITH SOAP AND WATER; IF DRENCHED REMOVE AND WASH CLOTHING BEFORE REUSE.						
INHALATION N/A						
IF VICTIM IS CONSCIOUS, GIVE TWO GLASSES OF WATER TO DRINK AND CALL A PHYSICIAN.						
SECTION 6 - CONTROL	AND PROTECTIVE MEASU	JRES				
RESPIRATORY PROTECTION (SPECIFY)	TYPES)					
PROTECTIVE GLOVES RUBBER GLO	OVES RECOMMENDED	EYE PROTECTION CHEMICAL GOGGLES WITH EYE GUARD				
VENTILATION TO BE USED	LOCAL EXHAUST	MECHANICAL (GENERAL)	SPECIAL			
	OTHER (SPECIFY)					
OTHER PROTECTIVE CLOTHING AND EQUIPMENT N/A						
HYGIENIC WORK PRACTICES						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES						
STEPS TO BE TAKEN IF MATERIAL IS SPILED OR RELEASED ABSORB WITH DRYING MATERIAL OR FLUSH SPILLED MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINER. PREVENT SPILLED LIQUID FROM ENTERING SEWERS, STORM DRAINS, DRAINAGE SYSTEMS AND NATURAL WATERWAYS.						
WASTE DISPOSAL METHODS						
DISPOSE OF PRODUCT IN ACCORDANCE WITH APPLICABLE LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.						
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE SHOULD BE STORED AT ROOM TEMPERATURE TO PROLONG SHELF LIFE. KEEP FROM FREEZING AND AWAY FROM EXCESSIVE HEAD						
OTHER PRECAUTIONS AND/OR SPECIAL	L HAZAROS					