

MATERIAL SAFETY DATA SHEET

SECTION I

000352

PRODUCT NAME OR NUMBER Graffiti Gobbler Paint & Ink 100,200		EMERGENCY TELEPHONE NO. 313-521-1600
MANUFACTURER'S NAME Semoco Petroleum Corporation		MANUFACTURER'S D-U-N-S NO. N/A
ADDRESS (Number, Street, City, State and Zip Code) 11555 Whittier Detroit, MI 48224		
HAZARDOUS MATERIALS DESCRIPTION AND PROPER SHIPPING NAME(49 CFR 172.101) N/A		HAZARD CLASS (49 CFR 172.101) N/A
CHEMICAL FAMILY Solvent	FORMULA Paint & Ink Remover	

SECTION II — INGREDIENTS (list all ingredients)

		CAS REGISTRY NO.	%
Glycol Ether	Less than	N/A	50
Alifatic Solvent	Less than	N/A	20
Aromatic Solvent	Less than	N/A	20
Potassium Hydroxide	Less than	N/A	5
Acetate Solvent	Less than	N/A	10
Ketone	Less than	N/A	10
Oleic	Less than	N/A	5

SECTION III — PHYSICAL DATA

BOILING POINT (°F) (°C) over	320°	SPECIFIC GRAVITY (H ₂ O=1)	.897-.96	
VAPOR PRESSURE (mm Hg) ☒ (psi) ☐	1.4	PERCENT VOLATILE BY VOLUME (%)	93-96%	
VAPOR DENSITY (AIR=1)	Unknown	EVAPORATION RATE (Butly =1) Acct	0.2	
SOLUBILITY IN WATER Emulsifiable		pH=	Unknown	
APPEARANCE AND ODOR			IS MATERIAL: LIQUID SOLID GAS PASTE POWDER	

SECTION IV-FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (method used) (°F) (°C)	130° Tag closed cup	FLAMMABLE LIMITS	LEL	UEL
EXTINGUISHING MEDIA Chemical Extinguisher-Foam				
SPECIAL FIRE FIGHTING PROCEDURES Apply dry Chemical or Foam-CO ₂ -water				
UNUSUAL FIRE AND EXPLOSION HAZARDS N/A				

MAINTENANCE PRODUCTS
& EQUIPMENT COMPANY
 By Weinheimer
 709 Erie Blvd. West
 Syracuse, NY 13204
 1-315-475-6301

SECTION V-HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE Causes light-headiness	THRESHOLD LIMIT VALUE ☐ PERMISSIBLE EXPOSURE LIMIT ☐
EMERGENCY AND FIRST AID PROCEDURES REMOVE TO OPEN AIR-DO NOT INDUCE VOMITING-GIVE MILK FLUSH EYES WITH WATER FOR 15 MINUTES	

